

READ AND UNDERSTAND MATERIAL SAFETY DATA SHEET BEFORE HANDLING OR DISPOSING
OF PRODUCT

MSDS CODE AND NAME : **GRADE 40 EXPANDABLE POLYSTYRENE (EPS)**
DATE ISSUED : **9/20/2005**
DATE PRINTED : **9/20/2005**

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MATERIAL IDENTITY**MSDS CODE AND NAME****GRADE 40 EXPANDABLE POLYSTYRENE (EPS)****Chemical Name and/or Family or Description:****Chemical Name:** Polystyrene thermoplastic polymer**Synonym(s):** Modified EPS**Molecular Formula:** (C₈H₈)_x**COMPANY INFORMATION**

Huntsman Corporation
P.O. Box 4980
The Woodlands, TX 77387-4980

TELEPHONE NUMBERS

Transportation Emergency

Company: (800) 328-8501

CHEMTREC: (800) 424-9300

Medical Emergency: (409) 722-9673 (24 Hour)

General MSDS Assistance: (281) 719-6432

Technical Information: (800) 972-1010

2. COMPOSITION AND INFORMATION ON INGREDIENTS

THE CRITERIA FOR LISTING COMPONENTS IN THE COMPOSITION SECTION ARE AS FOLLOWS: CARCINOGENS ARE LISTED WHEN PRESENT AT 0.1 % OR GREATER; COMPONENTS WHICH ARE OTHERWISE HAZARDOUS ACCORDING TO OSHA ARE LISTED WHEN PRESENT AT 1.0 % OR GREATER; NON-HAZARDOUS COMPONENTS ARE LISTED AT 3.0 % OR GREATER. THIS IS NOT INTENDED TO BE COMPLETE COMPOSITIONAL DISCLOSURE. REFER TO SECTION 14 FOR APPLICABLE STATES' RIGHT TO KNOW AND OTHER REGULATORY INFORMATION.

Product and/or Component(s) Carcinogenic According to:

OSHA___ IARC___ NTP___ OTHER___ NONE_ X__**Composition:**

Chemical Name	CAS Number	Exposure Limits	Range in %
Benzene, ethenyl-, homopolymer			≥92.6
Pentane	109-66-0	600 ppm TWA ACGIH 1000 ppm TWA OSHA 750 ppm STEL OSHA 120 ppm TWA (Canada) 350 mg/m ³ TWA (Canada)	≤7

* May contain trace amounts of styrene. See Section 11 for additional information.

MSDS CODE AND NAME : **GRADE 40 EXPANDABLE POLYSTYRENE (EPS)**
DATE ISSUED : **9/20/2005**
DATE PRINTED : **9/20/2005**
COMPANY : **HUNTSMAN**

3. HAZARD IDENTIFICATION

EMERGENCY OVERVIEW

Appearance:

Solid, white beads

Odor:

Slight hydrocarbon odor

WARNING STATEMENT


DANGER!

EXTREMELY FLAMMABLE VAPOR
 VAPOR MAY CAUSE FLASH FIRE
 VAPOR MAY CAUSE DIZZINESS AND DROWSINESS
 VAPOR MAY CAUSE IRRITATION TO EYES AND RESPIRATORY TRACT

Hazardous Material Information System (United States)

Health	1
Fire	3
Reactivity	0
Personal protection	○

National Fire Protection Association NFPA (United States)



POTENTIAL HEALTH EFFECTS

Primary Route of Exposure

Eye X Skin X Inhalation X Ingestion

Effects of Overexposure

Acute:

Eyes:

Vapor may cause irritation, experienced as discomfort, with excess tear production and blinking, and seen as excess redness of the eye. Product may contain residual amounts of dust or small particulates which may cause eye irritation or abrasion experienced as mild discomfort and slight excess redness of the eye.

Skin:

Product may contain residual amounts of dust or small particulates that may cause skin irritation or abrasion experienced as local redness with possible mild discomfort.

Inhalation:

Vapors or mist may cause irritation of the nose and throat. Inhalation may cause dizziness, drowsiness, euphoria, loss of coordination, disorientation, headache, nausea, and vomiting. In poorly ventilated areas or confined spaces, unconsciousness and asphyxiation may result. Prolonged or repeated overexposure may result in the absorption of potentially harmful amounts of material.

Dust may cause irritation of the nose and throat. Overexposure to high concentrations of dust may cause respiratory irritation, experienced as coughing and difficulty breathing.

Ingestion:

If more than several mouthfuls are swallowed, abdominal discomfort, nausea, and diarrhea may occur.

Sensitization Properties:

Unknown

Chronic:

Prolonged or repeated inhalation of dust or particulates may impair lung function or cause lung damage.

Medical Conditions Aggravated by Exposure:

Overexposure to vapor, dust or mist may aggravate existing respiratory conditions, such as asthma, bronchitis, and inflammatory or fibrotic respiratory disease.

MSDS CODE AND NAME : **GRADE 40 EXPANDABLE POLYSTYRENE (EPS)**
DATE ISSUED : **9/20/2005**
DATE PRINTED : **9/20/2005**
COMPANY : **HUNTSMAN**

Other Remarks:

None

4. FIRST AID MEASURES

Eyes:

Flush eyes with plenty of water for several minutes. Remove larger particulates from the eye as one would any foreign object. Get medical attention if eye irritation persists or particulates are difficult to remove from the eye.

Skin:

Wash skin with plenty of soap and water for several minutes. Get medical attention if skin irritation develops or persists.

Ingestion:

If more than several mouthfuls of this material are swallowed, give two glasses of water (16 oz.). Get medical attention.

Inhalation:

If inhaled, remove to fresh air. If not breathing, clear person's airway and give artificial respiration. If breathing is difficult, qualified medical personnel may administer oxygen. Get medical attention immediately.

Other Instructions:

None.

5. FIRE-FIGHTING MEASURES

Ignition Temperature - AIT (degrees C):

260 (500 F) for Pentane
471 (880 F) by ASTM D-1929 Expanded polystyrene

Flash Point (degrees C):

-40 (-40 F) CC for Pentane

Flammable Limits % (Lower-Upper):

Lower: 1.5 for Pentane
Upper: 7.8 for Pentane

Recommended Fire Extinguishing Agents And Special Procedures:

Water may be ineffective on flames but should be used to cool fire-exposed containers and provide protection for persons attempting to stop the leak. Use water spray, dry chemical, foam or carbon dioxide to extinguish flames.

Unusual or Explosive Hazards:

Danger! Extremely flammable materials may release vapors that travel long distances, ignite, and flash back. Containers may explode in a fire. Do not expose to heat, sparks, flame, static, or other sources of ignition. When handling, use non-sparking tool, ground and bond all containers.

Explosive air-vapor mixtures may form. Fire gives off dense black smoke and acid gasses. Electrostatic discharge can be a source of ignition due to accumulated pentane vapors exceeding the L.E.L. (lower explosive limit) of 1.5% (15,000 ppm). Pentane vapors may be emitted from newly opened containers or when the product is heated. If ignited, there could be a very high rate of flame propagation.

"NO SMOKING - NO MATCHES - NO LIGHTERS - NO WELDING" rules should be enforced.

Special Protective Equipment for Firefighters:

Wear full protective clothing and positive pressure breathing apparatus.

MSDS CODE AND NAME : **GRADE 40 EXPANDABLE POLYSTYRENE (EPS)**
DATE ISSUED : **9/20/2005**
DATE PRINTED : **9/20/2005**
COMPANY : **HUNTSMAN**

6. ACCIDENTAL RELEASE MEASURES (Transportation Spills: CHEMTREC (800)424-9300)

Procedures in Case of Accidental Release, Breakage or Leakage:

Avoid the generation of dust clouds. Place in appropriate containers for disposal or recycle. Avoid breathing dust. Pressure demand air supplied respirators should always be worn when the airborne concentration of the contaminant or oxygen is unknown. Otherwise, wear respiratory protection and other personal protective equipment as appropriate for the potential exposure hazard. Wear gloves, goggles, and protective clothing to avoid contact with eyes, skin, or clothing. Use vacuuming or sweeping compound for clean-up. Do not dry sweep or use methods which increase dusting. Prevent entry into sewers and waterways.

7. HANDLING AND STORAGE

Precautions to be Taken in

Handling:

Use spark-proof tools. Material may be at elevated temperatures and/or pressures. Exercise care when opening bleeders and sampling ports.

Storage:

Ground and bond shipping container, transfer line, and receiving container. Keep away from heat, sparks, flame, and other sources of ignition.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Protective Equipment (Type)

Eye/Face Protection:

Avoid eye contact. Chemical type goggles should be worn. Do not wear contact lenses.

Skin Protection:

Workers should wash exposed skin several times daily with soap and water. Soiled work clothing should be laundered or dry-cleaned.

Respiratory Protection:

Airborne concentrations should be kept to lowest levels possible. If vapor, mist or dust is generated and the occupational exposure limit of the product, or any component of the product, is exceeded, use appropriate NIOSH or MSHA approved air purifying or air supplied respirator after determining the airborne concentration of the contaminant. Air supplied respirators should always be worn when airborne concentration of the contaminant or oxygen content is unknown.

Ventilation:

Use explosion-proof equipment to maintain adequate ventilation to meet occupational exposure limits, if applicable (see below), prevent accumulation of explosive air-gas mixtures, and avoid significant oxygen displacement. Oxygen levels should be at least 19.5% in confined spaces or other work areas (OSHA value).

Exposure Limit for the Total Product:

None established for product; refer to Section 2 for component exposure limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:

Solid, white beads

Odor:

Slight hydrocarbon odor

MSDS CODE AND NAME : **GRADE 40 EXPANDABLE POLYSTYRENE (EPS)**
DATE ISSUED : **9/20/2005**
DATE PRINTED : **9/20/2005**
COMPANY : **HUNTSMAN**

Boiling Point (degrees C):

Not applicable

Melting/Freezing Point (degrees C):

Softens and expands at 93.3-101.7 C (200-215 F)

Specific Gravity (water=1):

Depending on bulk density of the product, the material may float on top of water.

pH:

Not applicable.

Vapor Pressure:

Negligible

Viscosity:

Not applicable

VOC Content:

Not determined.

Vapor Density (Air=1):

>1

Solubility in Water (%):

< 0.1

Other:

None

10. STABILITY AND REACTIVITY

This Material Reacts Violently With:

Air___ Water___ Heat X Strong Oxidizers X Others___ None of these___

Comments:

None

Products Evolved When Subjected to Heat or Combustion:

Toxic levels of carbon monoxide, carbon dioxide, irritating aldehydes and ketones.

Hazardous Polymerizations:

DO NOT OCCUR

11. TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION (ANIMAL TOXICITY DATA)

Oral:

LD50 Believed to be > 5.00 g/kg (rat) practically non-toxic

Inhalation:

Not determined.

Dermal:

LD50 Believed to be > 2.00 g/kg (rabbit) practically non-toxic

IRRITATION INDEX, ESTIMATION OF IRRITATION (SPECIES)

MSDS CODE AND NAME : **GRADE 40 EXPANDABLE POLYSTYRENE (EPS)**
DATE ISSUED : **9/20/2005**
DATE PRINTED : **9/20/2005**
COMPANY : **HUNTSMAN**

Skin:

(Draize) Believed to be > .50 - 3.00 /8.0 (rabbit) slightly irritating

Eyes:

(Draize) Believed to be > 15.00 - 25.00 /110 (rabbit) slightly irritating

Sensitization:

Not determined.

Other:

Product may contain dust or particulates that may cause eye irritation or abrasion.

This product may contain residual styrene. Typical concentrations are less than 0.1%. Please refer to product-specific purchasing specifications for information on residual styrene content of this product.

Chronic (lifetime) exposure to styrene resulted in bronchoalveolar (lung) tumors in mice, but not in rats. The relevance of these cell-type specific mouse lung tumors to humans is not known. Nasal effects were also observed in these rats and mice exposed to styrene. In subchronic exposure studies, repeated exposures of female mice to styrene resulted in liver toxicity, however, this effect was not observed in rats.

12. DISPOSAL CONSIDERATIONS:

Waste Disposal Methods:

This material should be disposed of in accordance with local, state and federal regulations.

Remarks:

Do not allow to enter drains or sewers.

13. TRANSPORT INFORMATION

Transportation

DOT:

Proper Shipping Name:

Polymeric beads, expandable

Hazard Class:

9

Identification Number:

UN 2211

Packing Group:

III

Label Required:

Class 9

IMDG

Proper Shipping Name:

Polymeric beads, expandable

Hazard Class

9

Identification Number

UN 2211

Packing Group

III

MSDS CODE AND NAME : **GRADE 40 EXPANDABLE POLYSTYRENE (EPS)**
DATE ISSUED : **9/20/2005**
DATE PRINTED : **9/20/2005**
COMPANY : **HUNTSMAN**

Label Required
Class 9 (See Section 16 for additional information)

ICAO

Proper Shipping Name:
Polymeric beads, expandable

Hazard Class
9

Identification Number
UN 2211

Packing Group
III

Label Required
Class 9 (See Section 16 for additional information)

TDG

Proper Shipping Name:
Polymeric beads, expandable

Hazard Class:
9

Identification Number:
UN 2211

Label Required:
Class 9 (per UN recommendations, black vertical stripes)

14. REGULATORY INFORMATION

Federal Regulations:

SARA Title III:

Section 302/304 Extremely Hazardous Substances

Chemical Name	CAS Number	Range in %	TPQ	RQ
None.				

Section 311 Hazardous Categorization:

Acute X Chronic X Fire X Pressure Reactive N/A

Section 313 Toxic Chemical

Chemical Name	CAS Number	Concentration
Styrene (residual)	100-42-5	0 - 0.3

CERCLA 102(a)/DOT Hazardous Substances:

Chemical Name	CAS Number	Range in %	RQ
Styrene (residual)	100-42-5	0 - 0.3	1000

States Right-to-Know Regulations:

Chemical Name	State Right-to-know
Pentane	FL, MA, MN, NJ, PA, RI
Styrene (residual)	CT, FL, IL, MA, MI, MN, NJ, PA, RI

California Prop. 65:

The following detectable components of this product are substances, or belong to classes of substances, known to the State of California to cause cancer and/or reproductive toxicity.

MSDS CODE AND NAME : **GRADE 40 EXPANDABLE POLYSTYRENE (EPS)**
DATE ISSUED : **9/20/2005**
DATE PRINTED : **9/20/2005**
COMPANY : **HUNTSMAN**

Chemical Name

None.

CAS Number

INTERNATIONAL REGULATIONS:

TSCA Inventory Status:

This product, or its components, are listed on, or are exempt from the Toxic Substance Control Act (TSCA) Chemical Substance Inventory.

WHMIS Classification:

Not determined.

Canadian Inventory Status:

This product, or its components, are listed on or are exempt from the Canadian Domestic Substance List (DSL).

EINECS Inventory Status:

This product, or its components, are listed on or are exempt from the European Inventory of Existing Chemical Substances (EINECS) or the European List of Notified Chemical Substances (ELINCS).

Australian Inventory Status:

This product, or its components, are listed on or are exempt from the Australian Inventory of Chemical Substances (AICS).

Japan Inventory Status:

This product, or its components, are listed on or are exempt from the Japanese Ministry of International Trade and Industry (MITI) inventory.

15. ENVIRONMENTAL INFORMATION

Aquatic Toxicity:

Not applicable.

Mobility:

Not applicable.

Persistence and Biodegradability:

This product is expected to persist in the environment.

Potential to Bioaccumulate:

Not applicable.

Remarks:

Sewer/waterways obstruction; fish may eat beads and obstruct their digestive tract.

16. OTHER INFORMATION 9/20/2005

European, ADR regulations require additional marking (see item 2912) "Keep Away From Any Source of Ignition." Vessel carriers request marking warning "No Smoking or Open Flame" on box doors.

Supersedes: 3/31/2003

The following sections have been revised: 2, 11, 14

Date Issued: 9/20/2005.

MSDS CODE AND NAME : **GRADE 40 EXPANDABLE POLYSTYRENE (EPS)**
DATE ISSUED : **9/20/2005**
DATE PRINTED : **9/20/2005**
COMPANY : **HUNTSMAN**

THE INFORMATION IN THIS DATA SHEET IS PROVIDED INDEPENDENTLY OF ANY SALE OF THE PRODUCT. IT IS PROVIDED FOR THE PURPOSE OF HAZARD COMMUNICATION AS PART OF HUNTSMAN'S PRODUCT SAFETY PROGRAM. IT IS INTENDED ONLY AS A GUIDE TO THE APPROPRIATE PRECAUTIONARY HANDLING OF THE PRODUCT BY A PROPERLY TRAINED PERSON. YOU ARE ENCOURAGED AND REQUESTED TO ADVISE THOSE WHO MAY COME IN CONTACT WITH SUCH PRODUCTS OF THE INFORMATION CONTAINED HEREIN. THE DATA RELATES ONLY TO THE SPECIFIC PRODUCT DESIGNATED, AND DOES NOT RELATE TO USE OF THE PRODUCT IN COMBINATION WITH ANY OTHER MATERIAL OR USE OF THE PRODUCT IN ANY PROCESS. THE DATA IS NOT INTENDED TO CONSTITUTE PERFORMANCE INFORMATION CONCERNING THE PRODUCT. NO EXPRESS WARRANTY, OR IMPLIED WARRANTY OF MERCHANTABILITY FOR FITNESS FOR A PARTICULAR PURPOSE IS MADE WITH RESPECT TO THE PRODUCT, ITS COMPOSITION, ITS SAFETY OR THE INFORMATION CONTAINED IN THIS DATA SHEET.

TO DETERMINE THE APPLICABILITY OR THE EFFECTS OF ANY LAW OR REGULATION WITH RESPECT TO THE PRODUCT, THE USER SHOULD CONSULT A LEGAL ADVISOR OR THE APPROPRIATE GOVERNMENT AGENCY. HUNTSMAN DOES NOT UNDERTAKE TO FURNISH ADVICE ON SUCH MATTERS.

CURRENT DATA SHEETS ARE AVAILABLE FOR ALL HUNTSMAN PRODUCTS. YOU ARE URGED TO OBTAIN DATA SHEETS FOR ALL HUNTSMAN PRODUCTS YOU BUY, USE OR DISTRIBUTE BY CALLING (281) 719-6432 OR DIRECTING YOUR INQUIRIES TO:

**HUNTSMAN
MANAGER, PRODUCT SAFETY
P.O. BOX 4980
THE WOODLANDS, TX 77387-4980**

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE. NO PART OF THIS DATA SHEET MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM, OR BY ANY MEANS, WITHOUT PERMISSION IN WRITING FROM HUNTSMAN. ALL REQUESTS FOR PERMISSION TO REPRODUCE MATERIAL FROM THIS DATA SHEET SHOULD BE DIRECTED TO HUNTSMAN, MANAGER, PRODUCT SAFETY AT THE ABOVE ADDRESS.

COPYRIGHT © BY HUNTSMAN CORPORATION. ALL RIGHTS RESERVED.