

Underlayments and Toppings

	Features	Level Set 100	Level Set 200	Level Set 300	Level Set LW-60**	Level Set G	Level Set Wear Topping***	Trowel Grade Underlayment	Feather Edge	Floor Patch
Features	Vertical / Overhead / Horizontal	H	H	H	H	H	H	H	H	H
	Interior/Exterior	Interior	Interior	Interior	Interior	Interior	Interior	Interior	Interior	Interior / Exterior
	Accepts Tile & Stone Installations	24 hrs.	3 to 4 hrs.	3 to 4 hrs.	3 to 4 hrs.	4 hrs.	3 to 4 hrs.	90 min.	30 min.	1 hr.
	Accepts Moisture-sensitive Floor Coverings	72 hrs.	16 hrs.	16 hrs.	16 hrs.	16 hrs.	16 hrs.	4 hrs.	30 min.	2 hrs.
Special Additives	Polymer Modified	●	●	●	●	●	●	●	●	●
Placement	Thickness	Feather edge to 5"*	Feather edge to 5"*	Feather edge to 5"*	Feather edge to 2"	1/8" to 5"*	1/4" to 5"*	Feather edge to 2"	Feather edge to 1/2"	Feather edge to 2"
	Working time (min, @ 70° F)	20	30	30	30	30	30	15	10-20	10-15
	Trowel, Pump or Pour Apply	Pump / Pour	Pump / Pour	Pump / Pour	Pump / Pour	Pump / Pour	Pump / Pour	Trowel	Trowel	Trowel
Compressive Strength	24 hours (psi)	1,700	3,000	3,000	2,000	2,000	3,500	2,000	2,100	1,300
	28 days (psi)	5,500	5,100	5,200	4,000	4,500	6,000	5,000	4,700	2,650

* Must be extended with aggregate

** Lightweight

*** Stainable