



# Technical Bulletin

2400 Boston Street, Suite 200, Baltimore, Maryland 21224  
Phone: 410-675-2100 or 800-543-3840

Revised: 5/30/01

## DAP® EASY SOLUTIONS □ DryDex □ Spackle

UPC Number: 12334

- For repairing holes and cracks in walls, ceilings and woodwork.
- Goes on pink and dries white.
- Interior/exterior use.
- Easy water clean-up.

**Packaging:** 4 fluid ounces (118 ml)

**Color:** White (Pink when applied, white when fully dried.)

### Company Identification:

Manufacturer: DAP Inc., 2400 Boston St., Baltimore, Maryland 21224

Usage Information: DAP HELPLINE: 888-DAP-TIPS, 9:00 am to 7:00 pm EST.

Order Information: 800-327-3339

Also, visit the DAP website at [www.dap.com](http://www.dap.com).

### Product Description:

DAP® Easy Solutions □ DryDex Spackle is a premium quality, ready to use formula for repairing holes and cracks in walls, ceilings and woodwork. It spreads easily for fast, professional repairs that will not crack, crumble or flake. Contains unique patent pending Dry Time Indicator that verifies when patched surface is dry and ready to be sanded and painted. Goes on pink and dries white. Interior/exterior use. When used for exterior applications, surface must be painted. Safe, latex-based formula allows for easy water clean-up.

### Suggested Uses:

*Ideal for: Repairing* holes and cracks in walls, ceilings and woodwork.

*Adheres To:* Drywall, plaster, wood, brick, concrete, stucco

### Performance Characteristics:

- Unique Dry Time Indicator - Goes on pink, dries white when ready to be sanded or painted.
- Ready to use □ needs no mixing or additives.
- Spreads easily.
- Won't crack, crumble or flake.
- Water clean-up.

# DAP® EASY SOLUTIONS □ DryDex □ Spackle

## **Surface Preparation & Application:**

- 1) Surface must be clean, dry and free of all loose paint, plaster and dirt.
- 2) Knead tube.
- 3) Remove cap and cut nozzle to desired bead size.
- 4) Squeeze spackle into crack or hole. Smooth surface with a putty knife.
- 5) For deep repairs, apply 2 or more layers of spackle, allowing to dry between applications.
- 6) DryDex □ Spackle will change color to white when surface can accept second application or is ready to be sanded or painted. Exterior surfaces must be painted after product is completely cured.
- 7) Clean tools immediately with water.
- 8) Reseal tube with cap for future use.

## ***For Best Results:***

- Use in temperatures between 50 F - 90° F. Dry time will be longer in cool and humid conditions.
- Store away from extreme heat or cold.
- When using for exterior applications, surface must be painted.
- Do not use as a skimcoat for smoothing large, rough surfaces.

## **Physical & Chemical Characteristics:**

Vehicle:	Acrylic Latex
Volatile:	20-25%
Solids:	75-80%
Weight Per Gallon:	15.50 lbs.
Service Temperature:	Full range of outdoor temperatures (0-150° F)
Freeze/Thaw Stability:	Stable □ 5 cycles
Consistency:	Thick paste
Applications:	Interior/Exterior
Shelf Life:	12 □ 18 months
MSDS No:	10421

## **Clean Up:**

Clean tools immediately with water.

## **Safety:**

See product label or Material Safety Data Sheet for safety information. You can request an MSDS sheet by calling 888-DAP-TIPS or by visiting our website at [www.dap.com](http://www.dap.com).

## **Warranty Information:**

If not satisfied with product performance when used as directed, return used container and sales receipt to DAP Inc., Technical Customer Service, 2400 Boston St., Baltimore, MD, 21224, for product replacement or, at DAP's discretion, sales price refund. DAP will not be liable for incidental or consequential damage.