



Technical Bulletin

2400 Boston Street, Suite 200, Baltimore, Maryland 21224
Phone: 410-675-2100 or 800-543-3840

Revised: 5/20/2005

DAP® CrackSHOT® Spackling Paste

- High performance, knife-grade formula
- Ideal for dents in metal doors & trim
- No shrinking
- Sands effortlessly
- Unsurpassed paintability – won't flash paint
- Interior/exterior use

Packaging: 5.5 fl. oz. squeeze tube, 1/2 pint tub, 1 quart tub, 1 gallon tub
Color: White
UPC Numbers: 70798 12374, 12378, 12380, 12372

Company Identification:

Manufacturer: DAP Inc., 2400 Boston Street, Baltimore, Maryland 21224
Usage Information: DAP HELPLINE: 888-DAP-TIPS, 9:00 am to 7:00 pm EST.
Order Information: 800-327-3339
Fax Number: 410-534-2650
Also, visit the DAP website at www.dap.com.

Product Description:

DAP® CrackSHOT® Spackling Paste is a high performance spackling for filling holes and cracks in surfaces such as drywall, plaster, wood, brick and stone. It can even be used for filling dents in metal doors and trim. Its ready-to-use smooth, white formula spreads easily for fast, professional repairs that will not crack, crumble or flake. It has a de-aired texture for excellent tooling and easy smoothing to a feather edge. CrackSHOT® sands effortlessly. It can even be finger sanded – no sandpaper needed when sanding small nail holes or hammer dents in drywall. Just use finger to smooth dried spackling before painting. CrackSHOT® provides unsurpassed paintability. It does not flash or gloss low sheen/flat paint. It accepts paint like bare drywall or other porous surfaces and provides a very smooth surface that disappears when painted. CrackSHOT® cures quickly, but has a long working time and will not gum up on knife. It can be used indoors or out.

Suggested Uses:

Ideal for filling holes, cracks, dents and defects on:

- Drywall/plaster
- Wood
- Brick
- Stone
- Metal doors and trim

Surface Preparation & Application:

- Surface must be clean, dry and free of foreign material.
- Stir thoroughly before use. If using squeezing tube, knead tube before use and cut nozzle to desired opening size.
- Apply with a clean putty knife.
- For a smoother finish, dip putty knife in water and lightly smooth spackling.

- One application is usually sufficient for small repairs. For repairs deeper than 1/4", apply two or more layers allowing spackling to dry between applications.
- May be sanded or painted in 1 to 5 hours depending on temperature, humidity and depth of fill. Wet sanding is recommended to avoid generation of dust.
- Clean tools immediately with water.
- Ensure that CrackSHOT® Spackling Paste is thoroughly dry before sanding or applying oil-based paint. Spackling may be painted immediately upon drying with a quality latex paint.

For Best Results:

- Do not apply when temperatures are below 50°F.
- Do not apply outside if rain is expected within 24 hours.
- Do not use on floors or as a caulk, sealant or joint filler over cracks and joints where expansion and contraction may occur.
- **DO NOT USE AS A SKIM COAT.**
- For exterior applications, always topcoat with a quality paint.
- If a textured finish is desired, add clean sand to spackling compound prior to application.
- Do not use for tuck pointing applications on brick.
- For larger areas to be patched on bare concrete, use a latex fortified Portland cement-based dry mix.

Physical & Chemical Characteristics:

Consistency:	Paste
Vehicle:	Acrylic polymer
Volatile:	Water
Filler:	Inert filler
Odor:	Slight acrylic
Weight/Gallon:	15.9 ± 0.3 pounds
Solids:	80% by weight
Application Temperature:	50°F or higher
Service Temperature:	0°F to 150°F
Shelf Life:	1 Year
Freezing:	Freeze/thaw stable 5 cycles at 0°F
Drying Time:	1 to 5 hours depending on temperature, relative humidity and depth of fill.
MSDS No.:	00010415001

Clean Up & Storage:

Wash tools immediately after use with water. Be sure container lid/cap is closed and tightly sealed. Store in a cool, dry place.

Safety:

See product label and Material Safety Data Sheet (MSDS) for safety information. You can request an MSDS by visiting our website at www.dap.com or by calling 888-DAP-TIPS.

Satisfaction Guaranteed:

If you are not satisfied with this product's performance when used as directed, return used container and sales receipt to DAP Inc., Technical Customer Service, 2400 Boston Street, Suite 200, Baltimore, MD 21224 for product replacement or sales price refund. DAP will not be liable for incidental or consequential damages.