

Description

Masterseal DR 1 fleece is a polypropylene drainage fleece with one hydrophobe side (hydrophile side with lettering). It is used in combination with a water-proofing membrane system.

Applications

Recommended for use in:

- Combination with a waterproofing membrane
- Use in lieu of plastic sheeting to divert running water

MASTERSEAL® DR 1

Drainage Fleece

Performance Characteristics

Setting time

Material	100% polypropylene, with black PE sheet; 0.2 mm (200 u)
Unit weight in lb/ft ² (g/m ²) approximate	1.1 (500)
Thickness in in. (mm) approximate	0.25 (4)
Tensile failure strain in % (DIN 53 857)	
● Lengthwise	100% ±10
● Widthwise	100% ±10
Tensile strength in psi (kN/m) (DIN 53 857)	
● Lengthwise	1.45 (10)
● Widthwise	1.885 (13)

Storage and Handling

Storage Temperature: Masterseal DR 1 fleece should be stored in a dry place.

Handling: Masterseal DR 1 fleece contains no hazardous materials and is completely transport class free. No safety precautions required.

Packaging

Masterseal DR 1 is delivered on rolls.

Roll length: min 164 ft (50 m) or on demand.

Roll width: 78.75 in (2 m).

Related Documents

Material Safety Data Sheets: Masterseal DR 1 fleece.

Product Data: MASTERSEAL® DR1

Additional Information

For additional information on Masterseal DR 1 fleece, contact your local sales representative.

The Admixture Systems business of BASF Construction Chemicals is a leading provider of innovative admixtures for specialty concrete used in the ready-mixed, precast, manufactured concrete products, underground construction and paving markets throughout the North American region. The Company's respected Master Builders brand products are used to improve the placing, pumping, finishing, appearance and performance characteristics of concrete.

LIMITED WARRANTY NOTICE. We warrant our products to be of good quality and will replace or, at our discretion, refund the purchase price of any products proved defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. Therefore, except for such replacement or refund, BASF MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY, RESPECTING ITS PRODUCTS, and BASF shall have no other liability with respect thereto. Any claims regarding product defect must be received in writing within one (1) year from the date of shipment. User shall determine the suitability of the products for the intended use and assume all risks and liability in connection therewith. Any authorized change in the printed recommendations concerning the use of our products must bear the signature of the BASF Technical Manager.

This information and all further technical advice are based on BASF's present knowledge and experience. However, BASF assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights. BASF SHALL NOT BE RESPONSIBLE FOR CONSEQUENTIAL, INDIRECT OR INCIDENTAL DAMAGES (INCLUDING LOSS OF PROFITS) OF ANY KIND. BASF reserves the right to make any changes according to technological progress or further developments.

For Professional use only. Not for sale to or use by the general public.

BASF Construction Chemicals
Admixture Systems

www.masterbuilders.com
www.meyco.basf.com

United States 23700 Chagrin Boulevard, Cleveland, Ohio 44122-5544 ● Tel: 800 628-9990 ● Fax: 216 839-8821
Canada 1800 Clark Boulevard, Brampton, Ontario L6T 4M7 ● Tel: 800 387-5862 ● Fax: 905 792-0651

©Construction Research & Technology GMBH

© BASF Construction Chemicals, 2009 ● Printed in USA ● 10/09 ● LIT # 1023950

