

MBT X-POZ-R ALL COLORS (FORMERLY: PRECO X-POZ-R ALL COLORS)

Version 2.1

7/3/06

1. **COMPANY AND PRODUCT INFORMATION**

Company : BASF Building Systems, Inc.
889 Valley Park Drive
Shakopee, MN 55379

Phone : 952-496-6000
Fax :
Emergency contact : 1-800-424-9300

Productname : MBT X-POZ-R ALL COLORS (FORMERLY: PRECO X-POZ-R ALL COLORS)
MSDS : 10405

2. **HAZARDOUS INGREDIENTS:** CASNO TLV STEL PEL CONTENT EXPOSURE LIMITS*

None by reference to: 1) OSHA Standard 29CFR 1910.1200
2) WHMIS (Canadian)

*) Refer to Section 7 for available LD/LC (50) Health Hazard Data.

3. **PHYSICAL DATA:**

Boiling Point (oC):	100	Water/Oil Distribution	
Percent VOC (w/w):	(Water) 50-75	Coefficient:	N/Av
Freezing Point (oC):	N/Av	Solubility in Water:	None
Vapor Pressure mmHg @20 (oC):	N/Av	Specific Gravity:	ca 1.0
Vapor Density:	> Air	pH:	N/Av
Odor Threshold: (ppm)	N/Av	Evaporation Rate:	N/Av
Appearance: Whitish liquid		Odor: Mild	

N/Av = Not Available N/Av = Not Applicable ca. = Approximate

4. **FIRE AND EXPLOSION HAZARD DATA:** HMIS Hazard Rating No. 0 (Minimal)

Flash Point: Non-flammable Method: Not Applicable

Auto-Ignition Temperature: Not Applicable

Limits Of Flammability: LEL: Not Applicable UEL: Not Applicable

Extinguishing Media: This material does not give a flash point by conventional test methods. Use extinguishing agent suitable for type of surrounding fire.

MBT X-POZ-R

4. **FIRE AND EXPLOSION HAZARD DATA:** (cont'd)

Special Fire & Unusual Hazards: None known.

5. **REACTIVITY DATA:** HMIS Hazard Rating No. 0 (Minimal)

Stability: Stable. Not sensitive to mechanical impact.

MBT X-POZ-R ALL COLORS (FORMERLY: PRECO X-POZ-R ALL COLORS)

Incompatibility: None known.

Hazardous Decomposition Products: (After water has evaporated.) Oxides of Carbon and Nitrogen; various unknown hydrocarbons.

Hazardous Polymerization: Will not occur.

6. ENVIRONMENTAL & DISPOSAL INFORMATION:

Action to Take for Spills/Leaks: Take action to eliminate source of leak; contain spill by diking; vacuum up liquid or use absorbent media; remove to storage for disposal and rinse residual stain with water.

Waste Disposal Method: Does not contain hazardous chemicals as defined in 40 CFR 260. Handle disposal of waste material in accordance with local, state, province and federal regulation.

7. HEALTH HAZARD DATA: HMIS Hazard Rating No. 0 (Minimal)

PRIMARY ROUTE OF ENTRY: Dermal, Eyes

Effects Of Overexposure

Inhalation: At room temperature, exposures to vapors are unlikely due to physical properties. Mists or spray can cause irritation to mucous membranes.

Eyes: Can cause slight irritation.

Skin Contact: Prolonged contact can cause slight irritation; prolonged or repeated contact can cause defatting and possibly dermatitis.

Skin Absorption: Not expected to be absorbed through the skin in sufficient quantities to increase overall toxicity.

Ingestion: Amounts ingested incidental to industrial handling are not expected to cause injury. Can cause gastrointestinal irritation, vomiting, and diarrhea.

Chronic: Product does not contain carcinogenic materials as defined by OSHA Hazardous Communications Act 1910.1200.

Materials are not known mutagenic, teratogenic, or reproductive health hazards

MBT X-POZ-R ALL COLORS (FORMERLY: PRECO X-POZ-R ALL COLORS)

MBT X-POZ-R

8. FIRST AID:

- Inhalation: Remove victim from exposure. If difficulty with breathing, administer oxygen. If breathing has stopped administer artificial respiration, preferably mouth-to-mouth. Seek medical attention.
- Eyes: Flush eyes with water, lifting upper and lower lids occasionally for 15 minutes. Seek medical attention.
- Skin: Remove contaminated clothing. Wash thoroughly with soap and water. If irritation persists seek medical attention. Wash contaminated clothing before reuse.
- Ingestion: Do **NOT** induce vomiting; give large quantities of water; If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquids into lungs. Do not give anything by mouth to an unconscious person. Contact a physician if discomfort is encountered

9. SPECIAL PROTECTION INFORMATION:

Ventilation: Ventilation is generally not required.

Personal Protection Equipment: Do **NOT** wear contact lenses when working with this material. Use chemical goggles/safety glasses with side shields and Rubber/Latex gloves. Selection of specific items such as boots and apron will depend on operation. Wear respirator protection whenever airborne concentrations exceed TLV or TWA limits. Use NIOSH/OSHA approved respirators equipped with an organic vapor cartridge for listed hazard.

Confined spaces, rooms, or tanks are areas where concern for TLV's is especially important. Reference OSHA Regulation CFR 29 1910.134 for recommended respiratory protection.

10. ADDITIONAL INFORMATION:

Average Shelf Life: Refer to Product Data Sheet

Special Instructions: Store in cool, dry place.

REGULATORY INFORMATION:

Title III Section 302: No reportable chemicals.

Title III Section 311/312:
Health hazard: None
Physical hazard: None

Title III Section 313: None above deminimis.

State: California No reportable chemicals.

WHMIS Classification: Not controlled.

Canadian Domestic Substance List: All chemicals are listed.

MBT X-POZ-R ALL COLORS (FORMERLY: PRECO X-POZ-R ALL COLORS)

MBT X-POZ-R

10. **ADDITIONAL INFORMATION:** (cont'd)

TRANSPORTATION

National Motor Freight Classification (NMFC): 33980 Sub - Class 55

Description: CONCRETE SURFACE CURING COMPOUNDS

Emergency Response Guide Page No.: NOT REGULATED

DOT Reportable Quantity: NOT REGULATED

Shipping Name: NOT REGULATED - USE NMFC DESCRIPTION

Marine Pollutant:

NL

P = Moderate

PP = Severe

WS = Water Sheen

NL = Not Listed

ND = Not Determined

This information is furnished without warranty, representation, or license of any kind, except that this information is accurate to the best of Master Builders' knowledge, or is obtained from sources believed by Master Builders to be accurate. No warranty is expressed or implied regarding the accuracy of this information or the results to be obtained from its use thereof. Master Builders assumes no responsibility for injuries proximately caused by use of the Material if reasonable safety procedures are not followed as stipulated in this Data Sheet. Additionally, Master Builders assumes no responsibility for injuries proximately caused by abnormal use of the Material even if reasonable safety procedures are followed. Buyer assumes the risk in its use of the Material.