



**TRIM-TEX, INC.**  
3700 W. PRATT AVENUE; LINCOLNWOOD, IL 60712  
847-679-3000  
24 Hour Emergency Phone: 800-424-9300

**MATERIAL SAFETY DATA SHEET**

**SECTION III ☐ HAZARDS IDENTIFICATION**

---

**EMERGENCY OVERVIEW \*\*\***

Keep from reach of children. Do not puncture, incinerate, or place aerosol product containers in compactors. Containers of this material may be hazardous when emptied since containers retain product residues (vapor, liquid, and/or solid). All hazard precautions given must be observed. Do not flame cut, braze or use a welding torch. Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal.

**EFFECTS OF OVEREXPOSURE:**

- **Eye Contact:** Can cause severe irritation, redness, tearing, and blurred vision.
- **Skin Contact:** Prolonged or repeated contact can cause moderate irritation defatting, and dermatitis.
- **Inhalation:** Excessive inhalation of vapors can cause nasal and respiratory irritation, dizziness, weakness, fatigue, nausea, headache, possible unconsciousness, and even asphyxiation. Overexposure may cause damage to the nervous system.
- **Ingestion:** No Information
- **Chronic Hazards:** Overexposure to this material (or its components) has apparently been found to cause the following effects in laboratory animals: kidney damage, eye damage, liver damage, lung damage, hearing loss, nasal damage, nervous system damage and testis damage. Overexposure to this material (or its components) has apparently been found to cause the following effects in humans: liver damage, kidney damage, brain damage, visual impairment, and central nervous system effects.
- **Primary Route(s) of Entry:** Skin contact, skin absorption, inhalation and eye contact.

**SECTION IV ☐ FIRST AID MEASURES**

---

- **Eye Contact:** Flush with large amounts of water, lifting upper and lower lids occasionally and get medical attention.
- **Skin Contact:** Thoroughly wash exposed area with soap and water. Remove contaminated clothing. Launder contaminated clothing before re-use. Get medical attention if irritation persists. Mineral oil, baby oil, make-up remover, mineral spirits or other similar mild solvent may be used to remove the sticky resin residue left by the adhesive.

**TRIM-TEX, INC.**  
3700 W. PRATT AVENUE; LINCOLNWOOD, IL 60712  
847-679-3000  
24 Hour Emergency Phone: 800-424-9300

**MATERIAL SAFETY DATA SHEET**

**SECTION IV ☐FIRST AID MEASURES (CONTINUED)**

---

- **Inhalation:** Remove individual to fresh air. If breathing is difficult, administer oxygen. Give artificial respiration if breathing has stopped. Keep person warm and quiet. Get medical attention.
- **Ingestion:** Do not induce vomiting. Give two glasses of water if conscious. Never give anything by mouth to an unconscious person. Get immediate medical attention.

**SECTION V ☐FIRE FIGHTING MEASURES**

---

**Flash Point:** -156°F (Pensky-Martens C.C.)  
**Lower Explosive Limit:** 1.0%  
**Upper Explosive Limit:** 18.0%  
**Auto-Ignition Temperature:** N.D.  
**Extinguishing Media:** CO<sub>2</sub>, Dry Chemical, Foam, Water Fog

- **Unusual Fire and Explosion Hazards:** Vapors are heavier than air and travel along the ground or may be moved by ventilation and ignited by ignition sources at locations distant from material handling point. For aerosol products ☐ exposure to temperatures over 130°F may cause containers to burst releasing highly flammable gas.
- **Special Firefighting Procedures:** Wear self-contained breathing apparatus with a full face piece operated in pressure-demand or other positive pressure mode when fighting fires. Keep fire exposed containers cool with water fog.

**SECTION VI ☐ACCIDENTAL RELEASE MEASURES**

---

- **Steps to be taken in case material is released or spilled:** Eliminate sources of ignition & ventilate area. Persons not properly equipped should be excluded from area. Stop spill at source ☐prevent spreading. Avoid inhalation of vapors. Avoid skin contact with liquid. Soak up on absorbent material and place into proper container for disposal. Use non-sparking scoops for flammable materials. Clean walking surfaces thoroughly to reduce slipping hazard.

**TRIM-TEX, INC.**  
3700 W. PRATT AVENUE; LINCOLNWOOD, IL 60712  
847-679-3000  
24 Hour Emergency Phone: 800-424-9300

**MATERIAL SAFETY DATA SHEET**

**SECTION VII □ HANDLING & STORAGE**

- **Handling:** Containers of this material may be hazardous when emptied, since containers retain product residues (vapor, liquid and/or solid). All hazard precautions given must be observed. Do not flame cut, braze or use welding torch on containers. Intentional misuse by deliberately concentrating and inhaling the vapors from this product may be harmful or fatal.
- **Storage:** Do not store above 120°F. Do not store in direct sunlight. Keep away from heat sources, open flame, pilot lights, sparks and other sources of ignition.

**SECTION VIII □ EXPOSURE CONTROLS / PERSONAL PROTECTION**

- **Engineering Controls:** Provide sufficient mechanical ventilation (general and/or local exhaust) to maintain exposure below TLV(s).
- **Respiratory Protection:** If workplace exposure limits of product or any component is exceeded, use a NIOSH/MSHA approved respirator. Consult your safety equipment supplier for recommendations.
- **Skin Protection:** Wear impervious gloves if method of use involves skin contact with product. Consult your safety supply vendor for glove recommendations.
- **Eye Protection:** Wear safety glasses at minimum, more extensive protection may be necessary depending on how the product is to be used.
- **Other Protective Equipment:** Wear impervious clothing if bodily exposure is anticipated. Consult your safety supply vendor for recommendations.
- **Hygienic Practices:** Wash hands before eating or smoking. Smoke in designated areas only. Remove and launder clothing if contaminated.

**SECTION IX □ PHYSICAL AND CHEMICAL PROPERTIES**

<b>Boiling Range:</b>	<b>-44°F to 472°F</b>	<b>Vapor Density:</b>	<b>Is heavier than air</b>
<b>Odor:</b>	<b>Mint when wet</b>	<b>Odor Threshold:</b>	<b>N.D.</b>
<b>Appearance:</b>	<b>Pink liquid</b>	<b>Evaporation Rate:</b>	<b>Is faster than Butyl</b>
<b>Solubility in H<sub>2</sub>O:</b>	<b>Negligible</b>		<b>Acetate</b>
<b>Freeze Point:</b>	<b>N.D.</b>	<b>Specific Gravity:</b>	<b>0.7122</b>
<b>Vapor Pressure:</b>	<b>N.D.</b>	<b>pH @ 0.0%:</b>	<b>N.D.</b>
<b>Physical State:</b>	<b>Liquid</b>	<b>Viscosity:</b>	<b>N.D.</b>
<b>Coefficient of Water/Oil Distribution:</b>	<b>N.D.</b>		

(See Section 16 for abbreviation legend.)

**TRIM-TEX, INC.**  
3700 W. PRATT AVENUE; LINCOLNWOOD, IL 60712  
847-679-3000  
24 Hour Emergency Phone: 800-424-9300

**MATERIAL SAFETY DATA SHEET**

**SECTION X  STABILITY AND REACTIVITY**

---

- **Conditions to Avoid:** Heat, sparks, welding arcs, open flame, pilot lights, static electricity or other source of ignition.
- **Incompatibility:** Oxidizing agents, acids, reducing agents and strong oxidizers.
- **Hazardous Decomposition Products:** Carbon monoxide, carbon dioxide and various hydrocarbons.
- **Hazardous Polymerization:** Will not occur under normal conditions.
- **Stability:** This product is stable under normal storage conditions.

**SECTION XI  TOXICOLOGICAL PROPERTIES**

---

- No product or component toxicological information is available.

**SECTION XII  ECOLOGICAL INFORMATION**

---

- **Ecological Information:** No Information

**SECTION XIII  DISPOSAL CONSIDERATIONS**

---

- **Disposal Method:** Dispose of in accordance with all local, state and federal regulations.

**SECTION XIV  TRANSPORTATION INFORMATION**

---

**D.O.T. Proper Shipping Name:** Aerosols  
**D.O.T. Technical Name:**  
**D.O.T. Hazard Class:** 2.1                      **Hazard Subclass:** None  
**D.O.T UN/NA Number:** UN1950            **Packing Group:** None  
**RESP. Guide Page:** 126

**Additional Information:** For domestic ground and air shipment this product may be shipped as a Consumer Commodity ORM-D. Outer cartons must have the ORM-D or ORM-D AIR designation. (Our original cartons are preprinted with the ORM-D designation for ground shipment.)

**TRIM-TEX, INC.**  
3700 W. PRATT AVENUE; LINCOLNWOOD, IL 60712  
847-679-3000  
24 Hour Emergency Phone: 800-424-9300

**MATERIAL SAFETY DATA SHEET**

**SECTION XV REGULATORY INFORMATION**

**U.S. FEDERAL REGULATIONS AS FOLLOWS:**

- **OSHA:** Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200)
- **CERCLA SARA Hazard Category:** This product has been reviewed according to the EPA Hazard Categories promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

IMMEDIATE HEALTH HAZARD  
FIRE HAZARD

CHRONIC HEALTH HAZARD  
PRESSURIZED GAS HAZARD

- **SARA Section 313:** This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

CHEMICAL NAME:	CAS NUMBER	WT/WT% IS LESS THAN
Hexane	110-54-3	20.0%
Toluene	108-88-3	5.0%

- **Toxic Substances Control Act:** This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

CHEMICAL NAME:	CAS NUMBER
No information is available.	

**U.S. STATE REGULATIONS AS FOLLOWS:**

- **California Proposition 65:** WARNING: The chemical(s) noted below and contained in this product, are known to the state of California to cause cancer, birth defects or other reproductive harm:

CHEMICAL NAME:	CAS NUMBER	WT/WT% IS LESS THAN
Toluene	108-88-3	5.0%
Benzene	71-43-2	30 PPM
Acetaldehyde	75-07-0	5 PPM
Formaldehyde	50-00-0	5 PPM

**TRIM-TEX, INC.**  
3700 W. PRATT AVENUE; LINCOLNWOOD, IL 60712  
847-679-3000  
24 Hour Emergency Phone: 800-424-9300

**MATERIAL SAFETY DATA SHEET**

**SECTION XV REGULATORY INFORMATION (CONTINUED)**

**INTERNATIONAL REGULATIONS AS FOLLOWS:**

- **Canadian WHMIS:** This MSDS has been prepared in compliance with Controlled Product Regulations except for use of the 16 headings.
- **Canadian WHMIS Class:** No information available.
- **TSCA Inventory:** All components of this product are on the US TSCA inventory.

Hexane is a mixture of n-hexane and other compounds all falling under the general chemical name light hydrotreated distillate CAS-68410-97-9. The n-hexane content of our hexane is 60 to 70 percent. On June 30, 1993, the OSHA Z-1-A table was revoked and OSHA reverted back to their prior exposure limits. The values on this MSDS reflect the roll back to the prior values. Some states may continue to enforce the 1993 limits. On June 16, 1995, EPA announced in a final rule that acetone would no longer be considered a VOC for air attainment standards (it is now an exempt compound). The VOC calculations on this MSDS are based on acetone being an exempt compound. The June 16, 1995 rule also removed acetone from the list of SARA 313 reportable chemicals.

**SECTION XVI OTHER INFORMATION**

HMIS Ratings <input type="checkbox"/> Health:	2	Flammability:	4	Reactivity:	1
Previous MSDS Revision Date:	01/26/07				
Reason for revision:	Scheduled Update				
VOC Content:	52.4% by weight, 372 grams/liter total product, 479 grams/liter less water and exempt, 0.53 lbs/can.				
Legend:	N.A. <input type="checkbox"/> Not Applicable N.D. <input type="checkbox"/> Not Determined N.E. <input type="checkbox"/> Not Established				

The information contained on this MSDS has been checked and should be accurate. However, it is the responsibility of the user to comply with all Federal, State, and Local laws and regulations. The environmental information and hazardous materials identification system have been included by Trim-Tex, Inc. in order to provide additional health and hazard classification information. The ratings recommended are based upon the criteria supplied by the developers of these rating systems, together with Trim-Tex, Inc.'s interpretation of the available data. Proper personal protective equipment varies widely with conditions of use and anticipated exposure. We recommend that a supervisor, or other qualified person, determine proper PPE for intended use.