



ROLL ROOFING PRODUCTS

World's Largest Producer of Roll Roofing & Felt

Preferred by roofing professionals.

Atlas has you covered on every part of the job, even what goes under your roofing. We are proud to offer the largest and most innovative variety of premium underlayment and roll-roofing products. They are manufactured to ensure easy installation as well as to perfectly complement virtually all roofing systems.



Residential Sales Offices

Corporate Sales and Marketing
200 River Edge Pkwy, Suite 800
Atlanta, Georgia 30328

Ardmore, OK
Daingerfield, TX
Franklin, OH
Hampton, GA
Meridian, MS

(800) 261-2852
(800) 270-2852
(800) 260-2852
(800) 251-2852
(800) 933-2721

Fax (580) 223-6894
Fax (903) 645-2291
Fax (937) 746-6040
Fax (770) 946-5249
Fax (601) 483-7344

ROLL ROOFING PRODUCTS

Asphalt Roll Roofing	ASTM	DESCRIPTION	WIDTH	LENGTH	APPROX.ROLL COVERAGE
#90 Mineral Surface Roll Roofing	—	The top surface of this organic-based roll is imbedded with mineral granules. Can be used alone as a primary roof covering.	36"	36'	1
#55 Smooth Surface Roll Roofing	D-6380 Class S IV	Organic Felt Based. Used primarily as flashing to seal the roof at intersections and protrusions. Provides extra deck protection at the eaves and valleys. (Previous ASTM D 244 Class IV)	36"	36'	1
Slate/Tile Underlayment	D-6380 Class M	Premium Slate Granule Surfaced Roof Tile Underlayment Organic Felt Based (Previous ASTM D 249 Type II) Also available Non-ASTM	36"	36'	1
Asphalt Saturated Organic Felt					
#15 Standard Saturated Felt	D-4869 Type I	Standard Shingle Underlayment Saturated Felt Also available Non-ASTM	36"	144'	4
#15 Specification Felt	D-4869 Type II	Premium Shingle Underlayment Saturated Felt (Previous ASTM D 226 Type I)	36"	144'	4
#15 Specification Felt, Perforated	D-4869 Type II	Premium Perforated Shingle Underlayment Saturated Felt (Previous ASTM D 226 Type I)	36"	144'	4
#30 Saturated Felt	D-4869 Type III	Heavy Shingle Underlayment Saturated Felt (Previous ASTM D 4869 Type II) Also available Non-ASTM	36"	72'	2
#30 Standard, Split Rolls - 18"x 72' Master Roll = 2 Split Rolls	D-4869 Type III	Wood Shake Shingle Underlayment 36" W-Perforated @ 18" Saturated Felt (Previous ASTM D 4869 Type II)	36"	72'	2
Jumbo #30 18" Standard Shake Felt Underlayment (Split Roll)	D-4869 Type III	Wood Shake Shingle Underlayment 36" W-Perforated @ 18" Saturated Felt (Previous ASTM D 4864 Type II)	36"	120'	1.66
#30 Specification Felt	D-4869 Type IV	Premium Specification Underlayment Saturated Felt (Previous ASTM D 226 Type II)	36"	72'	2
Glass Fiber Reinforced Asphalt Saturated Felt					
Gorilla Guard™	D-6757	Premium Glass Reinforced Shingle Underlayment	36"	141.5'	4
Synthetic Shingle Underlayment					
Summit™	D-6757	Light Weight, Extremely Strong, Woven Polypropylene Fabric with UV & Water Resistive Coatings, 6 mo. exposure, Synthetic Shingle Underlayment	48"	250'	10
Modified Bitumen Roll Roofing					
WeatherMaster™ Water & Ice Protection	D-1970	Granular Surfaced Peel & Stick SBS Reinforced Underlayment	36" 36"	33.3' 66.6'	1 2
PolySeal	D-1970	Peel & Stick, Polysurfaced, Hi-temp, SBS Modified Asphalt Roof Underlayment	36" 36"	33.3' 66.6'	1 2
Tile Seal	D-1970	Peel & Stick, Woven Polyester Surfaced SBS, Heavy Tile Underlayment	36"	66.6'	2
Shingle Starter Products					
Starter Rolls With Sealant	D-1970	SBS Peel & Stick Starter Roll Used to secure first shingle course	7.2"	33.4'	33 Lineal Feet
Starter Strip With Sealant	D-3462	Asphalt coated, Glass mat Reinforced Shingle Starter Strips	7"	36'	120 Lineal Feet