



RAPID RIDGE®

THE FASTEST WAY TO PROTECT A ROOF FROM HEAT AND MOISTURE

Rapid Ridge® nail gun-able ridge vent offers the quickest installation of any rolled ventilation product on the market, complete with superior weather and insect infiltration protection. Rapid Ridge features a see-through hinge for easy alignment and enhanced airflow as well as a unique low-profile design that easily installs with any pneumatic roofing nail gun—without a special adapter.



FEATURES

- Installs with a pneumatic gun
- 1 3/4" collated nails provided
- See-through hinge
- Compression resistant
- Breathable weather barrier
- No end cap installation
- Lightest ridge vent on a roll
- Visible nail line

BENEFITS

- Speeds installation
- No nails to purchase
- Easy to center over the ridge
- Creates smooth finish
- Prevents rain, snow, and insect infiltration
- Saves time by shingling over
- Easy to handle
- Assists with alignment of shingles

RAPID RIDGE®

Ridge Ventilation Competitive Comparison Chart Rolled Products: Nail Gun-able

Product Name	Rapid Ridge	Cobra Nail Gun	Cobra Ridge Runner	VentSure	Rigid Roll	Lo-Omni Roll	Peak Performance I & II (LP)
Company Name	Obdyke	GAF	GAF	Owens Corning	Trimline	Lomanco	AirVent / Gibraltar
Net Free Area	12.5	14.1	12.5	12.5	13	11	12
Length	20'/50'	20'	20'	20'	20'	30'	32'
Cedar Application	Y	N	N	Y	Y	N	N
Metric Application	Y	N	N	N	N	N	N
Nail Method	Gun	Gun	Gun	Gun	Gun	Gun	Gun
Nails Included	Y	Y	Y	N	N	Y*	Y
Nails Recommended	1-3/4" Coil	1-3/4" Coil and Nail Gun Adaptor	1-3/4"	Not Specified	Not Specified	1-3/4"	1-3/4"
Nail Line	Y	N	Y	Y	Y	Y	Y
Warranty	50 yrs	40 yrs	40 yrs	50 yrs	Lifetime Limited	30 yrs	Lifetime Limited
Miami-Dade NOA	Pending	Y	N	Y	Y	Y	N
ICC #	Y	Y	Pending	Y	Y	N	N
Florida Building Code	Y	Y	Y	Y	N	Y	N
Height	5/8"	5/8"	5/8"	5/8"	5/8"	5/8"	5/8"
Highest Pitch	18/12	Not Specified	16/12	20/12	20/12	16/12	Not Specified
End Caps	Shingle Over	None	Integrated	Separate Foam	Separate Foam	Integrated	Integrated
Fabric Weather Barrier	Y	N	Y	Y	Y	N	N/Y
Weight per 20' Roll	2.5 lbs	5.25 lbs	7.0 lbs	7.0 lbs	7.0 lbs	16.25 lbs	11.1 lbs

*Note: Requires double nailing - first the entire length of the vent, then the ridge caps.
Information reflects available data through 1/15/07

SPECIFICATIONS

Evaluation Reports

ICC ESR-1059, CCMC #12523-R
(For Ridge Application Only).

Codes

Rapid Ridge® Standard meets or exceeds the following codes:
ICC, BOCA, ICBO, SBCCI, NBC, FHA and HUD.

*Specifications are subject to change.



The low-profile design of Rapid Ridge allows nail-gun installation and provides easy alignment and enhanced airflow.

Testing

Certified testing was performed by Applied Research Laboratories, Miami, FL, U.S. Testing Co., Inc., Hoboken, NJ, Bodycote Materials Testing, Ontario, Canada, and PRI Asphalt Technologies, Tampa, FL.

Patents

US Patents #4,942,699, #5,960,595,
#6,298,613, and #6,981,916
Canadian Patents #2,300,803
Other patents pending



Complete the job with quality Benjamin Obdyke ridge ventilation solutions.

- Roll Vent® — Rolled ridge vents offering maximum net free area
- Rapid Ridge® — Nail gun-able ridge vents with a fast and easy installation
- Xtractor Vent® — Sectional ridge vents designed to extract heat and moisture from attics

**BENJAMIN
OBDYKE**
residential roof & wall products

BENJAMIN OBDYKE INCORPORATED • 400 Babylon Road, Suite A • Horsham, PA 19044 • www.benjaminobdyke.com
Sales: 800-523-5261 • Customer Service: 800-346-7655 • Fax: 215-672-3731 • Email: info@benjaminobdyke.com