



Grout-N-Go™ SANDED

PREMIXED SANDED GROUT

KEY FEATURES

- Premixed & ready to use
- For grout joints 1/8" to 3/8"
- For residential floors, walls & countertops

PRODUCT DESCRIPTION

Bostik Grout-N-Go™ Premixed Sanded Grout is an acrylic emulsion grout that is convenient for grouting most types of ceramic or porcelain tile, quarry tile and select natural stone.

WHERE TO USE

RESIDENTIAL For most interior floors, walls and countertops in dry to intermittent wet, light duty applications. Ideal for small jobs or repairs that include residential backsplashes, tub surrounds, floors and walls.

FEATURES & BENEFITS

- Premixed- Quick, convenient easy to use.
- Blockade® Antimicrobial Protection
- For grouting most ceramic, porcelain, quarry and Saltillo tile, and most types of natural stone.

DIRECTIONS FOR USE

Read and understand this technical data sheet completely before beginning installation. Follow applicable ANSI (American National Standards Institute), NTCA (National Tile Contractors Association) and TCNA installation standards.

SURFACE PREPARATION

- All surfaces must be clean, dry and smooth; free of voids, projections, loose materials, oil, grease, sealers, curing compounds or any other surface contaminants that may prevent proper bond. Certain tiles with high absorption, surface porosity or rough surfaces may require sealing before grouting to prevent permanent staining.



CURING, PROTECTION, WAIT TIMES

Wait Time Prior To:	Minimum Wait Time*
Light Foot Traffic	24 – 48 Hours
Intermittent Water Exposure	7 Days
Stain Resistance	7 Days

* Cure times vary based on temperature (ambient vs. substrate), humidity, grouting practices, etc.

PRE-MIXED GROUT-N-GO SANDED

Product Color	Color Number	Size	Product Number
White	H152	1 Quart	G00655
White	H152	1/2 Gallon	G00645
Classic Bone	H158	1/2 Gallon	G00646
Mushroom	H000	1/2 Gallon	G00647
Latte	H192	1/2 Gallon	G00648
Delorean Gray	H160	1/2 Gallon	G00650

COVERAGE PER ½ GALLON (1.89 L) & 1 QUART PAILS

Tile Size	Grout Joint Width				
	1/16" (1.5mm)	1/8" (3mm)	1/4" (6mm)	3/8" (10mm)	1/2" (12mm)
2" x 2" x 1/4" (50 x 50 x 6mm)	45 to 50 Sq. Ft. (1/2 GAL) 4.18 to 4.65 m ² 22.5 to 50 Sq. Ft. (1 QT) 2.09 to 2.32 m ²	23 to 26 Sq. Ft. (1/2 GAL) 2.14 to 2.42 m ² 11.5 to 13 Sq. Ft. (1 QT) 1 to 1.21 m ²	12 to 14 Sq. Ft. (1/2 GAL) 1.11 to 1.30 m ² 6 to 7 Sq. Ft. (1 QT) .55 to .65 m ²	9 to 11 Sq. Ft. (1/2 GAL) 0.84 to 1.02 m ² 4.5 to 5.5 Sq. Ft. (1 QT) 0.42 to .51 m ²	6 to 7 Sq. Ft. (1/2 GAL) 0.84 to 1.02 m ² 3 to 3.5 Sq. Ft. (1 QT) 0.42 to 0.51
4-1/4" x 4-1/4" x 1/4" (108 x 108 x 6mm)	100 to 110 Sq. Ft. (1/2 GAL) 9.29 to 10.2 m ² 50 to 55 Sq. Ft. (1 QT) 4.64 to 5.1 m ²	50 to 55 Sq. Ft. (1/2 GAL) 4.65 to 5.11 m ² 25 to 27.5 Sq. Ft. (1 QT) 4.65 to 5.11 m ²	24 to 27 Sq. Ft. (1/2 GAL) (2.23 to 2.51 m ²) 12 to 13.5 Sq. Ft. (1 QT) 1.16 to 1.25 m ²	19 to 21 Sq. Ft. (1/2 GAL) 1.77 to 1.95 m ² 9.5 to 10.5 Sq. Ft. (1 QT) 0.88 to .98 m ²	12 to 14 Sq. Ft. (1/2 GAL) 1.77 to 1.95 m ² 6 to 7 Sq. Ft. (1 QT) 0.89 to 0.98 m ²
6" x 6" x 1/4" (150 x 150 x 6mm)	135 to 150 Sq. Ft. (1/2 GAL) 12.5 to 13.9 m ² 67.5 to 55 Sq. Ft. (1 QT) 6.25 to 6.95 m ²	67 to 75 Sq. Ft. (1/2 GAL) 6.22 to 6.97 m ² 33.5 to 37.5 Sq. Ft. (1 QT) 3.11 to 3.48 m ²	34 to 38 Sq. Ft. (1/2 GAL) 3.16 to 3.53 m ² 17 to 38 Sq. Ft. (1 QT) 1.58 to 1.77 m ²	25 to 28 Sq. Ft. (1/2 GAL) 2.32 to 2.60 m ² 12.5 to 14 Sq. Ft. (1 QT) 1.16 to 1.3 m ²	17 to 19 Sq. Ft. (1/2 GAL) 2.32 to 2.60 m ² 8.5 to 9.5 Sq. Ft. (1 QT) 1.16 to 1.3 m ²
8" x 8" x 3/8" (200 x 200 x 10mm)	118 to 130 Sq. Ft. (1/2 GAL) 11.0 to 12.1 m ² 59 to 65 Sq. Ft. (1 QT) 5.5 to 6.05 m ²	59 to 65 Sq. Ft. (1/2 GAL) 5.48 to 6.04 m ² 29.5 to 32.5 Sq. Ft. (1 QT) 2.74 to 3.02 m ²	30 to 33 Sq. Ft. (1/2 GAL) 2.79 to 3.07 m ² 15 to 16.5 Sq. Ft. (1 QT) 1.40 to 1.55 m ²	22 to 25 Sq. Ft. (1/2 GAL) 2.04 to 2.32 m ² 11 to 12.5 Sq. Ft. (1 QT) 1.02 to 1.16 m ²	15 to 16 Sq. Ft. (1/2 GAL) 2.04 to 2.32 m ² 7.5 to 8 Sq. Ft. (1 QT) 1.02 to 1.16 m ²
12" x 12" x 3/8" (300 x 300 x 10mm)	170 to 190 Sq. Ft. (1/2 GAL) 15.8 to 17.7 m ² 85 to 95 Sq. Ft. (1 QT) 7.9 to 8.85 m ²	86 to 95 Sq. Ft. (1/2 GAL) 7.99 to 8.83 m ² 43 to 47.5 Sq. Ft. (1 QT) 3.96 to 4.42 m ²	43 to 48 Sq. Ft. (1/2 GAL) 3.99 to 4.46 m ² 21.5 to 24 Sq. Ft. (1 QT) 2.0 to 2.23 m ²	32 to 36 Sq. Ft. (1/2 GAL) 2.97 to 3.34 m ² 16 to 18 Sq. Ft. (1 QT) 1.49 to 1.67 m ²	21 to 24 Sq. Ft. (1/2 GAL) 2.97 to 3.34 m ² 10.5 x 12 Sq. Ft. (1 QT) 1.49 to 1.67 m ²

- Some glazed ceramic tile, marble, granite and marble agglomerates can be permanently stained, scratched, dulled or damaged when grouted with pigmented grout or sanded grout formulas.
- White grout is generally best for grouting white or light-colored natural stone. Ensure that natural stone tiles are compatible with colored grouts. Check the tile or stone manufacturer's literature and test grout on a separate sample before grouting to determine suitability.
- Before grouting: Ensure tile is firmly set, and adhesive or mortar is completely dry; remove all spacers, excess adhesive or mortar from grout joints so at least 2/3 of the tile depth remains for grouting; clean tile surface thoroughly to remove dust, dirt and other contaminants that may cause grout discoloration.
- Refer to Bostik's Surface Preparation Requirements document for tile and stone installation.

MIXING

Bostik Premixed Sanded Grout is ready to use. No mixing is required.

APPLICATION

1. Choose appropriate safety equipment before use. Refer to Material Safety Data Sheet (MSDS) for more information.
2. Review tile or stone manufacturer's specifications to verify suitability for specific installations and methods.
3. Install at temperatures between 50°F (10°C) and 95°F (35°C).
4. To facilitate application and clean up, slightly moisten tile surface with damp sponge. Do not flood tiles or allow water to stand in ungrouted joints.
5. Force Grout-N-Go™ into joints with rubber grout float. Make sure all joints are well-compacted and free of voids and gaps.
6. Remove excess grout from tile surface by moving grout float diagonally across joints.
7. Grout surface should be flush with the tile edge.
8. Begin cleaning within 5 to 10 minutes (depending on temperature, humidity). Grout small areas so cleaning can begin before grout skins over and dries on tile surface.

9. Drag a clean, damp cellulose sponge diagonally across tile joints, applying slight pressure. Use one side of sponge for each pass, rinsing sponge after second pass.
10. Change water frequently to prevent haze on tile.
11. If residue is still observed, a final wash can be performed about 1 hour after initial wash. If needed, 1 U.S. oz. (30 mL) of a clear dishwashing soap may be added to 3 U.S. gals. (11,4 L) clean water; use a clean white moistened scrubpad to loosen any remaining residue; remove with a moistened cellulose sponge.

CLEAN UP

1. Clean hands and tools with clean, soapy water while grout is fresh.
2. Never use acid for cleaning marble, glazed tile or pigmented grout surfaces. If persistent haze remains after normal cleaning, contact Bostik's Technical Services department

PROTECTION

3. Wait 7 days before water exposure (intermittent only) and to develop stain resistance.
4. **Floors:** Keep free from traffic for at least 24 to 48 hours after installation.
5. **Walls:** Protect from impact, vibration and hammering on adjacent and opposite walls for 7 days after tile installation.
6. Protect from freezing.

ONGOING MAINTENANCE

1. To maintain a clean tile surface, use a neutral-pH cleaner for maintaining the floor, followed by a clean-water rinse.
2. Do not use harsh chemicals to maintain the tile surface.
3. Before cleaning, consult cleaner literature for compatibility, use and application.

LIMITATIONS

- Do not install over substrates containing asbestos.
- Do not use for submerged applications or steam rooms.
- Do not add powder, liquid or any other substance to grout.
- For interior installations only.
- Not for use on shower floors.
- Do not freeze.
- Do not use in installations where deflection exceeds L/240 (1" in 20 feet). For marble and limestone, refer to the Marble Institute Of America's or TCNA Handbook for deflection recommendations.

- Do not use to grout moisture-sensitive stone such as green, red or cultured marble, some limestone, green granite, agglomerate tiles, or resin-backed tiles. Instead, use a suitable epoxy or urethane adhesive.
- Do not use for applications subject to heavy, commercial traffic; where negative hydrostatic pressure can occur.
- Do not use outdoors or in steam rooms; in commercial applications.
- Do not apply over dimensionally unstable substrates such as hardwood flooring, oriented strand board (OSB), particle board, Masonite, luaun, or similar unstable substrates; substrates containing asbestos or metal; laminate surfaces, existing tile, cutback adhesive residue.
- Some types of glazed ceramic tiles, marble, granite and marble agglomerates can be permanently stained, scratched, dulled or damaged when grouted with pigmented or sanded grout. Test grout on separate area before to determine suitability of grout color selected.
- Porous and abrasive tile may require pre-sealing to prevent grout residue from penetrating tile surface.
- Use only at temperatures between 50°F and 95°F (10°C and 35°C).
- Drying time will vary depending on tile size/porosity.

STORAGE/SHELF LIFE

Store in a clean, dry area not affected by freezing or hot temperatures. Shelf life is 12 months from date of manufacturing in original, unopened pail.

PACKAGING

Available in 1 Quart & 1/2 Gallon pails.

CAUTION

HARMFUL IF SWALLOWED OR INHALED. MAY IRRITATE EYES, SKIN AND RESPIRATORY TRACT. Contains a respirable carcinogen. Do not inhale dust. Do not get in eyes, on skin or on clothing. Do not breathe fumes. Do not swallow. Use with adequate ventilation or wear a mask. Wear protective clothing during handling. Wash thoroughly after handling. Store container in a cool, dry area with lid tightly sealed. Do not reuse container.

FIRST AID TREATMENT

Contains Water, Proprietary Polymer, Quartz Silica, Clay, Titanium Dioxide. If in eyes or on skin, rinse with water for at least 15 minutes. If breathed in, move person to fresh air. If swallowed, call a Poison Control Center or doctor immediately. Do not induce vomiting.

KEEP OUT OF REACH OF CHILDREN

LIMITED WARRANTY

The Limited Warranty for this product can be found at www.Bostik-US.com/resource-center/warranties or by calling 1-800-726-7845 (choose option 2, then option 2 again). TO THE MAXIMUM EXTENT ALLOWED BY LAW, BOSTIK DISCLAIMS ALL OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING WITHOUT LIMITATION WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. UNLESS OTHERWISE STATED IN THE LIMITED WARRANTY, THE SOLE REMEDY FOR BREACH OF WARRANTY IS REPLACEMENT OF THE PRODUCT OR REFUND OF THE BUYER'S PURCHASE PRICE. BOSTIK DISCLAIMS ANY LIABILITY FOR DIRECT, INCIDENTAL, CONSEQUENTIAL, OR SPECIAL DAMAGES TO THE MAXIMUM EXTENT ALLOWED BY LAW. DISCLAIMERS OF IMPLIED WARRANTIES MAY NOT BE APPLICABLE TO CERTAIN CLASSES OF BUYERS AND SOME STATES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATIONS MAY NOT APPLY TO YOU. It is the buyer's obligation to test the suitability of the product for an intended use prior to using it. The Limited Warranty extends only to the original purchaser and is not transferable or assignable. Any claim for a defective product must be filed within 30 days of discovery of a problem, and must be submitted with written proof of purchase.

BOSTIK HOTLINE™

Smart help™

1-800-726-7845

Bostik, Inc.

11320 W. Watertown Plank Road

Wauwatosa, WI 53226

A company of TOTAL

www.bostik-us.com



This document supersedes all previously published literature.