

09 30 00.11/BOS
BuyLine 1107



**Waterproofing
Crack Isolation
Patches &
Underlayments**



Mortars



**Grouts
Epoxies
Adhesives**

hydroment[®]

Product information also available at:

www.sweets.com • www.bostik-us.com
www.arcat.com

Now Featuring
STONEWALL HIGH PERFORMANCE
& NON-SAG MORTAR
& EZPOXY GROUT & MORTAR



#1 NAME IN THE INDUSTRY

Bostik Hydroment Brand Products are recognized for high quality, high performance results when installing all types of ceramic tile and natural stone.

We always have the products you need, and our warranty protects you and your reputation.



OUR GREEN MISSION



As a global leader in adhesives, coatings and sealant technologies, Bostik continuously strives to commercialize products that minimize environmental impact and promote the health and well being of our customers. Bostik shall demonstrate these objectives by achieving compliance with the most rigorous standards set forth by industry recognized green building authorities. All products displaying the USGBC logo are LEED compliant. to learn more about our GREEN MISSION visit us at www.greenmission.bostik-us.com.



Each product displaying Bostik's Blockade antimicrobial protection logo contains an agent which inhibits the growth of bacteria, mold, or mildew on the surface of the dried adhesive/membrane; the dried adhesive/membrane resists stains caused by mold. to obtain specific test information by product, please contact Bostik's Technical Service Department at 1-800-523-6530.

PRODUCT SELECTION CHART

PRODUCT NAME	DESCRIPTION	TILE TYPES	SUBSTRATES	SPECIFICATION	PAGE
SURFACE PREPARATION SYSTEMS					3-6
SL-150	Self-Leveling Underlayment	N/A	1,2,4,5,7	-	6
Fast Patch 102	Fast Setting Feather to 1/2"	N/A	1,2,4,5,6,7	-	6
Natural Cork	1/4" Sound Deadening			ISO-R-140 Standard for IIC Requirements	6
Bostik - Universal Primer		N/A	1,2,4		6
Ultra-Set Advanced (low odor)	Waterproofing & Crack Isolation Membrane	ABCDEFGH	1,2,3,4,5,6,7,8	ANSI A118.10	4
Gold	Waterproofing & Crack Isolation Membrane	N/A	1,2,3,4,5	ANSI A118.10	5
Black-Top 90210	Waterproofing & Crack Isolation Membrane	N/A	1,2,3,4,5,6,7	ANSI A118.10	5
MORTARS & THIN-SETS					7-9
ReFlex	High Performance, Flexible	ABCDEFH	1,2,3,4,5,6,7	A118.4 & A118.11	7
Single-Flex ES.	Fast Setting, Latex Thin-Set	ABCDEFH	1,2,3,4,5,6,7	A118.4 & A118.11	7
Single-Flex	Premium Multi-Purpose Latex Thin-Set	ABCDEFH	1,2,3,4,5,6,7	A118.4 & A118.11	7
StoneWall	High Performance & Non-Sag Mortar	ABCDEFH	1,2,3,4,5,6,7	A118.4 & A118.11	7
Big Tile & Stone	Premium Latex Medium Bed Mortar	ABCDEFH	1,2,3,4,5,6,7	A118.4 & A118.11	8
DitraSet Thin-Set Mortar	Premium Portland Cement Thin-Set Mortar	ABCDEFH	1,2,3,4,5,6,7	A118.1, (A118.4 & A118.11)*	9
Hydroment PM	General Purpose, Latex Thin-Set	ABCDEFH	1,2,3,4,5,6,7	A118.4 & A118.11	8
Porcelain-Mate	Thin-Set Mortar	ABCDEFH	2,4	A118.1 & A118.4	8
Tile-Mate Premium	Premium Portland Cement Thin-Set Mortar	ABCDEFH	1,2,3,4,5,6,7	A118.1, (A118.4 & A118.11)*	8
Hot Weather Mix	Premium Portland Cement for Hot & Dry Environments	ABCEFH	1,2,3,4,5,6,7	A118.1 (A118.4 & A118.11)*	9
Tile-Mate Floor & Wall	Portland Cement Thin-Set	ABCDEFH	1,2,3,4,5,6,7	A118.1, (A118.4 & A118.11)*	9
<i>*mixed with 425 Multi-Purpose Acrylic Latex Admixture or 447 Flex-A-Lastic</i>					
ADMIXTURES					10
425 Multi-Purpose Acrylic Latex Admixture	Acrylic Admixture for Cement Grout, Thin-Set, Mortarbeds & Priming	ABCDEFH	1,2,3,4,5,6,7	A118.4, A118.6, A118.7 & A118.11	10
447 Flex-A-Lastic Flexible Mortar Admixture	High Performance Flexible Admixture for Tile-Mate Thin-Sets	ABCDEFH	1,2,3,4,5,6,7	A118.4 & A118.11	10
MASTICS (ORGANIC ADHESIVES)					11
Hydroment Ultra-Premium Mastic	Interior Applications, Walls, Ceilings, Floors & Countertops	ABCDFH	1,2,3,4,5	A136.1 Type 1 & 11	11
Hydroment Multi-Purpose Mastic	Interior Applications, Walls, Ceilings, Floors & Countertops	ABCDF	1,2,3,4,5	A136.1 Type 1 & 11	11
Hydroment Professional Grade Mastic	Interior Applications, Walls, Ceilings, Floors & Countertops	ABCDF	1,2,3,4,5	A136.1 Type 1 & 11	11
GROUTS					12-13
Hydroment Ceramic Tile Grout (sanded)	Portland Cement Grout 1/8" to 1 1/2"	ABCDEFGH	N/A	A118.6 & A118.7 **	12
Hydroment Dry Tile Grout (unsanded)	Portland Cement Grout 1/8" or less	ABCDEFGH	N/A	A118.6 & A118.7**	12
Hydroment 1900 Modified Epoxy	Stain Resistant, Modified Epoxy	ABCDEFH	1,2,4,5,6,7	A118.8	13
EzPoxy™	100% Solids Epoxy Grout & Mortar	ABCDEFH	N/A	A118.3	13
<i>**mixed with 425 Multi-Purpose Acrylic Latex Admixture</i>					
SPECIALTY PRODUCTS					14
Tub & Tile Caulk	Interior Latex Caulk	-	-	-	14
Pure Silicone Caulk	Interior/Exterior Waterproof Temperature & Chemical Resistant Caulk	-	-	-	14

LEGEND:

TILE TYPES

A	Non-Vitreous
B	Semi-Vitreous
C	Vitreous
D	Impervious/Porcelain
E	White Translucent Marbles
F	Granite, Stable Stones, Slate


G	Moisture Sensitive Stone (i.e. Russo LeVanto and Nero Marquina Marble or Green Marble and their Agglomerates)
H	Large Ceramic Tile, Stable Stone and Granite

SUBSTRATES

1	Plywood	6	Properly Prepared Vinyl/VCT Tile
2	Concrete	7	Cutback Residue
3	Gypsum Wallboard	8	Cementitious Backer Units
4	Cementitious Backer Units		Clean Steel
5	Properly Prepared Ceramic Tile		

WATERPROOFING &

WATERPROOFING MEMBRANE



4



ULTRA-SET® ADVANCED

Ultra-Set Advanced™ is a tenacious, one-part, trowel applied, elastomeric waterproofing/crack/sound isolation membrane and setting adhesive. Use Ultra-Set Advanced as a waterproofing, crack, and sound isolation membrane over properly prepared concrete; structurally-sound, exterior grade plywood (interior/dry use only); cementitious backer board; and existing, well-bonded vinyl/VCT or ceramic tile; prior to the installation of ceramic or stone tile. Ultra-Set Advanced may be used with gypsum based underlayments in dry, above grade installations with minimum compressive strengths of 2,000 psi.

Ultra-Set Advanced is available in 5 gallon pail, 2 gallon pails and 30 oz. sausages.



Where Ultra-Set Advanced has been performing for over a decade...

Holiday Inns
McDonald's Restaurants
Steak & Ale Restaurants

Hyatt Regency Hotels
Ohio State University
The Transamerica Building

Mariott Courtyards
Tysons Corner Mall
Vons Groceries

Disney World
T.G.I. Friday's
Applebee's

CRACK ISOLATION SYSTEMS

09 30 00.11/BOS

BuyLine 1107

WATERPROOFING & CRACK ISOLATION



GOLD™

Gold™ is a ready to use, latex waterproofing and anti-fracture membrane for use beneath thin-set ceramic tile installations on vertical and horizontal surfaces.

Gold exceeds the requirements of ANSI A118.10 (specification for waterproof membranes beneath thin set tile and stone) and the proposed ANSI A118 specification for crack isolation membranes.


Use Gold in commercial or residential applications. Apply over concrete, cement block walls, cement backer board, gypsum board, exterior grade plywood (interior, dry installations only) and mortar beds.

Available in 3.5 gallon and 1 gallon containers.


- Dries in 1-3 hours
- Cleans up with water



AS A CRACK ISOLATION MEMBRANE



SHOWER DRAIN DETAIL WITH STANDARD CEMENT PREFLOAT



BLACK-TOP™ 90210

A liquid applied, fabric-reinforced waterproofing and crack isolation membrane. Black-Top 90210 may be used for both heavy duty and residential applications.

Use in commercial kitchens, pools, showers, fountains, spas, hospitals, schools, malls, airports, etc.

Applies as easy as paint. Dries in 2-4 hours. minimal thickness does not add elevation.

Exceeds the requirements of ANSI A118.10.

Available in 1 gal. and 6 gal. containers.



09 30 00.11/BOS
BuyLine 1107

PATCHES/UNDERLAYMENTS



SL-150™

SL-150 is a high compressive strength, self-leveling, cement-based underlayment used to repair, smooth and level concrete as well as existing ceramic, terrazzo or approved plywood sub-floors prior to the installation of carpet, vinyl, VCT, laminate, solid and engineered hardwood flooring, ceramic or natural stone. SL-150 is suitable for thickness from featheredge to 1" thick; or up to 5" thick when mixed as designed with pea gravel. Use on, above or below grade. Use SL-150 in smaller installations where it may be mixed by hand; or use underlayment pump to quickly cover large jobs. Mix with water. Prime all surfaces with Bostik Universal Primer.

Available in 50 lb. bags.



FAST PATCH 102™

Fast Patch 102 is a fast setting, high performance, polymer-modified cement-based patch used to repair holes, cracks, and uneven surfaces from feather edge to 1/2" thick.

Mix with water.

Available in 25 lb. bags.



NATURAL CORK SOUND CONTROL UNDERLAYMENT

1/4" thick rolled cork underlayment provides a sound barrier for all types of tile and stone flooring. Install Natural Cork with a Hydroment mastic. Set tile over the underlayment with a Hydroment latex-modified thin-set mortar. This system offers a single source warranty!



UNIVERSAL PRIMER

Universal Primer is designed for use with Hydroment SL-150™ Self Leveling Underlayment and all Self Leveling Underlayments. Use Universal Primer over concrete, approved plywood substrates; cement backer board, existing ceramic tile, marble, granite, and terrazzo or cut back adhesive residues.

Available in 5 gal. and 1 gal. containers.



TYPICAL PHYSICAL PROPERTIES

PRODUCT	SET TIME	COMPRESSIVE STRENGTH	MAX DEPTH
SL-150	2 hours	5500 psi	1"*
Fast Patch 102	2 hours	4900 psi	1/2"
* 5" with pea gravel.			

Here are just a few of the places you'll find Hydroment® products at work...

Best Western Hotels
Epcot Center
Holiday Inns
J.C. Penny
McDonald's Restaurants
Sears & Roebuck Co.
Texasco
United Nations Plaza

Burger King
The Gap Clothing Stores
Hyatt Regency Hotels
Macy's
Neiman-Marcus Stores
Shell Oil Co.
T.G.I. Friday's
Wendy's

Outback Steakhouse
Applebee's
Target
Walmart
Lowe's
Menards
Wells Fargo
Bank of America

Coca-Cola Bottling Cos.
Hilton Hotels
IBM Corporations
Proctor & Gamble Co.
Taco Bell
Trump Tower
William Sonoma Stores
Kaufman's

Lord & Taylor
Kohl's
Cleveland Brown's Stadium
Marriott Hotels
Angels Stadium
Newark International Airport
Ohio Stadium
Bank One Headquarters

MORTARS & THIN-SETS

09 30 00.11/BOS

BuyLine 1107

MORTARS & THIN-SETS

7



REFLEX®

(718 white/918gray)

Use ReFlex for the toughest residential and commercial applications, deflection up to 1/240, difficult tile such as porcelain, or for any job that requires an extremely high performance thin-set.

ReFlex is suitable for setting porcelain, ceramic and stone tile in both interior and exterior applications. ReFlex is recommended for installing tile over plywood, backer board and approved waterproofing/crack isolation membranes and existing ceramic and vinyl flooring. Mix with water only.

Available in 50 lb. bags.



SINGLE-FLEX™ F.S.™

(FAST SETTING) (913white/973gray)

Single-Flex F.S. is a rapid setting, multi-purpose latex modified thin-set mortar. For added convenience, Single-Flex F.S. is available in 25 and 50 lb. bags.

Use Single-Flex F.S. where there are limited downtime concerns, or to set and grout tile in the same day.

Mix Single Flex F.S. with water or 425 Multi-Purpose Acrylic Latex Admixture for improved bond strength and flexibility.

Single-Flex F.S. is suitable for setting porcelain, ceramic and stone tile in both interior and exterior applications. Single-Flex is recommended for installing tile over plywood, backer board and approved waterproofing/crack isolation membranes and existing ceramic and vinyl flooring.

Available in 50 lb. and 25 lb. bags.



SINGLE-FLEX™

(716 white/916gray)

Single-Flex is suitable for setting porcelain, ceramic and stone tile in both interior and exterior applications. Single-Flex is recommended for installing tile over plywood, backer board and approved waterproofing/crack isolation membranes, as well as existing ceramic and vinyl flooring. Mix with water only.

Available in 50 lb. bags.



STONEWALL HIGH PERFORMANCE & NON-SAG MORTAR

StoneWall is for interior or exterior, commercial or residential installations to set all types of porcelain, Saltillo, ceramic, granite, slate, marble, limestone, and dimension stone tiles. StoneWall is formulated to prevent large bodied ceramic, porcelain and stone tiles from slipping in vertical applications. StoneWall is also suitable for installing floor tiles.

- Excellent for Large Bodied Tile and Stone in Vertical Applications.
- Exceeds ALL requirements of ANSI A118.1, A118.4 and A118.11.
- Excellent for use on all approved floors and walls.
- For interior and exterior jobs.
- High Compressive Strengths for Extra Heavy Service.

Available in 50 lb. bags.



TYPICAL PHYSICAL PROPERTIES

	ReFlex™	Single-Flex F.S.™ w/425	Single-Flex F.S.™ w/water	Single-Flex™	StoneWall™
Final Set	10-15 hours	60-90 min.	60-90 min.	15 hours	10-15 hours
28 day Shear Strength					
• Porcelain Tile	576 psi.	575 psi.	490 psi.	450 psi.	575 psi.
• Glazed Wall Tile	560 psi.	525 psi.	500 psi.	450 psi.	550 psi.
• Quarry Tile	425 psi.	450 psi.	400 psi.	440 psi.	425 psi.
• Quarry Tile/Wood	300 psi.	260 psi.	250 psi.	250 psi.	300 psi.
28 day Compressive Strength	3600 psi.	3166 psi.	3100 psi.	3450 psi.	3403 psi.

MORTARS & THIN-SETS (CONT.)



BIG TILE & STONE™ MORTAR

(911 white/966 gray)

Big Tile and Stone is a latex-modified medium bed mortar designed for setting large floor tile. Big Tile and Stone is formulated to fill in uneven surfaces from 1/8" to 3/4" beneath the tile, minimizing lippage between tiles. Big Tile and Stone also contains surface-active agents to provide maximum transfer between the mortar and tile.

Big Tile and Stone is suitable for setting porcelain, ceramic and stone tile in both interior and exterior applications. Big Tile and Stone is recommended for installing tile over plywood, backer board and approved waterproofing/crack isolation membranes and over existing ceramic and vinyl flooring.

Available in 50 lb. bags.



TILE-MATE® PREMIUM

(710 white/760 gray)

Tile-Mate is a premium dual-purpose Portland cement thin-set mortar. Tile-Mate may be mixed with water for traditional masonry substrates for setting ceramic tile and natural stone in interior applications.

Mix Tile-Mate with 425 Multi-Purpose Acrylic Latex Admixture or 447 Flex-A-Lastic for exterior installations, porcelain tile, applications over plywood, cement board and approved waterproofing/crack isolation membranes, as well as existing ceramic and vinyl flooring.

Available in 50 lb. bags.



HYDROMENT PM™

(717 white/ 917 gray)

Polymer-modified thin-set mortar is suitable for setting porcelain, ceramic and stone tile in both interior and exterior applications. Hydroment PM is recommended for installing tile over plywood, backer board and approved waterproofing/crack isolation membranes as well as existing ceramic and vinyl flooring.


Available in 50 lb. bags.



PORCELAIN-MATE™

Porcelain Mate is for setting all types of ceramic, porcelain, granite, slate, marble, limestone, and dimension stone tiles. Use over properly prepared concrete, cement backer board, cured mortar beds, brick and cement block.

Available in 50 lb. bags.



TYPICAL PHYSICAL PROPERTIES

	Big Tile & Stone™	Hydroment PM™	Porcelain-Mate™ w/water
Final Set	10-15 hours	15 hours	12 hours
28 day Shear Strength			
• Porcelain Tile	375 psi.	400 psi.	250 psi.
• Glazed Wall Tile	557 psi.	443 psi.	300 psi.
• Quarry Tile	300 psi.	300 psi.	225 psi.
• Quarry Tile/Wood	250 psi.	200 psi.	N/A
28 day Compressive Strength	3400 psi.	3000 psi.	3200 psi.



DITRASET™ THIN-SET MORTAR

DitraSet is composed of select, proprietary chemicals, carefully graded aggregates, inorganic adhesion promoters and purified cements. It provides outstanding workability, excellent durability, and superior bond strengths in interior and exterior applications when used in conjunction with Schluter-DITRA uncoupling membrane over substrates approved by Schluter Systems and to set ceramic, porcelain and stone tile of Schluter-DITRA.

Available in 50 lb. bags.



TILE-MATE® FLOOR & WALL

(712 white/762 gray)

A dual purpose Portland cement mortar.


Available in 50 lb. bags.



HOT WEATHER MIX™

(715 white)

Designed for dry high temperature environments, Hot Weather Mix contains additional water retaining additives to prevent skinning in dry, hot climates. Mix with water. Not for porcelain tile or non-masonry substrates. (West Coast Only)



TYPICAL PHYSICAL PROPERTIES						
	Tile-Mate Premium™ w/447	Tile-Mate Premium™ w/425	Tile-Mate Premium™ w/water	Tile-Mate Floor/Wall w/447	Tile-Mate Floor/Wall w/425	Tile-Mate Floor/Wall w/water
Final Set	9-12 hours	9 hours	12 hours	9-12 hours	9 hours	12 hours
Shear Strength						
• Porcelain Tile	490 psi.	470 psi.	200 psi.	450 psi.	420 psi.	200 psi.
• Glazed Wall Tile	615 psi.	504 psi.	300 psi.	575 psi.	500 psi.	280 psi.
• Quarry Tile	450 psi.	370 psi.	225 psi.	400 psi.	350 psi.	215 psi.
• Quarry Tile/Wood	200 psi.	175 psi.	N/A	200 psi.	175 psi.	N/A
Compressive Strength	3200 psi.	3300 psi.	3200 psi.	3200 psi.	3300 psi.	3100 psi.

ADMIXTURES



425 MULTI-PURPOSE ACRYLIC LATEX ADMIXTURE™

This admixture is a versatile high solids acrylic emulsion with five primary applications.

Grout Admixture
Thin-Set Admixture
Mortar Bed Admixture
Bond Coat Admixture

425 Multi-Purpose Acrylic Latex Admixture may be mixed with Hydroment Ceramic Tile Grout to comply with ANSI 118.6 and ANSI 118.7 requirements. When mixed with grout, 425 Multi-Purpose Acrylic Latex controls the cure rate, producing excellent physical strengths, flexibility, and color uniformity. The addition of 425 Multi-Purpose Acrylic Latex Admixture to grout helps minimize cracking in wood framed structures and helps reduce staining because it lowers the porosity of the grout.

When mixed with Tile-Mate thin-set mortars, 425 Multi-Purpose Acrylic Latex Admixture exceeds the requirements of both ANSI A118.4 and ANSI A118.11. Use over plywood, existing vinyl or ceramic flooring, and exterior installations subject to moisture and freezing.

Use 425 Multi-Purpose Acrylic Latex Admixture instead of water for preparing mortar beds and bond coats in traditional thick bed applications to improve water resistance and durability.

Available in 5 gallon, 2 gallon, 1 gallon and quart containers.



447 FLEX-A-LASTIC®, FLEXIBLE MORTAR ADMIXTURE

This admixture is an extremely high solids, high-performance acrylic emulsion designed to be mixed full strength with Tile-Mate thin-set mortars. Use 447 Flex-A-Lastic wherever maximum performance is desired. **Use over difficult, non-traditional substrates, existing vinyl or ceramic flooring, exterior installations subject to moisture and freezing, and floors with deflection up to 1/240.** The tacky consistency of Flex-A-Lastic is excellent for setting large wall tile as well.

When mixed with Tile-Mate thin-set mortars, Flex-A-Lastic exceeds the requirements of ANSI A118.4 and ANSI A118.11.

Available in 5 gallon and 2 gallon containers.



MASTICS (ORGANIC ADHESIVES)

09 30 00.11/BOS

BuyLine 1107

MASTICS



HYDROMENT ULTRA-PREMIUM™ MASTIC

Ultra-Premium high performance mastic for interior installations of ceramic, porcelain and stone tiles. Hydroment Ultra-Premium is ready to use and provides excellent vertical

grab for large body wall tile.

Ultra-Premium Mastic exceeds the requirements of ANSI A136.1 (Type 1) mastics. Hydroment Ultra-Premium mastic may be used over concrete, cement block, cement backer board, Dens Shield, gypsum wallboard, veneer plaster, Hydroment Ultra-Set, Black-Top 90210 and Gold membranes.



Available in 3.5 gallon, 1 gallon, and quart containers.



HYDROMENT MULTI-PURPOSE™ MASTIC

A multi-purpose mastic for interior installations of ceramic, porcelain and stone tiles. Hydroment Multi-Purpose is ready to use and

provides excellent vertical grab.

Hydroment Multi-Purpose exceeds the requirements of ANSI A136.1 (Type 1) mastics. Hydroment Multi-Purpose may be used over concrete, cement block, cement backer board, Dens Shield, gypsum wallboard, veneer plaster, Hydroment Ultra-Set, Black-Top 90210 and Gold membranes.



Available in 3.5 gallon and 1 gallon containers.



HYDROMENT PROFESSIONAL GRADE™ MASTIC

Hydroment Professional Grade Mastic exceeds the requirements of ANSI A136.1 (Type 1 & 2) mastics. Hydroment Professional Grade

can be used over concrete, cement block, cement backer board, Dens Shield, gypsum wallboard, veneer plaster.



Available in 3.5 gallon and 1 gallon containers.



AVAILABLE IN 46 COLORS

GROUTS

Standard Series

Champagne	H138
French Gray	H142
Mohe Pearl	H145
Antique White	H125
White	H152
Natural	H146
Kahila Cream	H143
Sand Beige	H148
Fash Walnut	H141
Char Black	H135
Misty Gray	H144
Brick	H136
Taupe	H131
Peaches & Cream	H147
Summer Wheat	H150
Latte	H192
Shadow	H194
Bamboo	H179
Cashmere	H178

Designer Series

Cambridge	H167
Sea	H168
Classic Bone	H158
Blonde White	H163
Melrose	H169
Baronetta	H184
Ivory Palace	H185
Arise	H187
Seaside	H191
Almond	H182
Loose	H160
Myst	H165
Ice Blue	H161
Heaven Blue	H171
Blue Harbor	H166
Bright White	H177
Delorean Gray	H160
Jewels	H162
Woodlands	H194
Scaven	H186

Regency Series

Midnight Blue	H172
Essex Green	H170
Amalfi Red	H188
Windsor Blue	H191
Twilight	H193
Merlot Central	H182
Asacala	H180

Please refer to Grout Selector Card for color selection.



HYDROMENT® CERAMIC TILE GROUT (SANDED)

Hydroment Ceramic Tile Grout is a proven blend of quartz aggregates, specialty cements and colorfast pigments. Hydroment Grouts are available in 46 colors.

Use Hydroment Ceramic Tile Grouts for grouting ceramic tile, porcelain tile, quarry tile, brick pavers, slate, marble, granite and structural glazed block from

1/8" to 1 1/2". Hydroment Ceramic Tile Grout may be used for interior or exterior applications

Hydroment Ceramic Tile Grout meets the requirements of ANSI A118.6 mixed with water and A118.7 mixed with 425 Multi Purpose Latex Admixture.

Available in 25 lb. and 9 lb. bags.



CERAMIC TILE GROUT TYPICAL PHYSICAL PROPERTIES

Pot Life	1 hour
Setting Time	
• Initial set	1-3 hours
• Final set	3-8 hours
Compressive Strength (ANSI requirement 3500 psi)	
• 1 day	3500 psi
• 7 day	4000 psi
• 28 day	5000 psi



HYDROMENT® DRY TILE GROUT (UNSANDED)

Dry tile grout is a proven blend of quartz aggregates and specialty cements and colorfast pigments.

Use Dry Tile Grout where joints are less than or equal to 1/8" wide. Dry tile grout is ideal for grouting ceramic tile, porcelain tile, marble and granite.

Available in 25 lb. (selective colors) and 5 lb. bags.



The Hydroment Grout Selector Card is the standard for color selection, manufacturing, and quality control. Colors may vary due to jobsite conditions, absorption of tile, mixing ratios, or installation methods or from batch to batch and therefore may vary significantly from Grout Selector Card.

EzPOxy™ GROUT & MORTAR



Used for interior or exterior, vertical or horizontal installations. Typical applications include commercial kitchens, lobbies, bathrooms, fast food restaurants, breweries, dairies, wineries, factories, shopping malls, meat processors, and distilleries.

As a Mortar: Suitable bonding mortar for interior applications only. Use to set all ceramic, quarry, porcelain, granite, slate, pre-cast Terrazo, dimension stone tiles and moisture sensitive stone. Use over properly prepared concrete; structurally sound exterior grade plywood (interior/dry use only); cementitious backer board; Hydroment Gold, UltraSet Advanced, Black-Top 90210 and existing well bonded vinyl/VCT or ceramic tile. As a bonding mortar, EzPOxy should be for interior use only.

As a Grout: Use to grout all ceramic, quarry, porcelain, granite, slate, and pre-cast Terrazo, dimension stone tiles, in joints from 1/16" to 1/2" wide.

Available in kits containing 15 lb. and 30 lb. containers. (Kits contain Powder Aggregate, Part A Resin and Part B Hardener.)



HYDROMENT 1900™

1900 is a two-component epoxy admixture designed to be mixed with Hydroment Ceramic Tile Grout (sanded only – except white). Hydroment 1900 creates a modified epoxy grout and setting mortar with exceptional stain resistance and tenacious adhesion – all with workability like a traditional Portland cement grout or mortar.

The Hydroment 1900 System exceeds the requirements of ANSI A118.8 for modified epoxy grout and mortar. Use 1900 for grouting ceramic tile, porcelain tile, quarry tile, brick pavers, slate, marble, granite and structural glazed block wherever a high resistance to staining is required.



1900 TYPICAL PHYSICAL PROPERTIES

Shear Strengths (psi)	1 day	7 days	28 days
Glazed	240	439	600
Ceramic Mosaic	128	378	387
Quarry	179	372	475
Glazed to wood	—	251	300
Quarry to wood	—	263	280
<i>Minimum shear values due to failure of wood substrate.</i>			
Compressive Strengths: ASTM C-109 Modified			
7-day compressive strength			5500 psi
28-day compressive strength			7500 psi
7-day tensile strength			492 psi
Initial set @ 70°F			5 hours
Final set			15 hours
Pot life @ 70° F			1 hour, 30 min.
Adjustable time @ 70°F			1 hour, 20 min.
Open time @ 70°F			1 hour

Hydroment Ceramic Tile Grout when mixed with 1900 Epoxy Modified Admixture will be darker and richer in color.



09 30 00.11/BOS
BuyLine 1107

SPECIALTY PRODUCTS



PURE SILICONE CAULKING

Pure Silicone Caulking from Bostik is a 100% RTV Curing Silicone Caulking which is waterproof and permanently flexible. Use

Pure Silicone Caulking in tub surrounds to seal drains, fixtures, and plumbing penetrations.

Use as an adhesive or bedding compound for countertops, soap dishes and thresholds. Pure Silicone Caulking is highly chemical resistant and can withstand temperatures to 400°F.

Pure Silicone Caulking is available in clear and white and is sold in 10.1oz caulking cartridges.



REMOVE™

Remove™ is a specially formulated, non-acidic, non-abrasive latex grout cleaning concentrate. Its powerful surface active agents, wetting agents and sequestrants penetrate and remove latex film from ceramic tile surfaces and grout. Remove™ can cut cleaning time in half and has no odors.



HYDROCLEAN™

This very fine, pumice based cleaning powder removes all types of difficult stains including grout and epoxy haze, dirt and common grime. Use HydroClean on new and existing ceramic, porcelain, quarry, slate, brick, block, concrete and concrete pavers, polished granite, flamed granite and Saltillo tile.

TUB & TILE CAULK FROM CERAMASEAL®

This water cleanable caulking is available in sanded and unsanded formulas, and comes in all complementary Hydroment Colors. Use in tub surrounds, countertops, walls, floors. Interior applications only.



GROUT STAIN BY CERAMASEAL®

This oil-based stain is used to restore the color of grout. Grout stain is also an excellent grout sealer.



CeramaSeal Grout Stain is an extremely durable product with excellent hiding power. Grout Stain is available in all Hydroment Colors (except Natural) and is sold in pint cans.





Ceramic Tile Installation Warranty
5 Year • 10 Year • 25 Year

All Bostik warranties require applicable ANSI A108 specifications are followed along with the proper procedures outlined in Bostik most recently published literature for surface preparation, setting and grouting.

In the event of breach of warranty, Bostik will pay for replacement of tile, labor and related finishing materials on a square foot basis only on the portion of the installation that is proven to be defective. This payment is to include all reasonable materials and labor. Bostik is not responsible for workmanship not in accordance with Bostik most recently published literature or damages due to hydrostatic head. This warranty does not cover industrial applications subject to chemical and mechanical abuse or improper selection of tile. Bostik is not liable for damage caused by excessive structural movement; natural disasters such as earthquakes, fires, floods, and hurricanes; or for losses due to delays or any consequential damages.

	Substrate Description	Setting Materials	Grouting Materials
25 Year	Concrete on/above grade; or Ultra-Set Advanced waterproofing/crack isolation membrane/Black-Top 90210.	Single Flex F.S. mixed with #425 Multi-Purpose Admix, Tile-Mate 710/760 mixed with #447 Flex-A-Lastic, ReFlex, StoneWall or Big Tile & Stone Mortar.	Ceramic Tile Grout mixed with #425 Multi-Purpose Admix, or Hydroment 1900 Epoxy.
10 Year	Concrete/Cement Backer Units; Exterior Grade Plywood; or Gold, Ultra-Set Advanced waterproofing/crack isolation membrane.	Single Flex F.S., Single Flex, Tile-Mate 710/760 mixed with #425 or Multi-Purpose Admix.	Ceramic Tile Grout mixed with #425 Multi-Purpose Admix.
5 Year	Concrete/Cement Backer Units; Exterior Grade Plywood; or Gold, Ultra-Set Advanced waterproofing/crack isolation membrane.	Hydroment PM, Tile-Mate mixed with water or Porcelain Mate mixed with water	Ceramic Tile Grout mixed with water.
5 Year Wall Tile	Concrete, Cement Backer Board, Cement Block, Cement Mortar, Gypsum Board, Veneer, Plaster.	Ultra Premium Mastic. or Hydroment StoneWall	Ceramic Tile Grout mixed with water.

BOSTIK WARRANTIES ARE NOT TRANSFERABLE.
Contact Bostik Technical Service for job specific recommendations and warranties.



**Proud member of
the green clique.**

hydroment

Go to www.greenmission.bostik-us.com



Bostik

www.bostik-us.com • 888-592-8558

hydroment

Boston Street, Middleton, MA 01949
Phone: (800) 7-BOSTIK (800-726-7845) or (888) 592-8558
Fax: (978) 750-7212
Technical Service: (800) 523-6530
Email: contactus@bostik-us.com
Visit our website at www.bostik-us.com

Bostik

Printed in USA 10/07 12.5M