



November 13, 2008

Dear Bostik Customer:

Congratulations for your forward thinking and the environmentally conscious design of your current construction project. Bostik is pleased to be a U.S. Green Building Council member and a major proponent of the L.E.E.D. initiative in the construction materials industry.

Bostik is a leader in the adhesive, sealant and coatings segment of the construction market with one of the most comprehensive product offerings available, all backed by strong system warranties. Bostik is the 4th largest adhesive and sealant company in the world. The greatest advantage of utilizing all of our products for your flooring system and construction sealants/adhesives is that you have only one manufacturer to deal with if questions or concerns arise. Additionally, we have a dedicated sales and technical service organization that is at your service any time you need assistance.

Attached is a complete list of the Bostik products that may contribute to the qualification of a project for LEED-NC V2.2 certification under the following Indoor Environmental Quality credits for low emitting materials; EQ 4.1 Adhesives & Sealants, EQ 4.2 Paints & Coatings and EQ 4.3 Carpet Systems. (An extract of these standards is attached for your review.) The intent of these one-point credits is to reduce the quantity of indoor air contaminants that are odorous, potentially irritating and/or harmful to the comfort and well-being of installers and occupants.

If you have any questions regarding our product offering, please contact Bostik directly at (978) 7/BOSTIK. Once again, we look forward to working with you on this exciting project.

Regards, Scott J. Banda

Philip J.Pitts

Market Manager LEED<sup>•</sup> Accredited Professional Ceramic Installation Systems

Bostik, Inc. Construction & Distribution Division 211 Boston Street Middleton, MA 01949-2128 USA Tel: 978.777.0100 - Fax: 978.750.7802 www.bostik-us.com

C20

Ptsi 7 Pot

Market Manger Hardwood Installation Systems

James Downing

Market Manager Construction Adhesives and Sealants, Carpet/Vinyl/Patch Installation Systems



## Low-VOC Product Portfolio Adhesives/Sealants/Coatings

## DURABOND\*

Durabond® Hardwood Products	Product VOC	NAHB Model Green Home Guideline (based upon CARB VOC levels)	Product VOC g/L	USGBC LEED- NC/ LEED-H Standard (SCAQMD VOC levels)
		Weight %		g/L
		Moisture Vapor Pro	tection	
D-288™ Moisture Vapor Retarder	8.3	N/A	126	250
		Hardwood Adhesi	ves	
D-332 <sup>™</sup> Premium Wood Flooring Adhesive	5.8	15	86	100
D-321 <sup>™</sup> Moisture Cure Jrethane Adhesive	0	15	0	100
D-317 <sup>™</sup> Elastomeric Wood Flooring Adhesive	8.0	15	85	100
Durabond® Ceramic Products	Product VOC	NAHB Model Green Home Guideline (based upon CARB VOC levels)	VOC g/L	USGBC LEED- NC/ LEED-H Standard (SCAQMD VOC levels)
		Weight %		g/L
	Wat	erproofing & Antifractu	re Membrane	
D-222 DuraGuard™ <sup>Waterproofing</sup> Membrane	1.1	N/A	12.5	250
		Grouts/Epoxies	;	
TruColor <sup>™</sup> Pre-Mixed Grout	2.1	N/A	35	65
D-190 DuraPoxy <sup>™</sup> Epoxy-Modified Grout and Mortar Admixture	0	N/A	0	65
EzPoxy™ 100% Solids Epoxy Grout & Mortar	0	N/A	0	65
Fortified Tile Grout Sanded	0	N/A	0	N/A
Fortified Tile Grout (Unsanded)	0	N/A	0	N/A
		Liquid Admixtur	es	
D-L16 <sup>™</sup> High Strength Mortar and Grout Additive	0	N/A	0	65
		Thin Set Morta	'S	
D-70 <sup>™</sup> ProFlex	0	N/A	0	N/A
D-65™ High Performance & Non Sag Mortar	0	N/A	0	N/A
D-60 <sup>™</sup> Medium Set	0	N/A	0	NA
D-55 <sup>™</sup> Fast Set	0	N/A	0	N/A
D-50 <sup>™</sup> Flexible	0	N/A	0	N/A
D-40 <sup>™</sup> DuraFlex	0	N/A	0	N/A
D-25™ DitraSet	0	N/A	0	N/A
D-20 <sup>™</sup> Porcelain Set	0	N/A	0	N/A
D-5 <sup>™</sup> Premium	0	N/A	0	N/A
D-2 <sup>™</sup> Floor Grade	0	N/A	0	N/A



Durabond® Floor Covering Products	Product VOC	NAHB Model Green Home Guideline (based upon CARB VOC levels)	Product VOC g/L	USGBC LEED- NC/ LEED-H Standard (SCAQMD VOC levels)
		Weight %		g/L
	Moistu	re Vapor Barrier Coat	tings	
D-261™ Extreme Moisture Vapor Barrier Coating	4.0	N/A	59	250
D-250™ Moisture Vapor Barrier Coating	5.0	N/A	67	250
	N	Iultipurpose Adhesive		
D-990 <sup>™</sup> Multipurpose Adhesive	0	15	0	50
D-920 <sup>™</sup> Multipurpose Adhesive	0	15	0	50
D-910 <sup>™</sup> Multipurpose Adhesive	0	15	0	50
D-905 <sup>™</sup> Multipurpose Adhesive	0	15	0	50
		Carpet Adhesives		
D-870 <sup>™</sup> Carpet Tile & Pad Adhesive	0	15	0	50
D-860 <sup>™</sup> Double Stick Adhesive	0	15	0	50
D-850 <sup>™</sup> Carpet Adhesive	0	N/A	0	50
D-818 <sup>™</sup> Tack Strip & Multipurpose Adhesive	3.9	15	48	50
D-817 <sup>™</sup> Carpet Pad Adhesive	1.0	15	17	50
D-808 <sup>™</sup> Exterior Carpet Adhesive	0	15	0	50
		Wall Surface		
D-745 <sup>™</sup> Fire Retardant Wall Adhesive	0.9	15	15	50
D-740 <sup>™</sup> Multipurpose Wall Adhesive	1.7	15	39	50
		Hard Surface		
D-670 <sup>™</sup> Firm Set Goods and Carpet Adhesive	0	15	0	50
D-650 <sup>™</sup> Clear VCT Adhesive	0	15	0	50
D-640™ Pure Vinyl Adhesive	0	15	0	50
		Primers		
Durabond Extreme Primer	<1	N/A	7.7	250
Durabond® Patches and Underlayments	Product VOC	NAHB Model Green Home Guideline (based upon CARB VOC levels)	Product VOC g/L	USGBC LEED- NC/ LEED-H Standard (SCAQMD VOC levels)
		Weight %		g/L
	Self	Leveling Underlayment	ts	
83P <sup>™</sup> Self Leveling Underlayment	0	N/A	0	N/A
		Patches		
Webcrete <sup>®</sup> Ultra Finish	0	N/A	0	N/A
Webcrete <sup>®</sup> 95	0	N/A	0	N/A
Webcrete <sup>®</sup> 98	0	N/A	0	N/A
Webpatch 90	0	N/A	0	N/A
D-9001 Webpatch	0	N/A	0	N/A

## hydroment

Hydroment® Ceramic Products	Product VOC	NAHB Model Green Home Guideline (based upon CARB VOC levels)	Product VOC g/L	USGBC LEED- NC/ LEED-H Standard (SCAQMD VOC levels)
		Weight %		g/L
	Waterpr	oofing & Antifracture	Membranes	
Gold <sup>™</sup> Waterproofing Membrane	1.1	N/A	12.5	250
UltraSet <sup>®</sup> Advanced Antifracture Waterproofing, Crack Isolation and Sound Reducing Membrane	7.9	N/A	134	N/A
		Grouts/Epoxies		
TruColor™ Pre-Mixed Grout	2.1	N/A	35	65
1900 <sup>™</sup> Epoxy-Modified Grout and Mortar Admixture	0	N/A	0	65
EzPoxy™ 100% Solids Epoxy Grout & Mortar	0	N/A	0	65
Ceramic Tile Grout	0	N/A	0	N/A
Ceramic Tile Grout (Unsanded)	0	N/A	0	N/A
		Liquid Admixtures		
425 High Strength Mortar and Grout Additive	0	N/A	0	65
447 Flex-A-Lastic Admixture	0	N/A	0	65
		Thin Set Mortars		
ReFlex®	0	N/A	0	N/A
StoneWall <sup>™</sup> High Performance & Non Sag Mortar	0	N/A	0	N/A
Big Tile & Stone™	0	N/A	0	NA
Single Flex <sup>®</sup> FS	0	N/A	0	N/A
Single Flex®	0	N/A	0	N/A
Hydroment PM	0	N/A	0	N/A
Ditra-Set <sup>™</sup>	0	N/A	0	N/A
Porcelain-Mate <sup>™</sup>	0	N/A	0	N/A
Tile-Mate®	0	N/A	0	N/A
Tile-Mate <sup>®</sup> Floor & Wall	0	N/A	0	N/A
Bostik® Patches and Underlayments	Product VOC	NAHB Model Green Home Guideline (based upon CARB VOC levels)	Product VOC g/L	USGBC LEED- NC/ LEED-H Standard (SCAQMD VOC levels)
		Weight %		g/L
		Self Leveling Underlaym	ents	
SL-150 <sup>TM</sup> Self Leveling Underlayment	0	N/A	0	N/A
		Patches		
Fast Patch 102	0	N/A	0	N/A
		Primers		
Universal Primer	1.2	N/A	15	250

Bostik

Bostik Hardwood Products	Product VOC	NAHB Model Green Home Guideline (based upon CARB VOC levels)	Product VOC g/L	USGBC LEED- NC/ LEED-H Standard (SCAQMD VOC levels)	
		Weight %	g/L		
	N	loisture Vapor Protect	ion		
MVP <sup>4™</sup> Moisture Vapor Barrier Coating	8.3	N/A	126	250	
EMC <sup>™</sup> Epoxy Moisture Coating	5.0	N/A	67	250	
		Adhesives			
Bostik's Best	5.8	15	86	100	
TKO™ (New & Improved)	0	15	0	100	
BST™	4.6	15	72	100	
EFA+ (Elastomeric Flooring Adhesive)	8.0	15	85	100	

## Chem-Calk<sup>®</sup>

Chem-Calk® Products	Product VOC	NAHB Model Green Home Guideline (based upon CARB VOC levels)	Product VOC g/L	USGBC LEED- NC/ LEED-H Standard (SCAQMD VOC levels)
		Weight %		g/L
	Const	ruction Adhesives & S	ealants	
Chem-Calk <sup>®</sup> 900 Architectural Grade Urethane Sealant	3.9	4	48	250
Chem-Calk <sup>®</sup> 915 Construction Grade Urethane Sealant	3.9	4	53	250
Chem-Calk <sup>®</sup> 916 Textured Urethane Sealant	3.9	4	53	250
Chem-Calk <sup>®</sup> GPS1 General Purpose Urethane Sealant	2.4	4	51	250
Chem-Calk <sup>®</sup> 955-SL Self Leveling Sealant	3.9	4	51	250
Chem-Calk <sup>®</sup> 2020 Architectural Grade Hybrid Sealant	1.1	4	16	250
Chem-Calk <sup>®</sup> 2000 Construction Grade Hybrid Sealant	1.4	4	21	250
Chem-Calk <sup>®</sup> 300 General Purpose Butyl Sealant	17	4	240	250

HOME						
Bostik HOME® PRODUCTS	Product VOC	NAHB Model Green Home Guideline (based upon CARB VOC levels)	Product VOC g/L	USGBC L.E.E.D H System (based upon SCAQMD VOC levels)		
	1	Weight %		g/L		
	Cons	truction Adhesives & S	ealants			
Heavy Duty Construction Adhesive	6.9	15	105	70		
Siding ULTRA and Window Sealant	3.9	4	53	250		
Siding ULTRAclear	4.5	4	45	250		
Window & Door Sealant	3.9	4	51	250		
Roofing & Flashing Sealant	3.9	4	21	250		
Pour-a-Bull <sup>™</sup> Self Leveling Sealant	1.4	4	21	250		
Drywall Adhesive	1.7	15	39	50		
Concrete & Masonry Sealant	3.9	4	53	250		
Fiber Cement Board sealant	3.9	4	54	250		
Painters Caulk	2	15	33	250		
Siliconize Acrylic Latex Sealant	2	15	32	250		
Urethane Acrylic Latex Sealant	3.5	15	49	250		

BuildingGreen





**Bostik, Inc.** 211 Boston Street Middelton, MA 01949

Customer Service: 1-888-592-8558

Technical Service: 1-800-523-6530

Websites: www.bostik-us.com www.greenmission.bostik-us.com

G2/5M 2/2009