

## Vinyl Carpentry™ Value Soffit

### Vinyl Soffit

**General Description:** Value vinyl soffit is appropriate for use in new construction for single family homes, multi-housing projects, and light commercial developments. Value is also an ideal product for remodeling. The vented styles are for eaves installation only. The solid styles are appropriate for porch ceiling installation.

**Styles:**

Profile	Finish	Net Free Air Space Per Sq. Ft.	Panel Projection	Wall Thickness (Nominal)	Lock Design	Colors	Accessory Pocket
Triple 4" Solid	Matte	—	1/2"	.036"	Post-formed	9	1/2", 5/8" or 3/4"
Triple 4" Fully Vented	Matte	5.9 Sq. In.	1/2"	.036"	Post-formed	9	1/2", 5/8" or 3/4"
Triple 4" Center Vented	Matte	2.0 Sq. In.	1/2"	.036"	Post-formed	2	1/2", 5/8" or 3/4"
D5" Solid	Matte	—	1/2"	.036"	Post-formed	5	1/2", 5/8" or 3/4"
D5" Fully Vented	Matte	6.4 Sq. In.	1/2"	.036"	Post-formed	5	1/2", 5/8" or 3/4"

**Colors:**

Colonial White	Light Maple	Savannah Wicker	Heritage Cream	Snow
Desert Tan	Natural Clay	Sterling Gray	Herringbone	

Triple 4" Center Vented available in Colonial White and Snow only.

Double 5" Solid and Fully Vented available in Colonial White, Desert Tan, Savannah Wicker, Sterling Gray & Natural Clay.

**Lock:** Designed for ease of installation, Value panels feature a post-formed lock popular with installers for its locking assurance and trouble-free handling.

**Accessories:** CertainTeed manufactures a wide range of accessories which are compatible with Value soffit. Accessory products include installation components, receiving channels and decorative moldings.

**Composition:** Value soffit is produced using CertaVin™ custom-formulated PVC resin. This resin is produced exclusively by CertainTeed allowing CertainTeed to maintain the high quality of its siding products.

**Technical Data:** Value soffit is in compliance with ASTM specification D4477 for Rigid Polyvinyl Chloride (PVC) Soffit. Value soffit meets or exceeds the properties noted in Table 1.

Table 1

ASTM E 84	Meets Class A flame spread requirements as tested according to ASTM E84.
ASTM D 1929	Self-ignition temperature 813°F
ASTM D 635	Material is self-extinguishing with no measurable extent of burn when tested in accordance with this specification.

**Important Fire Safety Information:** When rigid vinyl siding is exposed to significant heat or flame, the vinyl will soften, sag, melt or burn, and may thereby expose material underneath. Care must be exercised when selecting underlayment materials because many underlayment materials are made from organic materials that are combustible. You should ascertain the fire properties of underlayment materials prior to installation. All materials should be installed in accordance with local, state, and federal building code and fire regulations.

**Documents:** CertainTeed Vinyl Siding meets the requirements of one or more of the following specifications.

Texas Department of Insurance Product Evaluation EC-11

Conforms to ASTM Specification D4477

Florida BCIS Approval 13389

ICC-ES Evaluation Report ESR-1066

For specific product evaluation/approval information, call 800-233-8990.


**Installation:** Prior to commencing work, verify governing dimensions of building, examine, clean and repair, if necessary, any adjoining work on which the siding is in any way dependent for its proper installation. Sheathing materials must have an acceptable working surface. Siding, soffit and accessories shall be installed in accordance with the latest editions of CertainTeed installation manuals on siding and soffit. Installation manuals are available from CertainTeed and its distributors.

**Warranty:** CertainTeed supports Value soffit products with a Lifetime Limited Warranty. The warranty is transferable if the home is sold.

**Technical Services:** CertainTeed maintains an Architectural Services staff to assist building professionals with questions regarding CertainTeed siding products. Call 800-233-8990 for samples and answers to technical or installation questions.

**Sample Short Form Specification:** Soffit as shown on drawings or specified herein shall be Value vinyl soffit as manufactured by CertainTeed Corporation, Valley Forge, PA. The soffit shall have a .036" nominal thickness (T4") or .038" nominal thickness (D5"). Installation shall be in accordance with manufacturers instructions.

**Three-part Format Specifications:** Long form specifications in three-part format are available from CertainTeed by calling our Architectural Services Staff at 800-233-8990. These specifications are also available on our website at [certainteed.com](http://certainteed.com).



CertainTeed Corporation  
P.O. Box 860  
Valley Forge, PA 19482  
[certainteed.com](http://certainteed.com)  
© 01/15