

Access Doors - Material Safety Data Sheet

---

**Section I - Supplier Information**

Trade name: GFRG\* (Glassfiber Reinforced Gypsum)  
Stonetex (Glassfiber Reinforced Faux Stone)

Chemical family:  
Manufacturer:  
Address: 8880 Elder Creek Road, Sacramento, CA 95828  
Phone: 916-381-6343  
Fax: 916-381-6344

Emergency  
Telephone Contact:  
Date Prepared: 11/21/03  
Distributor: Chicago Metallic Corp.  
Address: 4849 S. Austin Avenue, Chicago, IL 60638  
Phone: 800-323-7164

---

**Section II – Hazardous Ingredients**

<u>Chemical Names</u>	<u>CAS Numbers</u>	<u>Percent</u>
Fiberglass	65997-17-3	6%
Gypsum (non-hazardous)	10101-41-4	94%

<u>Exposure Limits in Air:</u>			
<u>Chemical Names</u>	<u>ACGIH TLV</u>	<u>OSHA PEL</u>	<u>Other</u>
Fiberglass	10 mg/m <sup>3</sup>	15 mg/m <sup>3</sup>	(10 mg/m <sup>3</sup> in CA)
Gypsum	None	None	

---

**Section III – Physical Properties**

Vapor Density (air = 1): N/A  
Melting Point or Range (F): N/A  
Specific Gravity: 2.5 approx.  
Boiling Point or Range (F): N/A  
Solubility in Water: 0.2%  
Evaporation Rate  
(Butyl Acetate = 1): N/A  
Vapor Pressure, mmHG or  
20% C: N/A  
Appearance and Odor  
Appearance: Material comes in solid “form molded” shapes.  
Odor: None

How to detect this substance: Warning properties of substance as a gas/vapor/dust or mist: N/A

---

**Section IV – Fire and Explosion**

Flash point (F) (give method): Non-Combustible  
Auto-Ignition Temperature (F): N/A  
Flammable Limits in Air  
(Volume %): N/A Lower (LEL) \_\_\_\_\_ Upper (UEL) \_\_\_\_\_  
\_\_\_\_\_ Water Spray \_\_\_\_\_ Carbon Dioxide \_\_\_\_\_ Other  
\_\_\_\_\_ Foam \_\_\_\_\_ Dry Chemical

Special Firefighting Procedures: None  
Unusual Fire and Explosion  
Hazards: None

---

## Section V – Health Hazard Information

Inhaled: Dust from grinding or cutting may cause temporary irritation.

Contact with Skin or Eyes: Dust may cause irritation, temporary itching of skin.

Absorbed Through Skin: N/A

Swallowed: No known hazard.

Suspected Cancer Agent: No. This products ingredients are not found in the lists.  
YES Federal OSHA \_\_\_\_\_ NTP \_\_\_\_\_ IARC \_\_\_\_\_

California employers using Cal/OSHA: Regulated carcinogens must register with Cal/OSHA and the Federal OSHA carcinogen lists are similar.

Medical Conditions Aggravated by Exposure: Those prone to allergies, asthma, bronchitis or pulmonary disease may experience increased irritation to the nose, throat, eyes or skin.

---

## Section VI – Reactivity Data

Stability: X Stable \_\_\_\_\_ Unstable

Conditions to Avoid: None. This material will lose its integrity when submersed in water.

Incompatibility (materials to avoid): None

Hazardous decomposition products (including combustion products): If heated to 1450°C, will release SO & CAE.

Hazardous Polymerization: \_\_\_\_\_ May Occur X Will not Occur

Conditions to Avoid: Keep product dry to maintain integrity.

---

## Section VII – Spill, Leak and Disposal

Spill Response Procedures: N/A

Preparing Wastes for Disposal (container type, neutralization, etc.): Normal disposal as for any dry, inert dust (from cutting) or solids.

Note: Dispose of all wastes in accordance with Federal, State and Local regulations.

---

## Section VIII – Special Handling Information

Ventilation and Engineering Controls: Local exhaust, if above TLV, during cutting or grinding.

Respiratory Protection: NIOSH approved respirator for dust if above TLV during cutting or grinding.

Eye Protection: Dust goggles or safety glasses during cutting or grinding.

Gloves: Light weight or work gloves may help reduce skin irritation from dust.

Other Clothing and Equipment: Coveralls or work clothes to protect street clothes from dust.

Work Practices, Hygenic Practice: Keep dust production to a minimum. Keep work area clean. Do not use compressed air to “blow down” clothing.

Wash exposed skin surfaces regularly with soap and water.

Other Handling and Storage Requirement: Store in dry area.

Protective Measures during Maintenance of Contaminated Equipment: N/A

---