



CONTINENTAL MATERIALS, INC

Fasteners • Asphalt • Underlayments • Fiberboard • Tools

*"Quality Manufactured
Components...
Making Construction
Systems Perform Better
Since 1958"*

SecureGrip 15™

Synthetic Roof Underlayment

Underlayments

visit us at www.continentalmaterials.com

*"An Effective Synthetic
Underlayment Designed
to Replace Asphalt
Saturated #15 Felt"*

- **Highly Engineered...** providing an affordable secondary water-shedding barrier for your shingle roof system.
- **Inorganic Construction...** 100% synthetic construction offers long term moisture protection - doesn't absorb water and is inert to mold growth.
- **Improves Project Outcome...** rolls out flat, will not wrinkle causing customer callbacks.
- **Easier Installation...** 33% more coverage per pass across the roof (vs 36" wide rolls).
- **Superior Performance...** designed to perform under extreme weather conditions.
- **Durable...** synthetic construction resists tearing during roof installation - UV stabilized to resist UV degradation up to 3 months.



Synthetic Roofing Underlayment

"Effective Replacement for Traditional #15 Felt on your Roofing Projects!"



Description

CMI SecureGrip 15™ Synthetic Roof Underlayment is a synthetic roof-deck protection designed and manufactured to replace asphalt saturated #15 felt in sloped roof system construction.

Uses

A cost effective roofing underlayment used beneath fiberglass and asphalt shingles, stone coated metal roofing shingles or sloped installations of standing seam metal panels.

Storage

Always store rolls upright on pallets (or in the cradled pallet they are shipped on) and in a dry protected area.

Availability

SecureGrip Synthetic Felts are available throughout the United States. Check with your local representative for product availability.

Specifications (meets or exceeds applicable standards)		
	Standard	SecureGrip15
Permeability	ASTM E96	.06 perms
Water Transmission	ASTM D4869	pass
Nail Sealability	ASTM D1970	pass
Pliability	ASTM D226	pass
Tear Strength	ASTM D4533	MD 27 lbs / CD 27 lbs
Tensile Strength	ASTM D751	MD 65 lbs / CD 65 lbs
Elongation	ASTM D751	MD 20% / CD 20%
Wt Per Square	ASTM D3776	2.4 lbs
Nominal Thickness	ASTM D5261	7 mil
Range of Temperature		-40°F to 240°F
Fire Rating UL Class A	ASTM E108	pass

PHYSICAL INFORMATION			
Roll Size	48" X 250'	Rolls Per Pallet	56 rolls
Material Per Roll	1000 sq. ft.	Wt Per Pallet	1,674 lbs
Squares Per Roll	10 squares	Limited Warranty	15 Years
Weight Per Roll	29 lbs		

COMPLIANCE: CODES
Performance characteristics meet or exceed ASTM D4869 – Type I, II, III and IV
Performance characteristics meet or exceed ASTM D226 – Type I, II
Tested in accordance with ICC-AC-207- UV Exposure – 180 days
U.L. Classified as a Prepared Roofing Accessory
Meets the requirements of ICC-AC- 207



*"Quality Manufactured Components...
Making Construction Systems Perform Better Since 1958"*

No-Smell™ Asphalt



Virtually eliminates objectionable asphalt odors during the installation—so complaints from occupants and the neighbors disappear.

Fiberboard



Your best choice for reliable performance in asphaltic or single ply roofing systems. It's even environmentally-friendly!

Underlayments



Top quality synthetic and asphaltic underlayments at prices you can afford—and with quality that you can rely on every day.

Fasteners



Superior value has made us one of the largest and fastest-growing fastener suppliers in North America—for more than half a century!

Application Tools



Ultra-high purity, 100% cotton mops deliver long-lasting performance and the perfect balance between cost and service life.