



Technical Bulletin

2400 Boston Street, Suite 200, Baltimore, Maryland 21224
Phone: 410-675-2100 or 800-543-3840

Revised: 7/27/10

DAP® ContactStik™ Adhesive Repair Strips

- **Gluing Made Cleaner™**
- **Easy-to-use, no-mess alternative to liquid contact cements and glues**
- **Ideal for small laminate repairs and other household projects**
- **Forms a strong, instant bond to almost all surfaces**
- **Non-toxic**
- **Acid-free**
- **Conforms to ASTM D 4236**
- **Can hold up to 2 lbs.**

Packaging: Contains 5 strips each, 1" x 2" and 1" x 3"
Color: Clear
UPC Number: 7079801215

Company Identification:

Manufactured For: DAP Products Inc., 2400 Boston St., Ste. 200, Baltimore, Maryland 21224
Usage Information: Call 1-888-DAP-TIPS or visit dap.com & click on "Ask the Expert"
Order Information: 800-327-3339
Fax Number: 410-534-2650

Product Description:

DAP® ContactStik™ Adhesive Repair Strips are an easy, no mess alternative to liquid contact cements and glues. These easy-to-use adhesive repair strips are available in two sizes and can even be cut to fit any size project. They are ideal for small repairs to laminate countertops, tables and surfaces. They bond to a variety of surfaces which makes them a perfect solution to many small household repairs where liquid contact cements, glues or tapes would normally be used. Just peel and press the strips to almost any surface for a strong, instant bond. The strips are non-toxic, acid free and conform to ASTM D4236.

Suggested Uses:

Ideal for:

- Repairing laminate, wallpaper and ceramic
- Holding down area rugs
- Shoe repair
- Hobbies and crafts
- Indoor/outdoor projects

Bonds To:

- Plastic Laminates
- Veneers
- Metals
- Wood
- Tile
- Linoleum
- Leather
- Fabric
- Foam
- Rubber

For Best Results:

- *Apply in temperatures above 50°F.*
- *Ensure surface is clean and dry.*
- *If necessary, cut strip(s) to the appropriate size using clean, sharp scissors.*
- ***This is an industrial-strength adhesive and may cause damage if removed.***
- ***Do not use for load-bearing, vertical applications.***
- ***If using for an underwater application, surfaces must be bonded when dry before being exposed to water.***
- *Greater coverage of bonding-surface area increases adhesive performance.*

Surface Preparation & Application:

1. Remove one side of the oversized liner and firmly press DAP® ContactStik™ onto surface.
2. Rub finger over remaining liner to ensure adhesion.
3. Peel off remaining liner and press materials firmly together.
4. **For Laminate Repair:** Following instructions above, apply uniform bond pressure with a J-roller or similar device.

Product Removal:

- Insert knife between bonded surfaces and carefully cut DAP® ContactStik™.
- Excess DAP® ContactStik™ can be cleanly removed with paint thinner or nail polish remover.

Physical & Chemical Characteristics:

Physical State:	Solid
Color:	Clear
Odor:	Minimal
Consistency:	Tape
Shelf Life:	2 years when stored at 75°F and 50% relative humidity or less when stored in factory provided packaging
MSDS No.:	00079502001

Clean Up:

Excess product can be cleanly removed from surfaces with paint thinner or nail polish remover.

Safety:

See product label and Material Safety Data Sheet (MSDS) for safety information. You can request an MSDS by visiting our website at dap.com or calling 1-888-DAP-TIPS.

Satisfaction Guaranteed:

If not satisfied with product's performance, when used as directed, return used container and sales receipt to DAP Products Inc., Tech. Customer Service, 2400 Boston St., Suite 200, Baltimore, MD 21224 for sales price refund. DAP will not be liable for incidental or consequential damages.