



# Technical Bulletin

2400 Boston Street, Suite 200, Baltimore, Maryland 21224  
Phone: 410-675-2100 or 800-543-3840

Revised: 7/28/05

## DAP® Bondex® Flexible Floor Patch and Leveler

- For Plywood Subfloors and Concrete
- Crack Resistant Formula
- Can Be Feather Edged

### Company Identification:

Manufacturer: DAP Inc.  
Marketed by: DAP Inc., 2400 Boston Street, Baltimore, Maryland 21224  
Usage Information: DAP HELPLINE: 888-DAP-TIPS, 9:00 am to 7:00 pm EST.  
Order Information: 800-327-3339  
Fax Number: 410-534-2650  
Also, visit the DAP website at [www.dap.com](http://www.dap.com).

### Product Description:

DAP® Bondex® Flexible Floor Patch and Leveler is a ready-to-use latex based product used to fill cracks, fasteners or knotholes, and level low areas in plywood subfloors or concrete surfaces. The Floor Patch and Leveler will remain flexible allowing the plywood subfloor to flex without cracking the filled-in areas.

### Suggested Uses

*It is ideal for filling and leveling surfaces prior to the installation of carpeting, vinyl floor tile or sheeting as well as ceramic or mosaic floor tile.*

### Surface Preparation & Application

- Surfaces to be filled or leveled must be clean, dry and free of all loose material, oil and grease.
- All old adhesive, wax or coating must be removed prior to application.
- Using a broad knife or a smooth face trowel, apply the Floor Patch and Leveler directly to the area to be filled.
- Apply up to ¼ inch and let dry approximately 6 hours to a hard consistency. For thickness greater than ¼ inch, apply in multiple coats allowing each coat to dry completely between application.
- Feather edge all applications to ensure a smooth surface.
- Maximum application depth is ¾ of an inch.
- Test for dryness by pressing a coin to patch. No indentation indicated sufficient dry time for adhesive application.

### Physical & Chemical Characteristics:

Coverage:	One quart fills 3 to 4 square feet ¼ inch thick.
Consistency:	Paste
Drying time:	6 hours
Storage:	Protect from freezing. Close lid tightly after each use.
Shelf Life:	1 year
Temperatures:	Apply above 40°F

Packaging:

<u>UPC</u>	<u>Size</u>	<u>Container</u>
59184	Quart	Tub
59190	Gallon	Tub
80250	946ml	Tub
80251	3.8 L	Tub

MSDS Number: 000 79729 001

**Clean Up:**

All tools may be cleaned with soap and water.

**Safety:**

See product label and Material Safety Data Sheet (MSDS) for safety information. You can request an MSDS by visiting our website at [www.dap.com](http://www.dap.com) or by calling 888-DAP-TIPS.

**Warranty Information:**

If you are not satisfied with this product's performance when used as directed, return used container and sales receipt to DAP Inc., Technical Customer Service, 2400 Boston Street, Suite 200, Baltimore, MD 21224 for product replacement or sales price refund. DAP will not be liable for incidental or consequential damages.