



Technical Bulletin

2400 Boston Street, Suite 200, Baltimore, Maryland 21224
Phone: 410-675-2100 or 800-543-3840

Revised: 1/30/03

DAP® Plaster Wall Patch

- Professional quality
- Long working time
- Easy to sand

Packaging: 4 lb. tub, 4.4 lb. box, 25 lb. bag.
Color: White
UPC Numbers: 10302, 52005, 10304

Company Identification:

Manufacturer: DAP Inc.
Marketed by: DAP Inc., 2400 Boston Street, Baltimore, Maryland 21224
Usage Information: DAP HELPLINE: 888-DAP-TIPS, 9:00 am to 7:00 pm EST.
Order Information: 800-327-3339
Fax Number: 410-534-2650
Also, visit the DAP website at www.dap.com.

Product Description:

DAP® Plaster Wall Patch may be used to repair large holes in interior plaster walls and ceilings. Its easy-to-mix formula applies smoothly and dries to a durable, uniform finish. DAP® Plaster Wall Patch is easy to sand and can be painted with any oil or latex-base paint. It passes ASTM E-119-88 Fire Test Specifications when used with Marshalltown's NuPride Fire Rated Patch-It Kit!

Suggested Uses:

For patching large holes and cracks in plaster walls and ceilings.

SURFACE PREPARATION & APPLICATION

- Surface must be clean and free of wallpaper, loose paint, plaster, wax, dust, and dirt.
- Under cut edges of existing plaster so patch anchors around opening. Dampen area to be patched with water.
- Add DAP® Plaster Wall Patch to clear water in clean container mixing 3 parts powder to 1 part cold water. Stir to a smooth consistency. (More water may be needed for large batches depending on consistency desired. Add small amounts at a time until desired consistency is achieved.) Do not mix more material than can be used in 2 hours. Discard any material that has begun to harden.
- Apply DAP® Plaster Wall Patch with a clean putty knife or trowel filling around edges. Remove excess material so that plaster is level and flush with the surface. For large, deep openings, apply a base layer and allow it to dry. When hard, wet surface and apply the finish layer of patch.
- When thoroughly dry, sand smooth. Be sure plaster is completely dry and hard before painting (2 hours).

FOR BEST RESULTS

Use cold water when mixing. Sand as needed before decorating. Wet sanding is recommended to avoid creating dust. Always use a good quality paint for a professional finish. For a faster setting plaster that’s ideal for craft work, use DAP® Plaster of Paris. To fill and conceal small cracks, nail holes, and blemishes, use DAP® FAST ‘N FINAL® Lightweight Spackling.

Physical & Chemical Characteristics:

Working Time 1.5 – 2 Hours depending on humidity.
Setting Time: 2 Hours
Final Cure: 3 Days
Shelf Life: 1 yr. When stored in original package & tightly sealed.
Packaging:

<u>UPC</u>	<u>Size</u>	<u>Color</u>	<u>Container</u>
52005	4lb.	White	Tub
10302	4.4 lb.	White	Box
10304	25 lb.	White	Bag

Mixing Ratios & Coverage:

<u>Wall Patch</u>	<u>Water</u>	<u>Coverage (calculated at 1/4” thickness).</u>
4 lb.	1 1/4 pt.	2 sq. ft.
4.4lb	3 c. or 1 1/2 pt.	2.2 sq. ft
25 lb.	3 1/2 to 4 qt.s.	13 sq. ft.

MSDS No.: 71006

Clean Up:

Clean with water immediately after use.

Safety:

See product label or Material Safety Data Sheet for safety information. You can request an MSDS sheet by calling 888-DAP-TIPS or by visiting our website at www.dap.com.

Warranty Information:

If not satisfied with product performance when used as directed, return used container and sales receipt to DAP Inc., Technical Customer Service, 2400 Boston St., Baltimore, MD, 21224, for product replacement or, sales price refund. DAP will not be liable for incidental or consequential damage.

