

## ESTIMATED RESIN REQUIREMENTS PER LINEAL FOOT OF CRACK

### Crack Width (in.)

Depth	1/32					1/16			1/8		3/16		1/4	
	.005	.010	.020	.0312	.040	.055	.0625	.070	.125	.145	.177	.187	.205	.250
1"	.06	.12	.24	.37	.48	.66	.75	.84	1.50	1.74	2.12	2.24	2.46	3.00
2"	.12	.24	.48	.75	.96	1.32	1.50	1.68	3.00	3.48	4.25	4.49	4.92	6.00
4"	.24	.48	.96	1.50	1.92	2.64	3.00	3.36	6.00	6.96	8.50	8.98	9.84	12.00
6"	.36	.72	1.44	2.25	2.88	3.96	4.50	5.04	9.00	10.44	12.74	13.46	14.76	18.00
8"	.48	.96	1.92	3.00	3.84	5.28	6.00	6.72	12.00	13.92	16.99	17.95	19.68	24.00
10"	.60	1.20	2.40	3.74	4.80	6.60	7.50	8.40	15.00	17.40	21.24	22.44	24.60	30.00
12"	.72	1.44	2.88	4.49	5.76	7.92	9.00	10.08	18.00	20.88	25.49	26.93	29.52	36.00
16"	.96	1.92	3.84	5.99	7.68	10.56	12.00	13.44	24.00	27.84	33.98	35.90	39.36	48.00
18"	1.08	2.16	4.32	6.74	8.64	11.88	13.50	15.12	27.00	31.32	38.23	40.39	44.28	54.00
24"	1.44	2.88	5.76	8.99	11.52	15.84	18.00	20.16	36.00	41.76	50.98	53.86	59.04	71.00
36"	2.16	4.32	8.64	13.48	17.28	23.76	27.00	30.24	54.00	62.64	76.46	80.78	88.56	108.00


### VOLUME OF RESIN REQUIRED (cu. in.)

## ESTIMATED LINEAL FEET PER GALLON

### Crack Width (in.)

Depth	1/32					1/16			1/8		3/16		1/4	
	.005	.010	.020	.0312	.040	.055	.0625	.070	.125	.145	.177	.187	.205	.250
6"	642	321	160	103	80	58	51	46	26	22	18	17	16	13
8"	481	241	120	77	60	44	39	34	19	17	14	13	12	10
10"	385	193	96	62	48	35	31	28	15	13	11	10	9	8
12"	321	160	80	51	40	29	26	23	13	11	9	8.5	8	6
16"	241	120	60	39	30	22	19	17	10	8	7	6	5.8	5
18"	214	107	54	34	27	19	17	15	9	7	6	5.7	5	4
24"	160	80	40	26	20	15	13	12	6	5.5	5	4	3.9	3
36"	107	54	27	17	13	10	9	8	4	3.5	3	2.8	2.5	2

### Lineal feet per gallon


**de neef**® Construction Chemicals, Inc

5610 Brystone drive Houston, Texas 77041

Phone 713-896-0123 Fax 713-849-3340

[www.deneef.com](http://www.deneef.com)