



Material Safety Data Sheet

The Dow Chemical Company

Product Name: TILE BOND(TM) HFC Roof Tile Adhesive Complete **Issue Date:** 05/22/2008
Print Date: 18 Aug 2011

The Dow Chemical Company encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

1. Product and Company Identification

Product Name
TILE BOND(TM) HFC Roof Tile Adhesive Complete

COMPANY IDENTIFICATION

The Dow Chemical Company
2030 Willard H. Dow Center
Midland, MI 48674
USA

Customer Information Number: 800-258-2436

EMERGENCY TELEPHONE NUMBER

24-Hour Emergency Contact: 989-636-4400
Local Emergency Contact: 989-636-4400

2. Hazards Identification

Emergency Overview

Color: Black

Physical State: Foam

Odor: Very slight

Hazards of product:

WARNING! May cause allergic skin reaction. May cause allergic respiratory reaction. May cause eye irritation. May cause skin irritation. Vapor reduces oxygen available for breathing. May cause anesthetic effects. May cause respiratory tract irritation. May cause lung injury. Aspiration hazard. Can enter lungs and cause damage. Keep upwind of spill. Stay out of low areas. Elevated temperatures can cause hazardous polymerization. Toxic fumes may be released in fire situations. Contents under pressure. Containers are under high pressure. Avoid temperatures above 50°C (122°F)

OSHA Hazard Communication Standard

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Potential Health Effects

Eye Contact: May cause eye irritation. May cause slight temporary corneal injury.

Skin Contact: Prolonged contact may cause moderate skin irritation with local redness. Material may stick to skin causing irritation upon removal. May stain skin.

Skin Absorption: Prolonged skin contact is unlikely to result in absorption of harmful amounts.

Skin Sensitization: Skin contact may cause an allergic skin reaction. Animal studies have shown that skin contact with isocyanates may play a role in respiratory sensitization.

Inhalation: In confined or poorly ventilated areas, vapor can easily accumulate and can cause unconsciousness and death due to displacement of oxygen. Excessive exposure may cause irritation to upper respiratory tract (nose and throat) and lungs. May cause pulmonary edema (fluid in the lungs.) Effects may be delayed. Symptoms of excessive exposure may be anesthetic or narcotic effects; dizziness and drowsiness may be observed. Excessive exposure may increase sensitivity to epinephrine and increase myocardial irritability (irregular heartbeats). Decreased lung function has been associated with overexposure to isocyanates.

Respiratory Sensitization: May cause allergic respiratory response. MDI concentrations below the exposure guidelines may cause allergic respiratory reactions in individuals already sensitized. Asthma-like symptoms may include coughing, difficult breathing and a feeling of tightness in the chest. Occasionally, breathing difficulties may be life threatening.

Ingestion: Low toxicity if swallowed. Small amounts swallowed incidentally as a result of normal handling operations are not likely to cause injury; however, swallowing larger amounts may cause injury. Aspiration into the lungs may occur during ingestion or vomiting, causing lung damage or even death due to chemical pneumonia. Observations in animals include: Gastrointestinal irritation.

Effects of Repeated Exposure: Tissue injury in the upper respiratory tract and lungs has been observed in laboratory animals after repeated excessive exposures to MDI/polymeric MDI aerosols. Contains component(s) which have been reported to cause effects on the following organs in animals: Kidney. Liver.

Cancer Information: Lung tumors have been observed in laboratory animals exposed to respirable aerosol droplets of MDI/Polymeric MDI (6 mg/m³) for their lifetime. Tumors occurred concurrently with respiratory irritation and lung injury. Current exposure guidelines are expected to protect against these effects reported for MDI.

Birth Defects/Developmental Effects: In laboratory animals, MDI/polymeric MDI did not cause birth defects; other fetal effects occurred only at high doses which were toxic to the mother. The data presented are for the following material: 1,1,1,2-Tetrafluoroethane. Has been toxic to the fetus in laboratory animals at doses toxic to the mother. Did not cause birth defects in laboratory animals.

3. Composition Information

Component	CAS #	Amount
Isocyanic acid, polymethylenepolyphenylene ester, polymer with .alpha.,.alpha.,.alpha."-1,2,3-propanetriyltris[.omega.-hydroxypoly	57029-46-6	>= 30.0 - <= 60.0 %
Polymethylenepolyphenyl polyisocyanate, polypropyleneglycol copolymer	53862-89-8	>= 5.0 - <= 10.0 %
Diphenylmethane Diisocyanate, isomers and homologues	9016-87-9	>= 15.0 - <= 40.0 %
4,4' -Methylenediphenyl diisocyanate	101-68-8	>= 10.0 - <= 30.0 %
1,1,1,2-Tetrafluoroethane	811-97-2	>= 10.0 - <= 30.0 %
Paraffin waxes and Hydrocarbon waxes, chlorinated	63449-39-8	>= 5.0 - <= 10.0 %

Note: CAS 101-68-8 is an MDI isomer that is part of CAS 9016-87-9.

4. First-aid measures

Eye Contact: Immediately flush eyes with water; remove contact lenses, if present, after the first 5 minutes, then continue flushing eyes for at least 15 minutes. Obtain medical attention without delay, preferably from an ophthalmologist.

Skin Contact: Remove material from skin immediately by washing with soap and plenty of water. Remove contaminated clothing and shoes while washing. Seek medical attention if irritation persists. Wash clothing before reuse. An MDI skin decontamination study demonstrated that cleaning very

soon after exposure is important, and that a polyglycol-based skin cleanser or corn oil may be more effective than soap and water. Discard items which cannot be decontaminated, including leather articles such as shoes, belts and watchbands.

Inhalation: Move person to fresh air. If not breathing, give artificial respiration; if by mouth to mouth use rescuer protection (pocket mask, etc). If breathing is difficult, oxygen should be administered by qualified personnel. Call a physician or transport to a medical facility.

Ingestion: Do not induce vomiting. Call a physician and/or transport to emergency facility immediately.

Notes to Physician: Maintain adequate ventilation and oxygenation of the patient. May cause asthma-like (reactive airways) symptoms. Bronchodilators, expectorants, antitussives and corticosteroids may be of help. May cause respiratory sensitization or asthma-like symptoms. Bronchodilators, expectorants and antitussives may be of help. Treat bronchospasm with inhaled beta2 agonist and oral or parenteral corticosteroids. Respiratory symptoms, including pulmonary edema, may be delayed. Persons receiving significant exposure should be observed 24-48 hours for signs of respiratory distress. If you are sensitized to diisocyanates, consult your physician regarding working with other respiratory irritants or sensitizers. If lavage is performed, suggest endotracheal and/or esophageal control. Danger from lung aspiration must be weighed against toxicity when considering emptying the stomach. The decision of whether to induce vomiting or not should be made by a physician. Exposure may increase "myocardial irritability". Do not administer sympathomimetic drugs such as epinephrine unless absolutely necessary. No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

Medical Conditions Aggravated by Exposure: Excessive exposure may aggravate preexisting asthma and other respiratory disorders (e.g. emphysema, bronchitis, reactive airways dysfunction syndrome).

5. Fire Fighting Measures

Extinguishing Media: Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Foam. Do not use direct water stream. May spread fire. Alcohol resistant foams (ATC type) are preferred. General purpose synthetic foams (including AFFF) or protein foams may function, but will be less effective.

Fire Fighting Procedures: Keep people away. Isolate fire and deny unnecessary entry. Stay upwind. Keep out of low areas where gases (fumes) can accumulate. Do not use direct water stream. May spread fire. Fight fire from protected location or safe distance. Consider the use of unmanned hose holders or monitor nozzles. Immediately withdraw all personnel from the area in case of rising sound from venting safety device or discoloration of the container. Move container from fire area if this is possible without hazard. Use water spray to cool fire-exposed containers and fire-affected zone until fire is out.

Special Protective Equipment for Firefighters: Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves). Avoid contact with this material during fire fighting operations. If contact is likely, change to full chemical resistant fire fighting clothing with self-contained breathing apparatus. If this is not available, wear full chemical resistant clothing with self-contained breathing apparatus and fight fire from a remote location. For protective equipment in post-fire or non-fire clean-up situations, refer to the relevant sections.

Unusual Fire and Explosion Hazards: Some components of this product will burn in a fire situation. Container may vent and/or rupture due to fire. Vaporizes quickly at room temperature. Dense smoke is produced when product burns.

Hazardous Combustion Products: During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Nitrogen oxides. Isocyanates. Hydrogen fluoride. Hydrogen halides. Carbon dioxide.

6. Accidental Release Measures

Steps to be Taken if Material is Released or Spilled: Contain spilled material if possible. Absorb with materials such as: Sawdust. Dirt. Vermiculite. Sand. Clay. Cob grit. Milsorb®. Do NOT use absorbent materials such as: Cement powder (Note: may generate heat). Collect in suitable and

properly labeled open containers. Do not place in sealed containers. Suitable containers include: Metal drums. Plastic drums. Polylined fiber pacs. Wash the spill site with large quantities of water. Attempt to neutralize by adding suitable decontaminant solution: Formulation 1: sodium carbonate 5 - 10%; liquid detergent 0.2 - 2%; water to make up to 100%, OR Formulation 2: concentrated ammonia solution 3 - 8%; liquid detergent 0.2 - 2%; water to make up to 100%. If ammonia is used, use good ventilation to prevent vapor exposure. Contact Dow for clean-up assistance. See Section 13, Disposal Considerations, for additional information.

Personal Precautions: Isolate area. Only trained and properly protected personnel must be involved in clean-up operations. Keep personnel out of low areas. Keep personnel out of confined or poorly ventilated areas. Keep upwind of spill. Ventilate area of leak or spill. Keep unnecessary and unprotected personnel from entering the area. If available, use foam to smother or suppress. Confined space entry procedures must be followed before entering the area. Refer to Section 7, Handling, for additional precautionary measures. Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection. See Section 10 for more specific information.

Environmental Precautions: Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

7. Handling and Storage

Handling

General Handling: Avoid contact with eyes, skin, and clothing. Avoid prolonged or repeated contact with skin. Do not swallow. Avoid breathing vapor. Use with adequate ventilation. Wash thoroughly after handling. Keep container tightly closed. Contents under pressure. Do not puncture or incinerate container. Do not enter confined spaces unless adequately ventilated. See Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION.

Other Precautions: Spills of these organic materials on hot fibrous insulations may lead to lowering of the autoignition temperatures possibly resulting in spontaneous combustion.

Storage

Store in a dry place. Protect from atmospheric moisture. Maintain a nitrogen atmosphere. Do not store product contaminated with water to prevent potential hazardous reaction. Avoid temperatures above 50°C (122°F) See Section 10 for more specific information. Additional storage and handling information on this product may be obtained by calling your Dow sales or customer service contact.

Storage Period: 12 Months

Storage temperature: 20 - 30 °C

8. Exposure Controls / Personal Protection

Exposure Limits

Component	List	Type	Value
4,4' -Methylenediphenyl diisocyanate	ACGIH	TWA	0.005 ppm
	OSHA Table Z-1	Ceiling	0.2 mg/m3 0.02 ppm
1,1,1,2-Tetrafluoroethane	WEEL	TWA	4,240 mg/m3 1,000 ppm

Personal Protection

Eye/Face Protection: Use safety glasses. Eye wash fountain should be located in immediate work area.

Skin Protection: Use protective clothing chemically resistant to this material. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task. Remove contaminated clothing immediately, wash skin area with soap and water, and launder clothing before

reuse or dispose of properly. Items which cannot be decontaminated, such as shoes, belts and watchbands, should be removed and disposed of properly.

Hand protection: Use gloves chemically resistant to this material. Examples of preferred glove barrier materials include: Chlorinated polyethylene. Neoprene. Polyethylene. Ethyl vinyl alcohol laminate ("EVAL"). Polyvinyl chloride ("PVC" or "vinyl"). Viton. Examples of acceptable glove barrier materials include: Butyl rubber. Natural rubber ("latex"). Nitrile/butadiene rubber ("nitrile" or "NBR"). **NOTICE:** The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Respiratory Protection: Atmospheric levels should be maintained below the exposure guideline. When atmospheric levels may exceed the exposure guideline, use an approved air-purifying respirator equipped with an organic vapor sorbent and a particle filter. For situations where the atmospheric levels may exceed the level for which an air-purifying respirator is effective, use a positive-pressure air-supplying respirator (air line or self-contained breathing apparatus). For emergency response or for situations where the atmospheric level is unknown, use an approved positive-pressure self-contained breathing apparatus or positive-pressure air line with auxiliary self-contained air supply. The following should be effective types of air-purifying respirators: Organic vapor cartridge with a particulate pre-filter.

Ingestion: Avoid ingestion of even very small amounts; do not consume or store food or tobacco in the work area; wash hands and face before smoking or eating.

Engineering Controls

Ventilation: Use only with adequate ventilation. Local exhaust ventilation may be necessary for some operations. Provide general and/or local exhaust ventilation to control airborne levels below the exposure guidelines. Exhaust systems should be designed to move the air away from the source of vapor/aerosol generation and people working at this point. The odor and irritancy of this material are inadequate to warn of excessive exposure.

9. Physical and Chemical Properties

Physical State	Foam
Color	Black
Odor	Very slight
Flash Point - Closed Cup	Not applicable
Flammable Limits In Air	Lower: No test data available Upper: No test data available
Autoignition Temperature	No test data available
Vapor Pressure	2,100 kPa @ 55 °C <i>Calculated</i>
Boiling Point (760 mmHg)	No test data available.
Vapor Density (air = 1)	No test data available
Specific Gravity (H2O = 1)	1.169 <i>Calculated</i>
Freezing Point	No test data available
Melting Point	No test data available
Solubility in Water (by weight)	No test data available
pH	Not applicable
Kinematic Viscosity	Not applicable

10. Stability and Reactivity

Stability/Instability

Stable under recommended storage conditions. See Storage, Section 7. Unstable at elevated temperatures.

Conditions to Avoid: Avoid temperatures above 50°C (122°F) Exposure to elevated temperatures can cause product to decompose.

Incompatible Materials: Avoid contact with: Acids. Alcohols. Amines. Ammonia. Bases. Metal compounds. Strong oxidizers. Products based on diisocyanates like TDI and MDI react with many materials to release heat. The reaction rate increases with temperature as well as with increased contact; these reactions can become violent. Contact is increased by stirring or if the other material acts as a solvent. Products based on diisocyanates such as TDI and MDI are not soluble in water and will sink to the bottom, but react slowly at the interface. The reaction forms carbon dioxide gas and a layer of solid polyurea. Reaction with water will generate carbon dioxide and heat.

Hazardous Polymerization

Can occur. Elevated temperatures can cause hazardous polymerization.

Thermal Decomposition

Decomposition products depend upon temperature, air supply and the presence of other materials. Toxic gases are released during decomposition.

11. Toxicological Information

Acute Toxicity

Ingestion

Single dose oral LD50 has not been determined.

Skin Absorption

The dermal LD50 has not been determined.

Sensitization

Skin

Skin contact may cause an allergic skin reaction. Animal studies have shown that skin contact with isocyanates may play a role in respiratory sensitization.

Respiratory

May cause allergic respiratory response. MDI concentrations below the exposure guidelines may cause allergic respiratory reactions in individuals already sensitized. Asthma-like symptoms may include coughing, difficult breathing and a feeling of tightness in the chest. Occasionally, breathing difficulties may be life threatening.

Repeated Dose Toxicity

Tissue injury in the upper respiratory tract and lungs has been observed in laboratory animals after repeated excessive exposures to MDI/polymeric MDI aerosols. Contains component(s) which have been reported to cause effects on the following organs in animals: Kidney. Liver.

Chronic Toxicity and Carcinogenicity

Lung tumors have been observed in laboratory animals exposed to respirable aerosol droplets of MDI/Polymeric MDI (6 mg/m³) for their lifetime. Tumors occurred concurrently with respiratory irritation and lung injury. Current exposure guidelines are expected to protect against these effects reported for MDI.

Developmental Toxicity

In laboratory animals, MDI/polymeric MDI did not cause birth defects; other fetal effects occurred only at high doses which were toxic to the mother. The data presented are for the following material: 1,1,1,2-Tetrafluoroethane. Has been toxic to the fetus in laboratory animals at doses toxic to the mother. Did not cause birth defects in laboratory animals.

Genetic Toxicology

In vitro genetic toxicity studies were negative for component(s) tested. Genetic toxicity data on MDI are inconclusive. MDI was weakly positive in some in vitro studies; other in vitro studies were negative. Animal mutagenicity studies were predominantly negative. For the component(s) tested: 1,1,1,2-tetrafluoroethane Animal genetic toxicity studies were negative.

12. Ecological Information

ENVIRONMENTAL FATE

Data for Component: **Isocyanic acid, polymethylenepolyphenylene ester, polymer with .alpha.,.alpha.'.alpha.'-1,2,3-propanetriyltris[.omega.-hydroxypoly**

Movement & Partitioning

In the aquatic and terrestrial environment, movement is expected to be limited by its reaction with water forming predominantly insoluble polyureas.

Persistence and Degradability

In the aquatic and terrestrial environment, material reacts with water forming predominantly insoluble polyureas which appear to be stable. In the atmospheric environment, material is expected to have a short tropospheric half-life, based on calculations and by analogy with related diisocyanates.

Data for Component: **Polymethylenepolyphenyl polyisocyanate, polypropylene glycol copolymer**

Movement & Partitioning

In the aquatic and terrestrial environment, movement is expected to be limited by its reaction with water forming predominantly insoluble polyureas.

Persistence and Degradability

In the aquatic and terrestrial environment, material reacts with water forming predominantly insoluble polyureas which appear to be stable. In the atmospheric environment, material is expected to have a short tropospheric half-life, based on calculations and by analogy with related diisocyanates.

Data for Component: **Diphenylmethane Diisocyanate, isomers and homologues**

Movement & Partitioning

In the aquatic and terrestrial environment, movement is expected to be limited by its reaction with water forming predominantly insoluble polyureas.

Persistence and Degradability

In the aquatic and terrestrial environment, material reacts with water forming predominantly insoluble polyureas which appear to be stable. In the atmospheric environment, material is expected to have a short tropospheric half-life, based on calculations and by analogy with related diisocyanates.

Data for Component: **4,4' -Methylenediphenyl diisocyanate**

Movement & Partitioning

In the aquatic and terrestrial environment, movement is expected to be limited by its reaction with water forming predominantly insoluble polyureas.

Persistence and Degradability

In the aquatic and terrestrial environment, material reacts with water forming predominantly insoluble polyureas which appear to be stable. In the atmospheric environment, material is expected to have a short tropospheric half-life, based on calculations and by analogy with related diisocyanates.

Data for Component: **1,1,1,2-Tetrafluoroethane**

Movement & Partitioning

Bioconcentration potential is low (BCF less than 100 or log Pow less than 3). Potential for mobility in soil is high (Koc between 50 and 150).

Henry's Law Constant (H): 5.00E-2 atm*m3/mole; 25 °C Measured

Partition coefficient, n-octanol/water (log Pow): 1.68 Estimated

Partition coefficient, soil organic carbon/water (Koc): 97 Estimated

Persistence and Degradability

1,1,1,2-Tetrafluoroethane (HFC-134a) has a stratospheric ozone depletion potential (ODP) of zero, relative to CFC 12 (ODP=1). Material is expected to biodegrade only very slowly (in the environment). Fails to pass OECD/EEC tests for ready biodegradability.

Indirect Photodegradation with OH Radicals

Rate Constant	Atmospheric Half-life	Method
6.20E-15 cm ³ /s	1,700 d	Estimated
OECD Biodegradation Tests:		
Biodegradation	Exposure Time	Method
4 %	28 d	OECD 301D Test

Theoretical Oxygen Demand: 0.47 mg/mg

Data for Component: **Paraffin waxes and Hydrocarbon waxes, chlorinated**

Movement & Partitioning

Bioconcentration potential is low (BCF less than 100 or log Pow greater than 7). Expected to be relatively immobile in soil (Koc > 5000). Given its very low Henry's constant, volatilization from natural bodies of water or moist soil is not expected to be an important fate process.

Henry's Law Constant (H): < 1.0E-07 atm*m³/mole; 25 °C Estimated

Partition coefficient, n-octanol/water (log Pow): 7.4 Estimated

Partition coefficient, soil organic carbon/water (Koc): > 5,000 Estimated

Persistence and Degradability

Expected to degrade only slowly in the environment.

Theoretical Oxygen Demand: 2.89 mg/mg

ECOTOXICITY

Data for Component: **Isocyanic acid, polymethylenepolyphenylene ester, polymer with .alpha.,.alpha.'.alpha.'"-1,2,3-propanetriyltris[.omega.-hydroxypoly**

The measured ecotoxicity is that of the hydrolyzed product, generally under conditions maximizing production of soluble species. Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).

Toxicity to Soil Dwelling Organisms

LC50, Earthworm Eisenia foetida, adult, 14 d: > 1,000 mg/kg

Data for Component: **Polymethylenepolyphenyl polyisocyanate, polypropyleneglycol copolymer**

The measured ecotoxicity is that of the hydrolyzed product, generally under conditions maximizing production of soluble species. Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).

Toxicity to Soil Dwelling Organisms

LC50, Earthworm Eisenia foetida, adult, 14 d: > 1,000 mg/kg

Data for Component: **Diphenylmethane Diisocyanate, isomers and homologues**

The measured ecotoxicity is that of the hydrolyzed product, generally under conditions maximizing production of soluble species. Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).

Toxicity to Soil Dwelling Organisms

LC50, Earthworm Eisenia foetida, adult, 14 d: > 1,000 mg/kg

Data for Component: **4,4' -Methylenediphenyl diisocyanate**

The measured ecotoxicity is that of the hydrolyzed product, generally under conditions maximizing production of soluble species. Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).

Toxicity to Soil Dwelling Organisms

LC50, Earthworm Eisenia foetida, adult, 14 d: > 1,000 mg/kg

Data for Component: **1,1,1,2-Tetrafluoroethane**

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).

Fish Acute & Prolonged Toxicity

LC50, rainbow trout (Oncorhynchus mykiss), static, 96 h: 450 mg/l

Aquatic Invertebrate Acute Toxicity

EC50, water flea Daphnia magna, 48 h, immobilization: 980 mg/l
Data for Component: Paraffin waxes and Hydrocarbon waxes, chlorinated
Material is very highly toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 <0.1 mg/L in most sensitive species).

Fish Acute & Prolonged Toxicity

LC50, rainbow trout (Oncorhynchus mykiss), static, 96 h: > 100 mg/l

Aquatic Invertebrate Acute Toxicity

EC50, water flea Daphnia magna, immobilization: 0.037 mg/l

13. Disposal Considerations

DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Recycler. Reclaimer. Incinerator or other thermal destruction device. For additional information, refer to: Handling & Storage Information, MSDS Section 7 Stability & Reactivity Information, MSDS Section 10 Regulatory Information, MSDS Section 15

14. Transport Information

DOT Non-Bulk

Proper Shipping Name: COMPRESSED GAS, N.O.S.

Technical Name: Fluorinated Hydrocarbons, Nitrogen

Hazard Class: 2.2 **ID Number:** UN1956

DOT Bulk

Proper Shipping Name: COMPRESSED GAS, N.O.S.

Technical Name: Fluorinated Hydrocarbons, Nitrogen

Hazard Class: 2.2 **ID Number:** UN1956

IMDG

Proper Shipping Name: COMPRESSED GAS, N.O.S.

Technical Name: Fluorinated Hydrocarbons, Nitrogen

ID Number: 2.2

EMS Number: F-C,S-V

Marine pollutant.: No

ICAO/IATA

Proper Shipping Name: COMPRESSED GAS, N.O.S.

Technical Name: Fluorinated Hydrocarbons, Nitrogen

Hazard Class: 2.2 **ID Number:** UN1956**Cargo Packing Instruction:** 200

Passenger Packing Instruction: 200

Additional Information

Reportable quantity: 8,333 lb – MDI

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the

transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

15. Regulatory Information

OSHA Hazard Communication Standard

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

Immediate (Acute) Health Hazard	Yes
Delayed (Chronic) Health Hazard	Yes
Fire Hazard	No
Reactive Hazard	No
Sudden Release of Pressure Hazard	Yes

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

This product contains the following substances which are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and which are listed in 40 CFR 372.

Component	CAS #	Amount
4,4' -Methylenediphenyl diisocyanate	101-68-8	>= 10.0 - <= 30.0 %
Paraffin waxes and Hydrocarbon waxes, chlorinated	63449-39-8	>= 5.0 - <= 10.0 %
Diphenylmethane Diisocyanate, isomers and homologues	9016-87-9	>= 15.0 - <= 40.0 %

Pennsylvania (Worker and Community Right-To-Know Act): Pennsylvania Hazardous Substances List and/or Pennsylvania Environmental Hazardous Substance List:

The following product components are cited in the Pennsylvania Hazardous Substance List and/or the Pennsylvania Environmental Substance List, and are present at levels which require reporting.

Component	CAS #	Amount
4,4' -Methylenediphenyl diisocyanate	101-68-8	>= 10.0 - <= 30.0 %

Pennsylvania (Worker and Community Right-To-Know Act): Pennsylvania Special Hazardous Substances List:

To the best of our knowledge, this product does not contain chemicals at levels which require reporting under this statute.

California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986)

This product contains no listed substances known to the State of California to cause cancer, birth defects or other reproductive harm, at levels which would require a warning under the statute.

US. Toxic Substances Control Act

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements under 40 CFR 720.30

CEPA - Domestic Substances List (DSL)

All substances contained in this product are listed on the Canadian Domestic Substances List (DSL) or are not required to be listed.

16. Other Information

Recommended Uses and Restrictions

A urethane adhesive --

Revision

Identification Number: 1015292 / 0000 / Issue Date 05/22/2008 / Version: 2.0

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

Legend

N/A	Not available
W/W	Weight/Weight
OEL	Occupational Exposure Limit
STEL	Short Term Exposure Limit
TWA	Time Weighted Average
ACGIH	American Conference of Governmental Industrial Hygienists, Inc.
DOW IHG	Dow Industrial Hygiene Guideline
WEEL	Workplace Environmental Exposure Level
HAZ_DES	Hazard Designation
Action Level	A value set by OSHA that is lower than the PEL which will trigger the need for activities such as exposure monitoring and medical surveillance if exceeded.

The Dow Chemical Company urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.