

Firestone Building Products Company

Material Safety Data Sheet

December 11, 2009

Page: 1

SECTION 1: PRODUCT IDENTIFICATION

Product Name: SBS Polyester Series

Chemical Name / Synonym: SBS Cap, SBS Flex Cap, SBS Premium, SBS Torch, SBS Smooth, SBS PolyBase, SBS Flashing, SBS Poly Torch Base, SBS Premium Torch

Chemical Family: Mixture

24-Hour Emergency Phone: (800) 424-9300 CHEMTREC

Manufacturer's Name: Firestone Building Products Company

Manufacturer's Address: 250 West 96th Street, Indianapolis, IN 46260

NFPA Hazard Rating: Health 1, Flammability 1, Reactivity 0

HMS Hazard Rating: Health 1, Flammability 1, Reactivity 0

SECTION 2: CHEMICAL COMPOSITION

Chemical Name:	Common Name:	CAS #:	% (by wt)	Exposure Limits:
Asphalt (Petroleum)	Bitumen	8052-42-4	60-70	TLV 0.5 mg/m ³ (Inhalable)
Calcium Carbonate	Limestone	1317-65-3	15-25	PEL 15 mg/m ³ (Total) PEL 5 mg/m ³ (Respirable)
Silica, Crystalline, Quartz	Rose Quartz, Sand	14808-60-7	5-10	PEL (Respirable) 10 mg/m ³ (% SiO ₂ +2) PEL (Total) 30 mg/m ³ (% SiO ₂ +2) TLV (Respirable) 0.025 mg/m ³

SECTION 3: HAZARD IDENTIFICATION

Primary Route of Exposure: Inhalation

Signs and Symptoms of Exposure: Causes a foreign body reaction (mechanical irritation). Fumes generated by molten asphalt may cause eye, skin and respiratory tract irritation. Molten asphalt will cause thermal burns.

Medical Conditions Aggravated by Exposure: None Known

Chronic Effects: No significant health effects have been reported in surveys of asphalt workers in oil refineries and in the roofing industry. Prolonged and repeated exposure to crystalline silica containing dust can result in injury to the lungs. This condition is known as silicosis. Silicosis is characterized by the shortness of breath, decreased expansion of the chest, dry cough, leading to fatigue, dyspnea, and cyanosis, loss of appetite, pleuritic pain and decreased work capacity.

Carcinogenicity: Animal inhalation studies have not yielded sufficient evidence of asphalt induced lung cancer, and only limited investigation has been done on the chemical properties and the metabolic changes caused by petroleum asphalt fumes. A roofing petroleum asphalt proved non-carcinogenic to the skin of mice and rabbits, although the condensates of coal tar fumes

Firestone Building Products Company

Material Safety Data Sheet

December 11, 2009

Page: 2

proved highly carcinogenic.

This material is coated with sand, which contains crystalline silica. Some researchers have reported evidence that it may be carcinogenic in humans following prolonged and repeated inhalation.

Petroleum asphalt is listed by IARC as a class 3, *unclassifiable as to carcinogenicity in humans*.

Crystalline silica is classified by IARC as group 1, *carcinogenic to humans*, and by NTP as *known to be a human carcinogen*.

SECTION 4: FIRST AID MEASURES

First Aid Procedures:	Hold eyelids open and wash with gentle stream of water until foreign material is removed. Get medical attention if irritation persists. For inhalation of the fume, smoke or dust of this material, remove to fresh air and treat symptomatically. For thermal burns, flush the affected area with cold water and seek medical attention.
-----------------------	---

SECTION 5: FIRE FIGHTING PROCEDURES

Suitable Extinguishing Media:	Alcohol foam, carbon dioxide, or dry chemical.
Hazardous Combustion Products:	Carbon dioxide, carbon monoxide and partially burned carbon.
Recommended Fire Fighting Procedures:	Wear impermeable protective clothing and self-contained breathing apparatus as toxic fumes and vapors may be evolved.
Unusual Fire and Explosion Hazards:	Combustion of this product produces dense black smoke.

SECTION 6: PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to Be Taken in Case Material is Released or Spilled:	None Required.
Precautions to Be Taken in Handling and Storing:	Keep away from heat, sparks and open flames. Care should be taken to minimize the amount of dust generated when applying or handling this product. The amount of dust generated while handling this product is expected to vary depending on the user's application.

SECTION 7: EXPOSURE CONTROLS / PERSONAL PROTECTION

Ventilation:	Use in well ventilated area.
Respiratory Protection:	Use NIOSH- approved dust, mist, and fume respirator if exposure might exceed the PEL or TLV.
Eye Protection:	The use of safety glasses with side shields may be warranted.
Skin Protection:	The use of leather or cotton gloves for direct handling may be warranted.
Other:	None recommended
Work / Hygienic Practices:	Wash exposed skin prior to eating, drinking or smoking and at the end of each shift. Wash contaminated clothing prior to reuse.

Firestone Building Products Company

Material Safety Data Sheet

December 11, 2009

Page: 3

SECTION 8: PHYSICAL AND CHEMICAL PROPERTIES

Appearance and Odor:	Black mat with sand and/ or granule surface. Asphalt odor.		
Flash Point:	Not Applicable	Lower Explosive Limit:	None
Method Used:	Not Applicable	Upper Explosive Limit:	None
Evaporation Rate:	Not Applicable	Boiling Point:	None
pH (undiluted product):	Not Applicable	Melting Point:	Unknown
Solubility in Water:	Insoluble	Specific Gravity:	Unknown
Vapor Density:	Not Applicable	Percent Volatile:	Unknown
Vapor Pressure:	Not Applicable		

SECTION 9: STABILITY AND REACTIVITY

Thermal Stability:	Stable
Hazardous Polymerization:	Will not occur
Conditions to Avoid:	Strong oxidizing agents

SECTION 10: TRANSPORTATION

Regulatory Agency:	Not Regulated
Proper Shipping Name:	Not Applicable
Hazard Classification:	Not Applicable
Identification Number:	Not Applicable
Labels Required:	Not Applicable
Other Requirements:	Not Applicable

SECTION 11: MISCELLANEOUS INFORMATION

Additional Comments:	The calcium carbonate is bound in an asphalt matrix and is not expected to be released. The sand is applied to the asphalt surface in such a manner that nominal release from the surface is anticipated.
Date of Previous MSDS:	March 2, 2009
Changes Since Previous MSDS:	Product added to section 1, chemical name/synonym.
Telephone Number for Additional Information:	(317) 575-7190

DISCLAIMER

The information contained herein is based on data considered accurate which has been obtained from other companies and organizations. However, no warranty or representation is expressed or implied that the information, is accurate, complete or representative. Firestone Building Products Company, a subsidiary of Firestone Diversified Products, LLC, assumes no responsibility for injury to the buyer, the buyer's employees, or any third persons, if reasonable safety procedures are not followed. Additionally, Firestone Building Products Company assumes no responsibility for injury to buyer, the buyer's employees, or any third persons caused by abnormal use of this material, even if reasonable safety procedures are followed.