

MATERIAL SAFETY DATA SHEET



Date Issued : 09/07/2007
 MSDS No : 403500-4
 Date Revised : 05/11/2012
 Revision No : 9

Proflex RV Instant Roof Repair

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Proflex RV Instant Roof Repair

MANUFACTURER

Geocel, LLC
 P.O. Box 398
 Elkhart, IN 46515-0398
Emergency Phone: 574-264-0645

24 HR. EMERGENCY TELEPHONE NUMBERS

ChemTel - 800-255-3924

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

PHYSICAL APPEARANCE: Liquid

IMMEDIATE CONCERNS: May cause significant eye and skin irritation.

POTENTIAL HEALTH EFFECTS

EYES: May cause significant irritation to the eyes.

SKIN: May cause significant irritation to the skin.

INGESTION: Possible nausea and/or vomiting.

INHALATION: May cause significant pulmonary irritation.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

EYES: Visual effects may include eye irritation, blurred vision, diplopia, changes in color perception, restriction of visual fields, and complete blindness.

SKIN: Irritation of the skin.

INGESTION: Possible nausea and/or vomiting.

INHALATION: Possible headache and/or dizziness.

CHRONIC EFFECTS: Repeated or prolonged contact may cause chemical burns to the eyes. Frequent or prolonged overexposure may irritate or cause dermatitis.

ROUTES OF ENTRY: Inhalation, ingestion, absorption through the eyes and skin.

COMMENTS: Use in well-ventilated area.

3. COMPOSITION / INFORMATION ON INGREDIENTS

| Chemical Name | CAS | EINECS |
|-----------------------|------------|-----------|
| Aromatic Hydrocarbons | 64742-95-6 | 265-199-0 |

4. FIRST AID MEASURES

EYES: Flush with large amounts of water, lifting upper and lower lids occasionally. Seek medical attention.

SKIN: Remove contaminated clothing, including shoes, and wash skin with plenty of soap and water. If irritation occurs, seek medical advice. Wash contaminated clothing and shoes before reuse.

INGESTION: Do not induce vomiting. Seek medical attention.

INHALATION: Move individual to fresh air. If breathing is difficult, administer oxygen. Seek medical attention.

5. FIRE FIGHTING MEASURES

FLASHPOINT AND METHOD: (108°F)

EXTINGUISHING MEDIA: Dry chemical, foam, carbon dioxide (CO₂), sand.

EXPLOSION HAZARDS: Vapors are heavier than air and may travel along the ground or be moved by ventilation and be ignited by heat, pilot lights, other flames and ignition sources at locations near or distant from the point of release.

SENSITIVE TO STATIC DISCHARGE: Grounding and/or bonding is recommended.

SENSITIVITY TO IMPACT: Not Applicable

Proflex RV Instant Roof Repair

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Wearing the personal protective equipment designated in Section 8, carefully contain the spill and transfer it to the appropriate container for disposal. Ventilate well while clean up is in process and until fumes dissipate.

LARGE SPILL: Wearing the personal protective equipment designated in Section 8, carefully contain the spill and transfer to the appropriate container for disposal. Do not discharge to lakes, streams, ponds, or sewers. Dispose of in compliance with local, state, and federal regulations. Ventilate well while cleanup is in process and until fumes dissipate.

7. HANDLING AND STORAGE

HANDLING: Ground and bond containers when transferring material.

STORAGE: Keep away from sources of ignition.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS: Use in a well ventilated area.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Wear safety glasses with side shields or goggles when handling this material.

SKIN: Chemical resistant protective gloves are recommended.

RESPIRATORY: Not required with adequate ventilation.

PROTECTIVE CLOTHING: Wear clothing that will protect the skin from exposure to this product.

WORK HYGIENIC PRACTICES: Wash hands thoroughly after each use, especially before eating or smoking. Good personal hygiene practices should always be followed.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

ODOR: Hydrocarbon odor

APPEARANCE: Viscous liquid

FLASHPOINT AND METHOD: (108°F)

DENSITY: 7.52

(VOC): < 550.000 g/l

10. STABILITY AND REACTIVITY

STABLE: Yes

HAZARDOUS POLYMERIZATION: No

11. TOXICOLOGICAL INFORMATION

EYE EFFECTS: Irritating to the eyes.

SKIN EFFECTS: Irritating to the skin.

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: No environmental studies have been carried out on this product.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR Part 261.3. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: Combustible Liquid, N.O.S. (in accordance with 49CFR 173.150(f)(2) when transported domestically by ground)

TECHNICAL NAME: Combustible Liquid, N.O.S.

PRIMARY HAZARD CLASS/DIVISION: None

UN/NA NUMBER: None

PACKING GROUP: None

OTHER SHIPPING INFORMATION: Generators must consult DOT laws and regulations to ensure the product is being transported

Proflex RV Instant Roof Repair

appropriately.

15. REGULATORY INFORMATION**UNITED STATES****SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)**

311/312 HAZARD CATEGORIES: This product poses the following physical and health hazard(s) as defined in 40 CFR Part 370 and is subject to the requirements of sections 311 and 312 of Title III of the Superfund Amendments and Reauthorization Act of 1986:

FIRE: Yes **PRESSURE GENERATING:** No **REACTIVITY:** No **ACUTE:** Yes **CHRONIC:** Yes

313 REPORTABLE INGREDIENTS: This product does not contain toxic chemicals subject to the requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

TSCA (TOXIC SUBSTANCE CONTROL ACT)

TSCA REGULATORY: All ingredients of this product are listed or are excluded from listing under the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

CALIFORNIA PROPOSITION 65: This product contains the following product on California's Proposition 65 List: CAS# 67-56-1 Methanol.

COMMENTS This product meets the RoHS guidelines for electronic components and hardware. We certify the following substances are not intentionally introduced to this product: barium, beryllium, cadmium, chromium, cobalt, copper, hexavalent chromium, lead, manganese, mercury, nickel, polybrominated biphenyls, polybrominated diphenyl ethers, selenium, silver, thallium, titanium, zinc.

16. OTHER INFORMATION

APPROVED BY: Technical Staff

PREPARED BY: Technical Staff

REVISION SUMMARY: This MSDS replaces the 10/04/2011 MSDS. Revised: **Section 15:** CALIFORNIA PROPOSITION 65.

NFPA STORAGE CLASSIFICATION: Health 2, Flammability 2, Physical Hazard 0

HMIS RATINGS NOTES: Health 2, Flammability 2, Physical Hazard 0, PPE B

MANUFACTURER DISCLAIMER: Information given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of the product for particular uses are beyond our control; all risks of use of the product are therefore assumed by the user. Nothing is intended as a recommendation for uses which infringe valid patents or as extending license under valid patents. Appropriate warnings and safe handling procedures should be provided to handlers and users.