



Last Rev Date: 03/07/2014

Physical Properties

Appearance Black mastic	Flash Point 120° F	Solids By Weight 78%
Base Refined asphalt	Freezability Does not freeze	Specific Gravity @ 77° F (25°C) 1.12
Color Black	Maximum VOC 250 g/l	Weight Per Gallon 9.1-9.5 lbs
Consistency @ 77° F Soft, easily trowelable paste		

Approvals and Certifications

Meets or exceeds ASTM Specification D-4586, Type I and 100% wet surface adhesion per ASTM D-3409
MIAMI-DADE COUNTY PRODUCT CONTROL APPROVED - HE208R is in compliance TAS 121 with Miami-Dade Cty
NOA #12-0725.04

Description

HE208R - HENRY 208R RUBBERIZED WET PATCH® ROOF LEAK REPAIR is a premium, rubberized roof sealant for sealing roof leaks on wet or dry surfaces. Especially easy to spread in cold temperatures.

Usage

HE208R - HENRY 208R RUBBERIZED WET PATCH® ROOF LEAK REPAIR can be used to:

- Repair holes, cracks, and splits on composition, mineral surface cap sheet, asphalt coated, SBS modified, metal, and masonry roofs.
- Seal leaks and openings around flashings, chimneys, vents, skylights, joints in metal edging, gutters, etc.

Coverage

12 1/2 sq.ft. per gallon applied 1/8" thick.

Surface Preparation

CLEAN: Do not thin or heat container. Clean dirt and loose material from surface. Remove embedded gravel and old roof cement that would interfere with a good bond. Remove rust and scale with wire brush.

Application

1. **APPLY** 1/8" to 1/4" thick with a trowel or putty knife. Work into hole and spread at least 2" beyond, feathering the edges. 2. **REINFORCE:** If hole is over 1/4" wide or 2" long, reinforce with **HENRY 181/183 Repair Fabric** between two layers of cement. For vertical surfaces in hot weather, use **#204 Plastic Roof Cement** or **#505 FlashMaster™**.

Precautions

DO NOT THIN. Do not heat container or store at temperatures greater than 110°F (43°C). When transporting, make sure the pail is secured and the lid is tight to prevent spills. **CLOSE AIR INTAKES ON ROOF UNTIL SOLVENTS DISSIPATE!** May not yield satisfactory results over some APP torch down membranes. Contact Henry and membrane manufacturer before use. Not recommended for use over gravel, rubber or PVC sheet roofing or wood shingles. To extend repair life, coat with a Henry Roof Coating after 30 days.

NOTE: Asphalt-based coatings form a water soluble residue as they weather. In areas without regular rainfall, the roof should be hosed off occasionally to prevent build up and discoloration (removable with soap and water). Areas that pond water may accumulate more asphalt residue.

Cleanup

Clean tools with **Henry Scrubbers™ Hand & Tool Cleaning Towels** or kerosene, paint thinner or mineral spirits. Clean hands with waterless hand cleaner.

Caution

WARNING! COMBUSTIBLE! Contains petroleum distillate. Keep away from heat and flame. Do not heat container or store at temperatures greater than 110°F (43°C). **CLOSE AIR INTAKES** until solvents dissipate. Contains volatile solvents that might contaminate potable water. Close container after each use. Dispose of container and unused contents in accordance with Local, State and Federal regulations. **DANGER! HARMFUL OR FATAL IF SWALLOWED! If swallowed**, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY! Use protective measures to avoid contact with eyes and skin. **In case of eye contact**, open eyelids wide and flush immediately with plenty of water for at least 15 minutes. GET MEDICAL ATTENTION! **USE ONLY WITH ADEQUATE VENTILATION!** Avoid breathing of vapor. If you experience eye watering, headaches, or dizziness, leave area or increase fresh air or wear respirator (**NIOSH/MSHA TC 23C** or equal). Repeated and prolonged occupational overexposure to solvent vapor may cause permanent brain and nervous system damage, and may cause liver or kidney damage.

KEEP OUT OF REACH OF CHILDREN.

FOR EXTERIOR USE ONLY.

WARNING: This product contains detectable amounts of chemicals known to the State of California to cause cancer, or birth defects, or other reproductive harm.

EMPLOYERS should obtain a copy of the **Material Safety Data Sheet (MSDS)** from your supplier or directly from Henry at the toll free number or website below.

Product Sizes

10.1 OZ CART (0 lb)
GALLON (10.9 lb)

29 OZ CARTRIDGE (0.86 lb)
3.5 GALLON (35 lb)

10.1 / 10.3/ 11 OZ (0.86 lb)

Limited Warranty

We, the manufacturer, warrant only that this product is free of defects, since many factors which affect the results obtained from this product - such as weather, workmanship, equipment utilized and prior condition of the substrate - are all beyond our control. We will provide at no charge replacement product if the applicator proves, to our satisfaction, this product was defective within 10 years from purchase date of the product. We will consider this product defective if it does not perform its intended application provided it has been applied in accordance with our written instructions and used with Henry Repair Fabric. Proof of purchase must be provided for this warranty to be effective. **DISCLAIMER OF WARRANTIES AND LIMITATION OF LIABILITY: THIS LIMITED WARRANTY IS IN LIEU OF ANY OTHER WARRANTIES EXPRESS OR IMPLIED INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. MANUFACTURER SHALL HAVE NO LIABILITY OF ANY KIND BEYOND PRODUCT REPLACEMENT, INCLUDING FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES RESULTING FROM ANY DEFECTS OR ANY DELAYS CAUSED BY REPLACEMENT OR OTHERWISE. THIS LIMITED WARRANTY PROVIDES THE PURCHASER'S EXCLUSIVE REMEDY FOR ANY DEFECT IN THE PRODUCT.** This limited warranty is in addition to and supplemented by the product warranty located on our website at: www.henry.com/warranty which also applies to this product.