



INSULATED FIRE RATED ACCESS DOOR WITH DRYWALL BEAD

Model KRP-350FR

For Walls And Ceilings



KARP ASSOCIATES, INC.
 84-84 43rd Street, Maspeth, NY 11378
 (718) 784-2105 - Phone
 (718) 784-8189 - Fax

DATE

SPECIFICATIONS

GENERAL SCOPE:

Classified access frame and fire door assembly 3 hour "B" Label Underwriters Laboratories File # R-10806. Warnock Hersey File # U81466.

CONSTRUCTION:

1. Frame shall be 16 gage steel, 1" wide, surrounded by galvanized drywall bead.
2. Door shall be 20 gage steel, welded pan type filled with 2" thick fire-rated insulation, and shall open to 175°, be self-latching with automatic closer and interior latch release.
3. Hinge shall be continuous piano hinge.
4. Latches shall be bolt type, operated by either a ring turn or flush key device (both provided and all keyed alike), or doors shall be prepared for locks which shall be supplied by others.
5. Finish shall be prime coat of rust inhibitive electrostatic powder, baked grey enamel. Stainless steel doors shall have #4 satin finish.

STANDARD SIZES

DOOR SIZE H X W (IN.)	WALL/CEILING OPENING (IN.)	NUMBER OF LATCHES	SHIP WT. (LBS.)
8 x 8	8 3/8 x 8 3/8	1	6.1
12 x 12	12 3/8 x 12 3/8	1	9.3
14 x 14	14 3/8 x 14 3/8	1	12.2
16 x 16	16 3/8 x 16 3/8	1	13.6
18 x 18	18 3/8 x 18 3/8	1	18.2
24 x 12	24 3/8 x 12 3/8	1	14.9
22 x 22	22 3/8 x 22 3/8	1	23.5
24 x 24	24 3/8 x 24 3/8	1	25.7
30 x 22	30 3/8 x 22 3/8	1	26.8
30 x 24	30 3/8 x 24 3/8	1	31.0
30 x 30*	30 3/8 x 30 3/8	1	36.3
32 x 32*	32 3/8 x 32 3/8	1	39.8
36 x 22	36 3/8 x 22 3/8	2	33.1
36 x 24	36 3/8 x 24 3/8	2	38.7
36 x 36*	36 3/8 x 36 3/8	2	50.1
48 x 24*	48 3/8 x 24 3/8	2	47.1
48 x 36*	48 3/8 x 36 3/8	2	59.7
48 x 48*	48 3/8 x 48 3/8	2	85.7

*NOTE: All doors sized larger than 24" wide are for walls only. Not available for ceilings.

PROJECT DATA
Project Name:
Architect:
Contractor:
Agent/Customer Name:
Tagging Instructions:
Special Instructions:

PROJECT SCHEDULE					
Qty.	H	W	No. of Latches	Finish	Remarks

