



SPECIFICATIONS

MODEL GP-3A

AIR OPERATED GROUT PUMP

Model: Kenrich GP-3A

Pump Type: Single Diaphragm, Self-Priming

Power Source: Compressed Air

Air Consumption: Less than 3 cfm

Pump Controls: Start/Stop Switch, Speed Control, Air Pressure Regulator and Gauge

***Output Capacity:** 5 gallons/minute (40 cu. ft./hr)

Output Pressure: 15 psi Maximum

Hopper Capacity: .62 cubic foot (4.6 gallons)

Placement Hose Size: 1-1/2" ID x 60" long, Clear Vinyl

Discharge Head: 10 foot Vertical Lift

Dimensions: 23-1/2" x 12" x 23" high

Net Weight: 27 pounds

*Output and performance will vary depending on cycle rate, viscosity of the grout mixture and pressure conditions.

OPTIONS

Remote Start/Stop Switch: Can be mounted at output end of placement hose

Hose Reducer Kits: 3/4" and 1" ID Available

1-1/2" ID Hose Lengths: 10 feet, 15 feet, and 20 feet

1-1/2" Hose Ends: Straight, 90 degree and 180 degree Elbows

Port Seal: Rubber, will fit 1-1/2" Hose Ends

KENRICH PRODUCTS, INC.

PHONE: 503/281-6190

email: rick@kenrichproducts.com