

550/600

CSA Approval #83070



600-D

Two (2) 600s are seamed together to form the 600-d

550/600 Series

- Includes 8 X 8 Permakote Aluminum
 Screen extends to the edges of the cap.
- Large nailing flange.
- Rolled flange on vent stack to prevent weather infiltration.
- All Aluminum construction.
 Available in black, brown, weathered
- bronze, and white baked enamel finish, as well as mill finish.
- NOTE: These are exhaust louvers



550-S/600-S

Models 550–S and 600–s have a tall throat to allow room for air circulation on shake roofs after the installation of shakes.

550 Series

Model No.	Overall Size	Opening Size	Sq. In. Net Free Area	Square Feet Louver Ventilates	No. Per Carton	Weight Per Carton
*550	15 3/8" x 16 1/2" x 4"	9"	50	104	6	8 lbs.
550-S	15 3/8" x 16 1/2" x 5 1/2"	9"	50	104	6	9 1/4 lbs.

^{*} Denotes Most Popular Models.

600 Series

Model No. Overall Size Opening Size

			Sq. In. Net Free Area	Sq. Ft. Louver Ventilates	No. Per Carton	Weight Per Carton
*600	16 5/8" x 18 7/8" x 4"	9 1/2"	60	125	6	10 1/2 lbs.
600-D	32 1/2" x 18 7/8" x 4"	Two 9 1/2"	120	250	4	13 lbs.
600-S	16 5/8" x 18 7/8" x 6 1/2"	9 1/2"	60	125	4	8 1/4 lbs.

^{*} Denotes Most Popular Models.

Model 135

- Includes attached 8x8 Permakote aluminum screen.
- Weather–shielding rain guard for maximum weather protection.

 Available in black, brown, weathered
- bronze, or white baked enamel finishes, as well as mill finish.
- Provides 144 square inches of net–free area.



- The 135 is Dade County approved Acceptance # 98–0522.01
- 14" Diameter opening
- NOTE: The 135 is an exhaust louver, for intake click here!

Model No.	Overall Size	Opening Size	Sq. In. Net Free Area	Square Feet Louver Ventilates	No. Per Carton	Weight Per Carton
*135	20" x 23" x 7	14"	144	300	2	14 1/4 lbs.

^{*} Denotes Most Popular Models.