

IV-9 FEATURES:

- Complete invisibility when installed.
- Aerodynamically curved internal baffles to minimize wind resistance.
- Excellent airflow design with superior weather protection and no filter to clog.

- Tough durable construction.
- Works on any pitch roof.
- Interlocking self alignment design with weatherproof over lapping joint.
- Quick, easy installation.
- Works on all tile roofs with use of a batten system.
- ▶ 9" net free area per linear foot.

- Supported molded in nail holes.
- Molded-in weep openings, nail holes and end plug.
- Cut line provided for two foot lengths.
- Engineered material guarantees longevity.
- Patented design.
- 30 year transferable warranty.

IV-9 Tile Roof Vent Specifications

NFA	Color	Length	Roof	Carton	
(in.2)		(ft.)	Pitch	Quantity	
9 Per Linear Foot	Black	4	2/12 & up	12	



Want more info? Scan this QR code with your smartphone.

How many Tile Vents do you need?

Attic floor space in square feet. 1000 1500 2000 2500 3000 3500

TILEINTAKE® INTAKE SYSTEM IV-9 Required 20 10 Exhaust Required (in.2) 288 360 504 648 720 864

Use with Lomanco *TileRidge®* exhaust vents for a complete TILE ROOF VENTILATION SYSTEM!

TILERIDGE® EXHAUST SYSTEM									
TRV-4 Required	8	10	14	18	20	24			
Intake Required (in 2)	288	360	504	648	720	864			

LO457 0714







