

## LEGACY®

Note: Malarkey Roofing Products™ (Malarkey) inventory SKU numbers for this product: **272 Legacy**, & **273 Legacy** featuring the Scotchgard™ Algae Resistant Roofing System from 3M™

**Product Use:** Legacy® SBS rubber-modified asphalt-laminated shingles are used whenever increased flexibility, architectural design, tensile strength, and tear-resistance is desired. These SBS rubber-modified asphalt shingles are designed for a 5 5/8" exposure.

**Composition and Materials:** Legacy® is mineral-surfaced and self-sealing, made with SBS rubber-modified asphalt coating and fire-retardant fillers on a Malarkey fiberglass mat. Legacy features the exclusive nail accuracy-enhancing design of The Zone™.

**Application Procedure:** All shingles should be applied over underlayment, Malarkey Right Start UDL™ or an approved substitute. Installation instructions are available on the shingle wrapper, at [www.Malarkey-Roofing.com](http://www.Malarkey-Roofing.com) or by contacting your local Malarkey representative. Industry standards are found in NRCA manuals. Shingles should be attached to decking by approved fasteners. Malarkey recommends the use of nails for fastening.

### Technical Data

Typical Properties:

Approximate Weight	275 lbs. (124.74 kg) per square
Dimensions	13-1/4" (± 1/8") x 40" (± 1/4") (.33 m x 1.02 m)
Exposure	5-5/8" (142.9 mm)
Shingles per square	64 shingles (4 bundles/square)
Granule Adhesion	0.5 gram loss
Fire Rating	Class 'A'
Warranty	50-year Limited Warranty
	110 mph (177 kph) Limited Wind Warranty
Algae Resistance Warranty	Legacy® sku #273 features a 20-Year Scotchgard Warranty

As manufactured, Legacy meets the requirements of:  
 ASTM D3018 Type 1; ASTM D3161 Class F; ASTM D3462; ASTM D7158 Class H;  
 ASTM E108 Class A; UL 2218 Class 4 Impact Resistance; CSA A123.5.  
 ICC Approval - ESR 3150  
 FBC Approval - #14809

**Warranty:** The Legacy® shingle carries a 50-year limited warranty and a 110 m.p.h. limited wind warranty. Documents may be obtained from your roofer, local distribution center or at [www.MalarkeyRoofing.com](http://www.MalarkeyRoofing.com). Deviations from recommended application procedures may affect warranty coverage.

**Precautions:** Legacy® shingles require dry storage or plastic-covered storage and protection from the weather until applied. Do not use on roofs where the slope is less than 2". For slopes 2" to 4", additional deck protection is recommended. Legacy® shingles have a factory-applied self-sealing strip that activates in warm weather. When applied in cold weather or windy location, hand-sealing is recommended but not required if sealant activates. In high wind areas, six nails are required. Contact Malarkey for further conditions and instructions.

**Technical Assistance:** Malarkey has technical services assistance available. Contact Malarkey for details at (800) 545-1191 or (503) 283-1191, weekdays 7:00 a.m. to 5:00 p.m. Pacific Time.

**Availability:** Legacy® is available in many standard colors and with the Scotchgard™ Algae Resistant Roofing System from 3M™. Malarkey Legacy® shingles are available throughout North America and Pacific Rim Countries. Visit [WWW.MALARKEYROOFING.COM](http://WWW.MALARKEYROOFING.COM) for additional product information and availability.