



## **B.U.R., Modified, & Steep Slope Roofing Systems**

### **2. Product Data Guide**

**THIS PAGE INTENTIONALLY LEFT BLANK**



**Malarkey**  
**Roofing Products™**

---

**PRODUCT**

---

**DATA GUIDE**

---



**THIS PAGE INTENTIONALLY LEFT BLANK**

---

## PRODUCT

---

|   |       |
|---|-------|
| SHINGLES                                  | 2-3   |
| HIP & RIDGE                               | 3     |
| UNDERLAYMENT                              | 4     |
| ICE & WATER GUARD                         | 4     |
| ROLL ROOFING                              | 4     |
| CONVENTIONAL BASE SHEETS                  | 4     |
| CONVENTIONAL CAP SHEETS                   | 4     |
| CONVENTIONAL PLY SHEETS                   | 5     |
| SBS MODIFIED BASE & CAP SHEETS            | 5 & 6 |
| APP MODIFIED BASE & CAP SHEETS            | 6     |
| WALKBOARD                                 | 7     |
| SEBS ROOFING ASPHALT                      | 7     |
| SATELLITE ROOF COATINGS & PLASTIC CEMENTS | 7 & 8 |

---

### STOCK ITEMS AND COLORS

Stock items and colors are normally available from our inventories for immediate shipment.

---

### \*\* SPECIAL ORDER ITEMS AND COLORS \*\*

A minimum of 400 squares per run, with the customer taking all overruns up to 10% of original order quantity with a \$600.00 special color run charge per production run. If a product features *3M™ Scotchgard™ Algae Resistant Roofing System* there will be an additional charge. All special run products must be shipped from Malarkey within 10 business days after Malarkey produces the product.

Please contact your local Malarkey Sales Representative for additional details.

---

### FOR ADDITIONAL INFORMATION

call or write:

Malarkey Roofing Products

P.O. Box 17217

Portland, OR 97217

(503) 283-1191 or (800) 545-1191

Facsimile (503) 289-7644

Website: [www.malarkeyroofing.com](http://www.malarkeyroofing.com)

Typical office hours: 8 am - 5 pm Pacific time

#### Order Desk

(503) 283-0182 or (800) 545-0182

Facsimile (503) 283-8069

#### Technical Services

(503) 283-1191 or (800) 545-1191

Facsimile (503) 283-5405

---

This information is effective 01/2006 and supersedes all previously published data. Malarkey Roofing Products reserves the right to change any information contained herein without notice.

## Shingles

| ITEM       | PRODUCT   | PRODUCT SPECIFICATIONS   | COLORS   | COMPLIES WITH  |
|------------|---|--|--|--|
| <b>202</b> | <b>Dura-Seal™ 20</b><br>Metric Fiberglass<br>3-Tab Shingle                          | Apr. Wt./Sq.: 200 lbs. (90.7 kg)<br>Shingles/Sq.: 66<br>Bundles/Sq.: 3<br>Exposure: 5 <sup>5</sup> / <sub>8</sub> " (142.9 mm)<br>Squares/Pallet: 20 PDX<br>Squares/Pallet: 16 South Gate<br>20-Year Ltd. Warranty<br>54 mph Ltd. Wind Warranty  | Antique Brown<br>Midnight Black<br>Oxford Grey<br>Sienna Blend<br>Silverwood<br>Golden Brown*<br>Sienna Shadow*<br>Dove White*<br>*South Gate Only | ASTM D 3018 & 3161 Type I<br>ASTM E 108<br>UL Class A Fire Rating  |
| <b>204</b> | <b>Dura-Seal™ 25</b><br>Metric Fiberglass<br>3-Tab Shingle                          | Apr. Wt./Sq.: 235 lbs. (106.6 kg)<br>Shingles/Sq.: 66<br>Bundles/Sq.: 3<br>Exposure: 5 <sup>5</sup> / <sub>8</sub> " (142.9 mm)<br>Squares/Pallet: 16 PDX<br>Squares/Pallet: 14 South Gate<br>25-Year Ltd. Warranty<br>54 mph Ltd. Wind Warranty | Antique Brown<br>Midnight Black<br>Oxford Grey<br>Rainforest<br>Sienna Blend<br>Silverwood<br>Weathered Wood<br>Dove White*<br>*South Gate Only    | ASTM D 3462, 3161 Type I,<br>& 3018 Type I<br>ASTM E 108<br>UL Class A Fire Rating<br>ICBO ER-5300<br>CAN/CSA A 123.5-M90  |
| <b>230</b> | <b>Alaskan®</b><br>SBS Modified Metric<br>3-Tab Shingle<br>Featuring Polyglass® Mat | Apr. Wt./Sq.: 235 lbs. (106.6 kg)<br>Shingles/Sq.: 66<br>Bundles/Sq.: 3<br>Exposure: 5 <sup>5</sup> / <sub>8</sub> " (142.9 mm)<br>Squares/Pallet: 16<br>35-Year Ltd. Warranty<br>100 mph Ltd. Wind Warranty<br>Class 4 Impact Resistant         | Antique Brown<br>Midnight Black<br>Oxford Grey<br>Rainforest<br>Sienna Blend<br>Silverwood<br>Weathered Wood                                       | ASTM D 3462, 3161 Type I,<br>& 3018 Type I<br>ASTM E 108<br>Miami-Dade Approval<br>NOA #00-1127.05<br>State of Florida Approval #FL3851<br>UL 2218 Class 4<br>ICBO ER-5300<br>WH Class A Fire<br>CAN/CSA A 123.5-M90 |

*Available featuring 3M™ Scotchgard™ Algae Resistant Roofing System upon request. Scotchgard™ treated product may be shipped in #240 Hurricane™ wrappers.*

## Laminated Shingles

| ITEM       | PRODUCT   | PRODUCT SPECIFICATIONS  | COLORS  | COMPLIES WITH  |
|------------|---|---|---|--|
| <b>270</b> | <b>Northwest-XL®</b><br>Laminated Shingle   | Apr. Wt./Sq.: 260 lbs. (117.9 kg)<br>Shingles/Sq.: 64<br>Bundles/Sq.: 4<br>Exposure: 5 <sup>5</sup> / <sub>8</sub> " (142.9 mm)<br>Squares/Pallet: 12<br>40-Year Ltd. Warranty<br>80 mph Ltd. Wind Warranty | Antique Brown<br>Black Oak<br>Storm Grey<br>Midnight Black<br>Oxford Grey<br>Sienna Blend<br>Silverwood<br>Weathered Wood<br>Natural Wood | ASTM D 3462, 3161 Type I,<br>& 3018 Type I<br>ASTM E 108<br>State of Florida Approval #FL3739<br>WH Class A Fire Rating<br>CAN/CSA A 123.5-M90 |
| <b>269</b> | <i>All colors available featuring 3M™ Scotchgard™ Algae Resistant Roofing System; 20-Year Ltd. Algae Resistance Warranty available.</i> |   |   |  |
| <b>271</b> | <b>Highlander-CS®</b><br>Laminated Shingle  | Apr. Wt./Sq.: 245 lbs. (111 kg)<br>Shingles/Sq.: 64<br>Bundles/Sq.: 4<br>Exposure: 5 <sup>5</sup> / <sub>8</sub> " (142.9 mm)<br>Squares/Pallet: 12<br>30-Year Ltd. Warranty<br>70 mph Ltd. Wind Warranty   | Antique Brown<br>Midnight Black<br>Oxford Grey<br>Storm Grey<br>Sienna Blend<br>Silverwood<br>Natural Wood<br>Weathered Wood              | ASTM D 3462, 3161 Type I,<br>& 3018 Type I<br>ASTM E 108<br>WH Class A Fire Rating<br>CAN/CSA A123.5 M90*                                      |
| <b>277</b> | <i>All colors available featuring 3M™ Scotchgard™ Algae Resistant Roofing System; 20-Year Ltd. Algae Resistance Warranty available.</i> |   |   |  |



## Laminated Shingles

| ITEM | PRODUCT  | PRODUCT SPECIFICATIONS  | COLORS   | COMPLIES WITH   |
|------|--|---|--|---|
| 272  | <b>Legacy®</b><br>SBS Modified<br>Laminated Shingle<br>Class 4 Impact Resistant<br>                                     | Appr. Wt./Sq.: 275 lbs. (124.8 kg)<br>Shingles/Sq.: 64<br>Bundles/Sq.: 4<br>Exposure: 5 <sup>5</sup> / <sub>8</sub> " (142.9 mm)<br>Squares/Pallet: 12<br>50-Year Ltd. Warranty<br>110 mph Ltd. Wind Warranty                             | Antique Brown<br>Midnight Black<br>Oxford Grey<br>Storm Grey<br>Sienna Blend<br>Silverwood<br>Rainforest<br>Natural Wood<br>Weathered Wood | ASTM D 3462, 3161 Type I,<br>& 3018 Type I  |
|      |  |   |  | ASTM E 108<br>State of Florida Approval #FL3692<br>UL 2218 Class 4<br>ICBO ER-5300<br>WH Class A Fire Rating<br>CAN/CSA A 123.5-M90 |
| 273  | <b>Legacy®</b><br>SBS Modified<br>Laminated Shingle<br>Class 4 Impact Resistant<br>featuring 3M™<br>Scotchgard™<br>Algae Resistant<br>Roofing System<br>20-Year Ltd. Algae Resistance Warranty Available | Appr. Wt./Sq.: 275 lbs. (124.8 kg)<br>Shingles/Sq.: 64<br>Bundles/Sq.: 4<br>Exposure: 5 <sup>5</sup> / <sub>8</sub> " (142.9 mm)<br>Squares/Pallet: 12<br>50-Year Ltd. Warranty<br>110 mph Ltd. Wind Warranty<br>Class 4 Impact Resistant | Antique Brown<br>Midnight Black<br>Oxford Grey<br>Storm Grey<br>Sienna Blend<br>Silverwood<br>Rainforest<br>Natural Wood<br>Weathered Wood | ASTM D 3462, 3161 Type I,<br>& 3018 Type I  |
|      |  |   |  | ASTM E 108<br>State of Florida Approval #FL3692<br>UL 2218 Class 4<br>WH Class A Fire Rating<br>CAN/CSA A 123.5-M90                 |

## Matching Hip and Ridge Strips

| ITEM | PRODUCT  | PRODUCT SPECIFICATIONS   | COLORS  |
|------|--|--|---|
| 221  | <b>Pro Design™</b><br>SBS Modified<br>Decorative, High Profile<br>Hip & Ridge Shingle  | Appr. Wt./Box: 60 lbs. (27.3 kg)<br>Units/Box: 48<br>Ln Ft. Coverage: 30' (9.75 m)<br>Exposure: 8" (203.2 mm)<br>Width: 10" (254 mm)<br>Boxes/Pallet: 24   | Antique Brown<br>Autumn Blend<br>Birchwood<br>Black Oak<br>Burnt Wood<br>Cedar<br>Chaparral<br>Midnight Black |
|      |  |  | Desert Tan<br>Dove White<br>Natural Wood<br>Oxford Grey<br>Pewter<br>Rainforest<br>Redwood<br>Sage            |
| 223  | <b>Rake 'n Ridge™</b><br>SBS Modified<br>Decorative, High Profile<br>Hip & Ridge Shingle   | Appr. Wt./Box: 45 lbs. (20.5 kg)<br>Units/Box: 48<br>Ln Ft. Coverage: 30' (9.75 m)<br>Exposure: 8" (203.2 mm)<br>Width: 8" (203.2 mm)<br>Boxes/Pallet: 26  | Antique Brown<br>Autumn Blend<br>Birchwood<br>Black Oak<br>Burnt Wood<br>Cedar<br>Chaparral<br>Midnight Black |
|      |  |  | Desert Tan<br>Dove White<br>Natural Wood<br>Oxford Grey<br>Pewter<br>Rainforest<br>Redwood<br>Sage            |
| 225  | <b>SBS Modified<br/>                     Hip &amp; Ridge Strips</b><br>featuring 3M™<br>Scotchgard™<br>Algae Resistant<br>Roofing System<br>Scored Seal Down Strip<br>Provides 13 <sup>1</sup> / <sub>4</sub> " x 9 <sup>7</sup> / <sub>8</sub> " Unit<br>20-Year Ltd. Algae Resistance Warranty Available | Appr. Wt./Bundle: 70 lbs. (31.8 kg)<br>Units/Bundle: 88<br>Shingles/Bundle: 22<br>Ln Ft. Coverage: 41' 3" (12.6 m)<br>Exposure: 5 <sup>5</sup> / <sub>8</sub> " (142.9 mm)<br>Bundles/Pallet: 60 | Antique Brown<br>Midnight Black<br>Oxford Grey<br>Sienna Blend<br>Silverwood<br>Rainforest                    |
|      |  |  | Weathered<br>Wood<br>Black Oak<br>Natural Wood<br>Storm Grey  |

### Underlayment - Universal Steep Slope Underlayment

| ITEM | PRODUCT   | PRODUCT SPECIFICATIONS   | SURFACING                        | COMPLIES WITH  |
|------|---|--|----------------------------------|--|
|      | <b>Right Start UDL®</b><br>Premium Fiberglass<br>SBS Modified<br>Underlayment | Appr. Wt./Roll: 75 lbs. (34.0 kg)<br>Coverage: 2 square<br>Width: 39 <sup>3</sup> / <sub>8</sub> " (1 m)<br>Length: 66' (20.1 m)<br>Rolls/Pallet: 25 PDX, 30 Southgate | Sand Parting Agent<br>Both Sides | ASTM D 4601-97a Type II<br>UL Class A Fire Rated<br>State of Florida Approval #FL3614<br>ICC Report ESR 1561<br>Meets Requirements For:<br>ASTM D 4869 & 226 Type II<br>AC 165 |

### Ice & Water Guard

| ITEM       | PRODUCT   | PRODUCT SPECIFICATIONS  | COMPLIES WITH |
|------------|---|---|---------------|
| <b>170</b> | <b>Arctic Seal™</b><br>Ice & Water<br>Eave & Valley Guard | Appr. Wt./Roll: 84 lbs. (38.1 kg)<br>Coverage: 200 sq. ft./roll<br>Width: 39 <sup>3</sup> / <sub>8</sub> " (1 m)<br>Length: 65' 8" (20.0 m)<br>Rolls/Pallet: 20 | ASTM D 1970   |

### Roll Roofing

| ITEM       | PRODUCT  | PRODUCT SPECIFICATIONS   | COLORS   | COMPLIES WITH  |
|------------|--|--|--|--|
| <b>350</b> | Premium Fiberglass<br>Mineral Surfaced<br>SBS Modified Cap Sheet | Appr. Wt./Roll: 78 lbs. (35.4 kg)<br>Coverage: 1 square<br>Width: 39 <sup>3</sup> / <sub>8</sub> " (1 m)<br>Length: 33' (10 m)<br>Rolls/Pallet: 25 PDX, 30 Southgate | Antique Brown<br>Dove White<br>Midnight Black<br>Oxford Grey<br>Sienna Blend<br>Silverwood<br>Rainforest<br>Weathered Wood<br>Black Oak<br>Natural Wood<br>Storm Grey<br>Red | ASTM D 3909-97b<br>UL 55 A Type G3<br>WH Listed<br>Zero Perm<br><i>Tested to</i> ASTM D 5147-97<br><br>UL listed as an approved<br>fire-rated underlayment |

### Fiberglass Built-Up Roofing

#### Base Sheets - Conventional

| ITEM       | PRODUCT                           | PRODUCT SPECIFICATIONS   | SURFACING                        | COMPLIES WITH  |
|------------|-----------------------------------|--|----------------------------------|--|
| <b>515</b> | Standard Fiberglass<br>Base Sheet | Appr. Wt./Roll: 83 lbs. (37.7 kg)<br>Coverage: 3 square<br>Width: 39 <sup>3</sup> / <sub>8</sub> " (1 m)<br>Length: 99' (30.2 m)<br>Rolls/Pallet: 20 | Sand Parting Agent<br>Both Sides | ASTM D 4601-97a Type II<br>UL 55 A Type G2<br>FM & WH Listed |

#### Cap Sheets - Conventional

| ITEM       | PRODUCT                                  | PRODUCT SPECIFICATIONS   | COLORS                              | COMPLIES WITH  |
|------------|--|--|-------------------------------------|--|
| <b>502</b> | <b>Premium1™</b><br>Fiberglass Cap Sheet | Appr. Wt./Roll: 72 lbs. (32.7 kg)<br>Coverage: 1 square<br>Width: 39 <sup>3</sup> / <sub>8</sub> " (1 m)<br>Length: 33' (10 m)<br>Rolls/Pallet: 25 PDX, 30 Southgate | Dove White<br>Midnight Black<br>Tan | ASTM D 3909-97B<br>UL 55 A Type G3<br>FM & WH Listed |



## Ply Sheets - Conventional

| ITEM | PRODUCT  | PRODUCT SPECIFICATIONS   | COMPLIES WITH  |
|------|--|--|--|
| 500  | <b>Premium1™</b><br>Fiberglass Ply Sheet       | Appr. Wt./Roll: min. 36 lbs. (16.3 kg)<br>Coverage: 5 square<br>Width 39 <sup>3</sup> / <sub>8</sub> " (1 m), Length: 165' (50.3 m)<br>Rolls/Pallet: 25 PDX, 30 Southgate<br><i>Available in 10 square roll - 16 rolls/pallet, 72 lbs./roll*</i><br>*Southgate production only | ASTM D 2178-97a Type IV<br>UL 55 A Type G1<br>FM & WH Listed |
| 506  | <b>Super6™</b><br>Premium Fiberglass Ply Sheet | Appr. Wt./Roll: min. 46 lbs. (20.9 kg)<br>Coverage: 5 square<br>Width: 39 <sup>3</sup> / <sub>8</sub> " (1 m)<br>Length: 165' (50.3 m)<br>Rolls/Pallet: 20 PDX, 30 Southgate   | ASTM D 2178-97a Type VI<br>UL 55 A Type G1<br>FM & WH Listed |

## SBS Modified BUR Base & Ply Sheets

| ITEM | PRODUCT   | PRODUCT SPECIFICATIONS  | SURFACING   | COMPLIES WITH  |
|------|---|---|---|--|
| 501  | <b>Premium1™</b><br>Fiberglass<br>SBS Base Sheet      | Appr. Wt./Roll: 92 lbs. (41.8 kg)<br>Coverage: 3 square<br>Width: 39 <sup>3</sup> / <sub>8</sub> " (1 m)<br>Length: 99' (30.2 m)<br>Rolls/Pallet: 20  | Sand Parting Agent<br>Both Sides                        | ASTM D 4601-97a Type II<br>UL 55 A Type G2<br>FM & WH Listed                     |
| 503  | <b>Premium1™</b><br>Fiberglass<br>SBS Base Sheet      | Appr. Wt./Roll: 70 lbs. (31.7 kg)<br>Coverage: 2 square<br>Width: 39 <sup>3</sup> / <sub>8</sub> " (1 m)<br>Length: 66' (20.1 m)<br>Rolls/Pallet: 25  | Sand Parting Agent<br>Both Sides                        | ASTM D 4601-97a Type II<br>UL, FM & WH Listed                                    |
| 602  | <b>Arctic Shield™</b><br>Fiberglass<br>SBS Base Sheet | Appr. Wt./Roll: 95 lbs. (43.1 kg)<br>Coverage: 2 square<br>Width: 39 <sup>3</sup> / <sub>8</sub> " (1 m)<br>Length: 66' (20.1 m)<br>Rolls/Pallet: 20  | Sand Parting Agent<br>Both Sides                        | ASTM D 4601-97a Type II<br>UL, FM & WH Listed                                    |
| 603  | <b>Superbase™</b><br>Fiberglass<br>SBS Base Sheet     | Appr. Wt./Roll: 75 lbs. (34. kg)<br>Coverage: 1 square<br>Width: 39 <sup>3</sup> / <sub>8</sub> " (1 m)<br>Length: 33' (10 m)<br>Rolls/Pallet: 28     | Sand Parting Agent<br>Both Sides                        | ASTM D 6163 Type II,<br>& 4601-97a Type II<br>FM & WH Listed                     |
| 605  | <b>Panoply™</b><br>Fiberglass<br>SBS Base Sheet       | Appr. Wt./Roll: 100 lbs. (45.4 kg)<br>Coverage: 2 square<br>Width: 39 <sup>3</sup> / <sub>8</sub> " (1 m)<br>Length: 66' (20.1 m)<br>Rolls/Pallet: 20 | Sand Parting Agent<br>Both Sides                        | ASTM D 4601-97a Type II<br>FM & WH Listed<br><i>Tested to:</i><br>ASTM D 5147-97 |
| 1000 | <b>ESHAvent®</b>                                      | Appr. Wt./Roll: 75 lbs. (34. kg)<br>Coverage: 1.5 square<br>Width: 39 <sup>3</sup> / <sub>8</sub> " (1 m)<br>Length: 49.2' (15 m)<br>Rolls/Pallet: 27 | Sand Parting Agent,<br>Top;<br>Release Sheet,<br>Bottom | Listed by WH & FM<br>for fire-resistance<br>and 1-90 wind uplift                 |

## SBS Modified BUR Cap Sheets

| ITEM       | PRODUCT  | PRODUCT SPECIFICATIONS  | COLORS                              | COMPLIES WITH  |
|------------|--|---|-------------------------------------|--|
| <b>601</b> | High Performance Premium Polyglass® SBS Modified Mineral Cap Sheet | Appr. Wt./Roll: 100 lbs. (45.4 kg)<br>Coverage: 1 square<br>Width: 39 <sup>3</sup> / <sub>8</sub> " (1 m)<br>Length: 34' (10.3 m)<br>Rolls/Pallet: 20 PDX, 25 Southgate | Dove White<br>Midnight Black<br>Tan | ASTM D 3909- 97b<br>UL, FM & WH Listed<br><i>Tested to:</i><br>ASTM D 5147- 97 |
| <b>625</b> | Paragon™ SBS Modified Mineral Cap Sheet                            | Appr. Wt./Roll: 102 lbs. (46.3 kg)<br>Coverage: 1 square<br>Width: 39 <sup>3</sup> / <sub>8</sub> " (1 m)<br>Length: 34' (10.4 m)<br>Rolls/Pallet: 20                   | Dove White<br>Midnight Black        | ASTM D 3909- 97b, 5147-97 & 6163-97 Type I<br>WH & FM Listed                   |
| <b>650</b> | Panoply™ SBS Modified Mineral Cap Sheet                            | Appr. Wt./Roll: 76 lbs. (34.5 kg)<br>Coverage: 0.75 square<br>Width: 39 <sup>3</sup> / <sub>8</sub> " (1 m)<br>Length: 26' (7.9 m)<br>Rolls/Pallet: 25                  | Dove White<br>Midnight Black        | ASTM D 3909- 97b, 5147-97 & 6163-97 Type II<br>WH & FM Listed                  |

| ITEM        | PRODUCT   | PRODUCT SPECIFICATIONS  | SURFACING  | COMPLIES WITH   |
|-------------|---|---|--|---|
| <b>1020</b> | ESHAlum® SBS Modified Aluminum Surfaced Cap Sheet | Appr. Wt./Roll: 97 lbs. (44.0 kg)<br>Coverage: 1 square<br>Width: 39" (1 m)<br>Length: 33' (10 m)<br>Rolls/Pallet: 25 | Aluminum Foil Surface<br>Torch Applied<br>Burn-off Sheet on back | WH, UL & FM Listed<br><i>Tested To:</i><br>ASTM D 5147-97, 3909-97b, 146, & 6298-98 |

## APP Modified Base Sheets

| ITEM       | PRODUCT                                  | PRODUCT SPECIFICATIONS   | SURFACING                     | COMPLIES WITH  |
|------------|--|--|-------------------------------|--|
| <b>159</b> | APP Torchable Base Sheet                 | Nom. Wt./Roll: 90 lbs. (40.9 kg)<br>Coverage: 2 square<br>Width: 39 <sup>3</sup> / <sub>8</sub> " (1 m)<br>Length: 65.3' (19.91 m)<br>Rolls/Pallet: 20 | Smooth<br>Surfaced<br>Product | WH & UL Listed<br><i>Tested to:</i><br>ASTM D 6509 & 5147-97 |
| <b>160</b> | APP Torchable Polyester Smooth Cap Sheet | Nom. Wt./Roll: 90 lbs. (40.9 kg)<br>Coverage: 1 square<br>Width: 39 <sup>3</sup> / <sub>8</sub> " (1 m)<br>Length: 32.8' (10 m)<br>Rolls/Pallet: 23    | Smooth<br>Surfaced<br>Product | WH & UL Listed<br><i>Tested to:</i><br>ASTM D 6222 & 5147-97 |

## APP Modified Cap Sheets

| ITEM       | PRODUCT                                      | PRODUCT SPECIFICATIONS   | COLORS   | COMPLIES WITH  |
|------------|--|--|--|--|
| <b>161</b> | APP Torchable Polyester Mineral FR Cap Sheet | Nom. Wt./Roll: 105 lbs. (47.7 kg)<br>Coverage: 1 square<br>Width: 39 <sup>3</sup> / <sub>8</sub> " (1 m)<br>Length: 32.8' (10 m)<br>Rolls/Pallet: 20 | White<br>Tan<br><i>(Other colors available on request)</i> | WH & UL Listed<br><i>Tested to:</i><br>ASTM D 6222 & 5147-97 |
| <b>162</b> | APP Torchable Polyester Mineral Cap Sheet    | Nom. Wt./Roll: 105 lbs. (47.7 kg)<br>Coverage: 1 square<br>Width: 39 <sup>3</sup> / <sub>8</sub> " (1 m)<br>Length: 32.8' (10 m)<br>Rolls/Pallet: 20 | White<br>Tan<br><i>(Other colors available on request)</i> | WH & UL Listed<br><i>Tested to:</i><br>ASTM D 6222 & 5147-97 |

## Walk Board

| ITEM       | PRODUCT                        | PRODUCT SPECIFICATIONS  | COLORS |
|------------|--------------------------------|---|--------|
| <b>140</b> | Recycled Rubber Walkboard Pads | 3' x 4' pad<br>Appr. Wt.: 3 lbs./sq. ft.,<br>36 lbs./pad<br>Dimensions: 3' X 4'<br>Thickness: 1/2"<br>Pads per Pallet: 100    | Black  |
| <b>141</b> | Recycled Rubber Walkboard Pads | 32" x 36" pad<br>Appr. Wt.: 2 lbs./sq. ft.,<br>16 lbs./pad<br>Dimensions: 32" X 36"<br>Thickness: 3/8"<br>Pads per Pallet: 50 | Black  |

## Roofing Asphalt

*For hot application of built-up roofing and waterproofing*

| ITEM       | PRODUCT              | PRODUCT SPECIFICATIONS                             | SOFTENING POINT | COMPLIES WITH        |
|------------|----------------------|--|-----------------|----------------------|
| <b>950</b> | SEBS Mopping Asphalt | Wt./Carton: 50 lbs. (22.7 kg)<br>Carton/Pallet: 48 | 205 F ± 5 F     | ASTM D 312 & 6152-97 |

## Satellite™ Roof Coatings & Plastic Cements *Asbestos Free*

| ITEM                                   | PRODUCT              | PRODUCT SPECIFICATIONS   | COLORS                           | COMPLIES WITH            |
|--|----------------------|--|----------------------------------|--------------------------|
| <b>703</b>                             | Plastic Roof Cement  | Consistency: Trowel grade<br>Weight: 9 lbs./gal.<br>Maximum VOC: 300 grams/lt.<br>Packaging: 5 gal. containers               | Black                            | ASTM D 4586-93 Type I    |
| <b>705</b>                             | Cold Method Adhesive | Coverage: 1.5-2 gal./100 sq. ft.<br>Weight: 7.5 lbs./gal.<br>Maximum VOC: 250 grams/lt.<br>Packaging: 5 & 55 gal. containers | Black                            | ASTM D 3019-80 Type III. |
| <b>706</b>                             | Asphalt Primer       | Coverage: .75-1 gal./100 sq. ft.<br>Weight: 7.5 lbs./gal.<br>Maximum VOC: 500 grams/lt.<br>Packaging: 5 & 55 gal. containers | Dark brown when wet; dries black | ASTM D 41-94             |
| <b>707</b><br><b>Low</b><br><b>VOC</b> | Asphalt Primer       | Coverage: .75-1 gal./100 sq. ft.<br>Weight: 8.3 lbs./gal.<br>Maximum VOC: 300 grams/lt.<br>Packaging: 5 & 55 gal. containers | Dark brown when wet; dries black | ASTM D 41-94             |

**Satellite Roof Coatings & Plastic Cements - Continued**

| ITEM       | PRODUCT                           | PRODUCT SPECIFICATIONS  | COLOR                                | COMPLIES WITH                                      |
|------------|-----------------------------------|---|--------------------------------------|--|
| <b>709</b> | Modified Flashing Cement          | Consistency: Trowel Grade<br>Weight: 9.6 lbs./gal.<br>Maximum VOC: N/A<br>Packaging: 5 gal. container | Black                                | ASTM D 4586-93 Type I                              |
| <b>725</b> | Non-Fibered Aluminum Roof Coating | Weight: 8.5 lbs./gal.<br>Maximum VOC: 500 grams/lt.<br>Packaging: 5 & 50 gal. containers              | Silver                               | ASTM D 2824-02 Type I                              |
| <b>726</b> | Aluminum Fibered Roof Coating     | Weight: 11 lbs./gal.<br>Maximum VOC: 500 grams/lt.<br>Packaging: 5 & 50 gal. containers               | Silver                               | ASTM D 2824-02 Type III                            |
| <b>727</b> | Modified Bitumen Adhesive         | Weight: 8.5 lbs./gal.<br>Maximum VOC: 250 grams/lt.<br>Packaging: 5 & 55 gal. containers              | Black                                | ASTM 3019-94 Type III                              |
| <b>729</b> | Aluminum Emulsion                 | Weight: 8.8 lbs./gal.<br>Packaging: 5 & 55 gal. containers  | Dark brown when wet, dries to Silver | ASTM D 1227-95 Type II Class I                     |
| <b>751</b> | Fibered Emulsion                  | Weight: 8.8 lbs./gal.<br>Packaging: 5 & 55 gal. containers  | Dark brown                           | ASTM D 1227-95 Type II Class I                     |
| <b>801</b> | Acrylic Base Coat                 | Weight: 11.5 lbs./gal.<br>Packaging: 5 & 55 gal. containers   | Tinted                               | ASTM D 6083  |
| <b>802</b> | Acrylic Finish Coat               | Weight: 11.5 lbs./gal.<br>Packaging: 5 & 55 gal. containers   | White                                | ASTM D 6083<br>CRRC Rated Product<br>ID# 0850-0005 |