



# Material Safety Data Sheet

Material Name: CERAMIC TILE MORTAR

ID: SAH00383

## \*\*\* Section 1 - Chemical Product and Company Identification \*\*\*

**Material Name:** CERAMIC TILE MORTAR

**Product Use**

Polymer-Modified Mortar

**Manufacturer Information**

USA and Puerto Rico

**MAPEI**

1144 East Newport Center Drive

Deerfield Beach, FL 33442

Phone: 1-954-246-8888

Canada

**MAPEI**

2900 Francis-Hughes Avenue

Laval, QC H7L 3J5

Phone: 1-450-662-1212

IN THE EVENT OF A CHEMICAL EMERGENCY INVOLVING A SPILL, LEAK, FIRE, EXPLOSION, EXPOSURE OR ACCIDENT, CONTACT THE FOLLOWING NUMBERS:

Emergency 24 hour numbers:

(USA) CHEMTREC 1-800-424-9300

(Canada) CANUTEC 1-613-996-6666

## \*\*\* Section 2 - Hazards Identification \*\*\*

**Emergency Overview**

This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication) and the Canadian Workplace Hazardous Materials Information System (WHMIS).

White or gray powder. Cement odor. Causes burns to the skin and eyes when mixed with water.

**Hazard Statements**

DANGER! CORROSIVE. Causes burns to the skin and eyes when mixed with water. Irritating to eyes, respiratory system and skin. May be harmful or fatal if swallowed. Chronic lung disease (silicosis) and/or lung cancer may result from prolonged/repeated breathing of the dust of this material. Wear suitable gloves, eye/face protection, and respiratory protection. Keep out of the reach of children.

**Potential Health Effects: Eyes**

This product is irritating to the eyes. Symptoms can include irritation, redness, scratching of the cornea, and tearing.

**Potential Health Effects: Skin**

This product is irritating to the skin. Mechanical rubbing may increase skin irritation.

**Potential Health Effects: Ingestion**

This product may be harmful if it is swallowed. Ingestion of this product may cause nausea, vomiting and diarrhea.

**Potential Health Effects: Inhalation**

This product is irritating to the respiratory system. Chronic lung disease (silicosis) and/or lung cancer may result from prolonged/repeated breathing of the dust of this material. Inhalation of dusts produced during cutting, grinding or sanding of this product may cause irritation of the respiratory tract.

**Medical Conditions Aggravated by Exposure**

Hypersensitivity to product, allergies, and skin or respiratory disorders

# Material Safety Data Sheet

Material Name: CERAMIC TILE MORTAR

ID: SAH00383

## Potential Environmental Effects

None identified.

**HMIS Ratings:** Health: 2\* Fire: 0 Reactivity: 0 Pers. Prot.: Safety glasses, gloves, dust respirator if airborne concentrations exceed exposure limits

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe \* = Chronic hazard

## \* \* \* Section 3 - Composition / Information on Ingredients \* \* \*

CAS #	Component	Percent
14808-60-7	Silica Sand	40-70
65997-15-1	Portland cement	10-30
7778-18-9	Calcium sulfate	1-5

## \* \* \* Section 4 - First Aid Measures \* \* \*

### First Aid: Eyes

Immediately flush eyes with plenty of water for at least 15 minutes. If irritation persists get medical attention.

### First Aid: Skin

Flush with large amounts of water. If irritation persists, get medical attention.

### First Aid: Ingestion

Flush out mouth with water. If ingestion of a large amount does occur, seek medical attention. Do not induce vomiting.

### First Aid: Inhalation

Immediately remove the affected person to fresh air. If symptoms persist, get medical attention.

### First Aid: Notes to Physician

Provide general supportive measures and treat symptomatically.

## \* \* \* Section 5 - Fire Fighting Measures \* \* \*

### General Fire Hazards

See Section 9 for Flammability Properties.

As with all dry powders, it is advisable to ground mechanical equipment in contact with dry material to dissipate the potential buildup of static electricity.

### Hazardous Combustion Products

Irritating and toxic gases or fumes may be released during a fire. Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

### Extinguishing Media

Dry chemical (preferred), foam, water.

### Unsuitable Extinguishing Media

None identified.

### Specific Hazards Arising From the Chemical

None identified.

### Fire Fighting Equipment/Instructions

Firefighters should wear full protective clothing including self contained breathing apparatus.

**NFPA Ratings:** Health: 2 Fire: 0 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

# Material Safety Data Sheet

Material Name: CERAMIC TILE MORTAR

ID: SAH00383

## \* \* \* Section 6 - Accidental Release Measures \* \* \*

### Personal Precautions

Avoid the generation of dusts during clean-up. Wear appropriate protective equipment and clothing during clean-up.

### Containment Procedures

Contain the discharged material.

### Environmental Precautions

Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulations.

### Clean-Up Procedures

Attempt to reclaim the free product, if this is possible. Shovel the material into waste container. Thoroughly wash the area with water after a spill or leak clean-up. Wear appropriate protective equipment and clothing during clean-up. Keep out of the reach of children.

### Evacuation Procedures

None identified.

### Special Procedures

Wear a dust mask if dust is generated above exposure limits.

## \* \* \* Section 7 - Handling and Storage \* \* \*

### Handling Procedures

Do not breathe dust from this material. Do not get this material in contact with skin or eyes. Wash hands after handling and before eating. Keep out of the reach of children.

### Storage Procedures

Store in a cool, dry, well-ventilated area. Keep the container tightly closed. Do not freeze.

## \* \* \* Section 8 - Exposure Controls / Personal Protection \* \* \*

### A: Component Exposure Limits

#### Silica Sand (14808-60-7)

ACGIH:	0.025 mg/m3 TWA (respirable fraction)
OSHA:	0.1 mg/m3 TWA (respirable dust)
NIOSH:	0.05 mg/m3 TWA (respirable dust)
Alberta:	0.025 mg/m3 TWA (respirable particulate)
British Columbia:	ACGIH Category A2 - Suspected Human Carcinogen; IARC Category 1 - Human Carcinogen 0.025 mg/m3 TWA (respirable)
Manitoba:	0.025 mg/m3 TWA (respirable fraction)
New Brunswick:	0.1 mg/m3 TWA (respirable fraction)
NW Territories:	0.1 mg/m3 TWA (respirable mass); 0.3 mg/m3 TWA (total mass)
Nova Scotia:	0.025 mg/m3 TWA (respirable fraction)
Nunavut:	0.1 mg/m3 TWA (respirable mass); 0.3 mg/m3 TWA (total mass)
Ontario:	0.10 mg/m3 TWA (respirable fraction) 0.10 mg/m3 TWA (designated substance regulation, respirable)
Quebec:	0.1 mg/m3 TWAEV (respirable dust)
Saskatchewan:	0.05 mg/m3 TWA (respirable fraction, listed under Silica - crystalline)
Yukon:	300 particle/mL TWA (listed under Silica)

# Material Safety Data Sheet

Material Name: CERAMIC TILE MORTAR

ID: SAH00383

## Portland cement (65997-15-1)

ACGIH:	1 mg/m3 TWA (particulate matter containing no asbestos and <1% crystalline silica, respirable fraction)
OSHA:	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)
NIOSH:	10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)
Alberta:	10 mg/m3 TWA
British Columbia:	10 mg/m3 TWA (total particulate matter containing no Asbestos and <1% Crystalline silica, total particulate); 3 mg/m3 TWA (particulate matter containing no Asbestos and <1% Crystalline silica, respirable particulate)
Manitoba:	1 mg/m3 TWA (particulate matter containing no Asbestos and <1% Crystalline silica, respirable fraction)
New Brunswick:	10 mg/m3 TWA (particulate matter containing no Asbestos and <1% Crystalline silica)
NW Territories:	5 mg/m3 TWA (respirable mass); 10 mg/m3 TWA (total mass)
Nova Scotia:	1 mg/m3 TWA (respirable fraction, particulate matter containing no Asbestos and <1% Crystalline silica)
Nunavut:	5 mg/m3 TWA (respirable mass); 10 mg/m3 TWA (total mass)
Ontario:	10 mg/m3 TWA (containing no Asbestos and <1% Crystalline silica, total dust)
Quebec:	10 mg/m3 TWAEV (total dust, containing no Asbestos and <1% Crystalline silica); 5 mg/m3 TWAEV (respirable dust, containing no Asbestos and <1% Crystalline silica)
Saskatchewan:	20 mg/m3 STEL 10 mg/m3 TWA
Yukon:	20 mg/m3 STEL 30 mppcf TWA; 10 mg/m3 TWA

## Calcium sulfate (7778-18-9)

ACGIH:	10 mg/m3 TWA (inhalable fraction)
OSHA:	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)
NIOSH:	10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)
Alberta:	10 mg/m3 TWA
British Columbia:	10 mg/m3 TWA (inhalable)
Manitoba:	10 mg/m3 TWA (inhalable fraction)
New Brunswick:	10 mg/m3 TWA (particulate matter containing no Asbestos and <1% Crystalline silica)
Nova Scotia:	10 mg/m3 TWA (inhalable fraction)
Ontario:	10 mg/m3 TWA (inhalable)
Quebec:	10 mg/m3 TWAEV (total dust, containing no Asbestos and <1% Crystalline silica); 5 mg/m3 TWAEV (respirable dust, containing no Asbestos and <1% Crystalline silica)
Saskatchewan:	20 mg/m3 STEL (listed under Gypsum and Plaster of Paris) 10 mg/m3 TWA (listed under Gypsum and Plaster of Paris)

## Engineering Controls

Use general ventilation.

## PERSONAL PROTECTIVE EQUIPMENT

### Personal Protective Equipment: Eyes/Face

Wear safety glasses with side shields.

### Personal Protective Equipment: Skin

The use of nitrile-latex gloves is recommended.

### Personal Protective Equipment: Respiratory

If airborne concentrations are above the applicable exposure limits, use NIOSH approved respiratory protection.

### Personal Protective Equipment: General

Laundry contaminated clothing before reuse. Use good industrial hygiene practices in handling this material.

# Material Safety Data Sheet

Material Name: CERAMIC TILE MORTAR

ID: SAH00383

## \*\*\* Section 9 - Physical & Chemical Properties \*\*\*

<b>Appearance:</b>	White or gray powder	<b>Odor:</b>	Cement odor
<b>Physical State:</b>	Solid	<b>pH:</b>	11.0 - 13.0
<b>Vapor Pressure:</b>	N/A	<b>Vapor Density:</b>	N/A
<b>Boiling Point:</b>	N/A	<b>Melting Point:</b>	N/A
<b>Solubility (H2O):</b>	Dispersible	<b>Specific Gravity:</b>	2.0 - 2.3
<b>Evaporation Rate:</b>	N/A	<b>VOC:</b>	0 g/L
<b>Octanol/H2O Coeff.:</b>	N/A	<b>Flash Point:</b>	N/A
<b>Flash Point Method:</b>	N/A	<b>Upper Flammability Limit (UFL):</b>	N/A
<b>Lower Flammability Limit (LFL):</b>	N/A	<b>Burning Rate:</b>	N/A
<b>Auto Ignition:</b>	N/A		

### Physical Properties: Additional Information

The data provided in this section is to be used for product safety handling purposes. Please refer to Product Data Sheets, Certificates of Conformity or Certificates of Analysis for chemical and physical data for determinations of quality and for formulation purposes.

## \*\*\* Section 10 - Chemical Stability & Reactivity Information \*\*\*

### Chemical Stability

Stable under normal conditions.

### Chemical Stability: Conditions to Avoid

Keep away from heat, ignition sources and incompatible materials.

### Incompatibility

This product may react with strong acids, bases and oxidizing agents.

### Hazardous Decomposition

Irritating and/or toxic fumes and gases may be emitted upon the product's decomposition. Upon decomposition, this product may emit fumes of carbon monoxide, carbon dioxide, oxides of nitrogen, and other organic compounds.

### Possibility of Hazardous Reactions

Will not occur.

## \*\*\* Section 11 - Toxicological Information \*\*\*

### Acute Dose Effects

#### A: General Product Information

No information available for the product.

#### B: Component Analysis - LD50/LC50

##### Silica Sand (14808-60-7)

Oral LD50 Rat 500 mg/kg

##### Calcium sulfate (7778-18-9)

Oral LD50 Rat >3000 mg/kg

# Material Safety Data Sheet

Material Name: CERAMIC TILE MORTAR

ID: SAH00383

## Carcinogenicity

### A: General Product Information

Exposure to quartz (the most stable and common form of crystalline silica) is responsible for the majority of clinically diagnosed silicosis. Silicosis is a fibronodular lung disease that occurs after occupational exposure to crystalline silica for 5 years or longer. Inhalation of quartz dusts may cause shortness of breath, limitation of chest expansion, dry cough, and a lessened capacity for work. Individuals with a pre-existing disease in, or a history of ailments involving the skin or respiratory tract, are at a greater risk of developing adverse health effects when exposed to this material. There may be a relationship between silicosis and certain cancers.

### B: Component Carcinogenicity

#### Silica Sand (14808-60-7)

ACGIH:	A2 - Suspected Human Carcinogen
NIOSH:	potential occupational carcinogen
NTP:	Known Human Carcinogen (respirable size) (Select Carcinogen)
IARC:	Monograph 100C [in preparation] (listed under Crystalline silica inhaled in the form of quartz or cristobalite from occupational sources); Monograph 68 [1997] (Group 1 (carcinogenic to humans))

#### Portland cement (65997-15-1)

ACGIH:	A4 - Not Classifiable as a Human Carcinogen
--------	---

## Sensitization

No information available for the product.

## \*\*\* Section 12 - Ecological Information \*\*\*

## Ecotoxicity

### A: General Product Information

No information available for the product.

### B: Component Analysis - Ecotoxicity - Aquatic Toxicity

#### Calcium sulfate (7778-18-9)

Test & Species		Conditions
96 Hr LC50 Lepomis macrochirus	2980 mg/L [static]	
96 Hr LC50 Pimephales promelas	>1970 mg/L [static]	
120 Hr EC50 Nitscheria linearis	3200 mg/L	

## \*\*\* Section 13 - Disposal Considerations \*\*\*

## US EPA Waste Number & Descriptions

### A: General Product Information

No additional information available.

### B: Component Waste Numbers

No EPA Waste Numbers are applicable for this product's components.

## Disposal Instructions

Waste must be handled in accordance with all federal, state, provincial, and local regulations. Consult authorities before disposal.

See Section 7 for Handling Procedures. See Section 8 for Personal Protective Equipment recommendations.

## \*\*\* Section 14 - Transportation Information \*\*\*

## International Transportation Regulations

Not regulated as dangerous goods.

# Material Safety Data Sheet

Material Name: CERAMIC TILE MORTAR

ID: SAH00383

## \* \* \* Section 15 - Regulatory Information \* \* \*

### US Federal Regulations

#### A: General Product Information

All components are on the U.S. EPA TSCA Inventory List. All components of this product are included, or are exempt from inclusion, in the Canadian Domestic Substance List unless otherwise noted.

#### B: Component Analysis

None of this products components are listed under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), or CERCLA (40 CFR 302.4).

### State Regulations

#### A: General Product Information

Other state regulations may apply. Check individual state requirements.

#### B: Component Analysis - State

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA	RI
Silica Sand	14808-60-7	No	Yes	Yes	Yes	Yes	No
Portland cement	65997-15-1	No	Yes	Yes	Yes	Yes	No
Calcium sulfate	7778-18-9	No	Yes	Yes	Yes	Yes	No

The following statement(s) are provided under the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):  
WARNING! This product contains a chemical known to the state of California to cause cancer.

### Canadian WHMIS Information

#### A: General Product Information



D2A, E,

#### B: Component Analysis - WHMIS IDL

The following components are identified under the Canadian Hazardous Products Act Ingredient Disclosure List:

Component	CAS #	Minimum Concentration
Silica Sand	14808-60-7	1 %

### Additional Regulatory Information

#### A: General Product Information

Supplier(s) of proprietary component(s) state that these components are contained on the TSCA inventory.

#### B: Component Analysis - Inventory

Component	CAS #	TSCA	CAN	EEC
Silica Sand	14808-60-7	Yes	DSL	EINECS
Portland cement	65997-15-1	Yes	DSL	EINECS
Calcium sulfate	7778-18-9	Yes	DSL	EINECS

## \* \* \* Section 16 - Other Information \* \* \*

### Reference

T1-2622-52

# Material Safety Data Sheet

**Material Name:** CERAMIC TILE MORTAR

**ID:** SAH00383

## Other Information

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

## MSDS History

This MSDS has been revised in the following section(s):

Section 2 - Hazards Identification  
Section 3 - Composition / Information on Ingredients  
Section 4 - First Aid Measures  
Section 5 - Fire Fighting Measures  
Section 7 - Handling and Storage  
Section 8 - Exposure Controls / Personal Protection  
Section 15 - Regulatory Information  
Section 16 - Other Information

## Key/Legend

ACGIH = American Conference of Governmental Industrial Hygienists; ADG = Australian Code for the Transport of Dangerous Goods by Road and Rail; ADR/RID = European Agreement of Dangerous Goods by Road/Rail; AS = Standards Australia; BLV=Biological Limit Values; CAN = Canadian DSL and NDSL Inventories status; CAS = Chemical Abstracts Service; CC = Closed Cup; CFR = Code of Federal Regulations; DFG = Deutsche Forschungsgemeinschaft; DOT = Department of Transportation; DSL = Domestic Substances List; EEC = European Economic Community; EINECS = European Inventory of Existing Commercial Chemical Substances; ELINCS = European List of Notified Chemical Substances; EPA = Environmental Protection Agency; EU = European Union; g/L = grams per Liter; HMIS = Hazardous Materials Identification System; IARC = International Agency for Research on Cancer; IMO = International Maritime Organization; IATA = International Air Transport Association; MAK = Maximum Concentration Value in the Workplace; mg/kg = milligrams per kilogram; mg/L = milligrams per Liter; mg/m<sup>3</sup> = milligrams per Cubic Meter; NA, N/A, S.O. = Not available or Not Applicable; NDSL = Non-Domestic Substances List; NFPA = National Fire Protection Association; NIOSH = National Institute for Occupational Safety and Health; NJTSR = New Jersey Trade Secret Registry; NOHSC = National Occupational Health & Safety Commission; NTP = National Toxicology Program; OC = Open Cup; OSHA = Occupational Safety and Health Administration; STEL = Short-term Exposure Limit; TDG = Transportation of Dangerous Goods; TLV = Threshold Limit Value; TSCA = Toxic Substances Control Act; TWA = Time Weighted Average; TWAEV = Time Weighted Average Exposure Value; WHMIS = Workplace Hazardous Materials Information System

**Contact:** Product Safety Representative

**Contact Phone:** 1-954-246-8888

End of Sheet SAH00383