

BUTYL SEAL TAPE

DESCRIPTION

Mule-Hide Butyl Seal Tape is a butyl rubber adhesive tape, which remains flexible even in cold temperatures..

BASIC USES

Butyl Seal Tape may be used on to seal EPDM membranes in certain details. It adheres to plastics, concrete and metals. This product may be used to repair gutters, chimney flashings, and metal roofs on mobile homes and transport vehicles. May be used as a substitute for water Cut-Off Mastic in certain details as noted in the published Mule-Hide details.

PHYSICAL DATA

Solids	100%
Odor	None
Shrinkage	None
Elongation	54%
Chemical Resistance	Excellent to water, ozone and mild alcohol
Bonding Time	Instant tack, full cure in 24 hours
Service Temperature	-40°F to +250°F

COLOR

Gray Butyl Tape.

PACKAGING

Packaged in cartons: 1/8" x 3/4" x 50' (10 per ctn)

APPLICATION

Surface must be clean, dry, and free of oil, grease and dust. Position the Tape over the area to be covered. Peel off the release paper from the Butyl Seal Tape. Without stretching the tape, apply over the prepared surface area. Allow tape to lay naturally. **DO NOT STRETCH TAPE.** Press firmly over cracks and uneven surfaces.

TECHNICAL SERVICE

Contact Mule-Hide Products Company at 800/786-1492 for technical service information.

HEALTH AND SAFETY PRECAUTIONS

None known at this time.

PRIOR TO USE OF THIS MATERIAL, READ ALL APPROPRIATE MATERIAL SAFETY DATA SHEETS AND WARNINGS.

DISCLAIMER

The statements provided concerning the material shown are intended as a guide for material usage and are believed to be true and accurate. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. Since the manner of use is beyond our control, Mule-Hide does not make nor does it authorize anyone to make any warranty of merchantability or fitness for any purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material except that it conforms to Mule-Hide's physical properties. Buyer and user accept the product under these conditions and assume the risk of any failure, any injury of person or property (including that of the user), loss or liability resulting from the handling, storage or use of the product whether or not it is handled, stored or used in accordance with the directions or specifications. Mule-Hide must be notified in writing of any claims and be given the opportunity to inspect the complaint or failure before repairs are made.