



**MH PROJECT#** \_\_\_\_\_

# MULE-HIDE PRODUCTS CO.,INC.

EFFECTIVE  
FEB 2002

P.O. Box 1057 Beloit, WI 53512-1057 Phone: 608/365-3111 Fax: 608/365-7852 www.mulehide.com

## COATINGS WARRANTY APPLICATION

**PROJECT NAME:**

Building Name \_\_\_\_\_  
 Street \_\_\_\_\_  
 City \_\_\_\_\_ State \_\_\_\_\_ Zip \_\_\_\_\_  
 Architect/Consultant \_\_\_\_\_  
 Phone \_\_\_\_\_

**BUILDING OWNER:**

Name \_\_\_\_\_  
 Street \_\_\_\_\_  
 City \_\_\_\_\_ State \_\_\_\_\_ Zip \_\_\_\_\_  
 Contact Name \_\_\_\_\_  
 Phone \_\_\_\_\_

**CONTRACTOR NAME:**

Name \_\_\_\_\_  
 Street \_\_\_\_\_  
 City \_\_\_\_\_ State \_\_\_\_\_ Zip \_\_\_\_\_  
 Phone \_\_\_\_\_ Fax \_\_\_\_\_  
 Mule-Hide Applicator Number \_\_\_\_\_  
 Person filling out application \_\_\_\_\_

**DISTRIBUTOR INFORMATION:**

Distributor Name \_\_\_\_\_  
 City \_\_\_\_\_ State \_\_\_\_\_  
 Salesman \_\_\_\_\_

**IF SPECIFICATIONS WERE WRITTEN FOR THIS PROJECT, PLEASE SUBMIT ONE COPY WITH THE APPLICATION**

**NOTE: THESE PRODUCTS ARE NOT INTENDED TO BE USED OVER GRAVELED SUBSTRATES**

**FOR ELASTOMERIC ACRYLIC (A-SERIES)** Application:  Spray  Roller

Type of Existing Substrate:  Aged Smooth BUR (over 5 yrs old)  Aged Hypalon (over 5 yrs old)  EPDM

Metal  New PUF  Smooth Mod Bit  Granulated Mod Bit  New Smooth BUR (less than 5 yrs old)

Granulated Mineral Surface & Mineral Surface Cap Sheets  Skylights  Masonry Walls

**THIS BUILDING IS**  Commercial  Industrial  Institutional  Residential (Material Warranties Only)

**BUILDING USE** \_\_\_\_\_ **BUILDING HEIGHT** \_\_\_\_\_ ft. **NUMBER OF LEVELS** \_\_\_\_\_

**SLOPE** \_\_\_\_\_ Inch per ft.  New Roof  Re-roof **SIZE OF COATED AREA** \_\_\_\_\_ Square ft.

**PROJECT START DATE** \_\_\_\_\_ **PROJECTED OR ACTUAL COMPLETION DATE** \_\_\_\_\_

WARRANTY FEE INFORMATION	TYPE	PRICE/S.F.	SIZE(S.F.)	COST
Material Only *	5 Years	N/A	_____ =	NO CHARGE
System Warranty* (Metal Roof Only)	5 Years	\$.04	_____ = \$ _____ (MIN \$300.00)	
Material Only **	10 Years	N/A	_____ =	NO CHARGE
System Warranty** (Metal Roof Only)	10 Years	\$.07	_____ = \$ _____ (MIN \$500.00)	

\* Elastomeric Acrylic Application must be applied at a minimum of 2 gallons per square  
 \*\*Elastomeric Acrylic Application must be applied at a minimum of 3 gallons per square (2 coat minimum)  
**SEE PRODUCT CHART ON THE BACK OF THIS FORM FOR FURTHER DETAILS ON THE APPLICATION OF COATINGS**



# INSTALLATION

TOTAL INSTALLATION COST: \_\_\_\_\_

Materials Used: Primer \_\_\_\_\_gallons

Flashing Grade \_\_\_\_\_gallons

Finish Coat \_\_\_\_\_gallons

***MULE-HIDE REQUIRES THAT ALL MATERIAL INVOICES BE SENT WITH THIS APPLICATION***

LIST DEVIATIONS TO PUBLISHED SPECIFICATIONS OR CONDITIONS REQUIRING SPECIAL CONSIDERATION \_\_\_\_\_

\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

Warranty applications must be sent in for approval before the start of the project. Requests for final inspection must be received within 30 days of roof completion. Warranties must be executed within 90 days of roof completion. Any warranty issued by Mule-Hide Products Co., Inc. will be based upon the accuracy and completeness of the information contained in this warranty application, roof drawing and pre-job survey.

**ELIGIBLE CONTRACTOR SIGNATURE (MUST BE AN OFFICER OF THE COMPANY)**

By \_\_\_\_\_ Title \_\_\_\_\_ Date \_\_\_\_\_

***MULE-HIDE WARRANTY DEPARTMENT USE ONLY***

REVIEWED BY \_\_\_\_\_ ACCEPTED  CHANGES  REJECTED

CONTACTED CONTRACTOR  Yes  No NAME OF CONTACT \_\_\_\_\_

NOTES \_\_\_\_\_

\_\_\_\_\_



# PRODUCT APPLICATION CHART

## Finish Coating Products:

A-300 = FINISH (Standard)  
 A-320 = FINISH (over asphaltic substrates)  
 A-350 = FINISH (over ponded water areas)  
 A-301 = SKYLIGHT FINISH  
 A-400 = MASONRY WALL COATING

## Companion Products:

115 = CLEANER  
 A-125 = METAL ROOF PRIMER  
 A-200 = FLASHING GRADE  
 A-151 = EPDM ReSurface Agent™

## Specialty Products:

LIQUI-THIX® - turns A-300 into A-200  
 FAST-CAPST™ - stop metal roof fastener leaks  
 SEAL FAST™ TAPE - stops leaks, compatible with coatings  
 A-300-FF - FAST FILM FINISH when rainfall is expected\*  
 \*Applied by Airless Sprayer Only

**IMPORTANT NOTICE FOR ALL SYSTEMS:** An ADHESION TEST should first be performed to ensure compatibility between the coating and substrate. Mule-Hide also recommends a two (2) coat application. If required finished coverage rates exceed 2 gals. Per 100 sq. ft, 2 coats are required.  
**(SEE NOTES BELOW)**

Existing Substrate	Finish Coating	Finished Coverage Rate	Warranties Available	Companion Products	Important Remarks	
Metal	A-300	2 gal / square 3 gal / square	5 yr L & M** or Lmtd Mat 10 yr Labor & Material**	115, A-125, A-200	5 yr L&M Warranty Fee - 4 cents per sq ft. 10 yr L&M Warranty Fee - 7 cents per sq ft.	
**Must be applied by a Mule-Hide Warranty-Eligible Coatings Contractor						
Aged Smooth BUR (over 5 yrs old)		2 gal / square 3 gal / square	5 yr Limited Material 10 yr Limited Material	A-200 See Notes	Blisters, holes, splits or tears, and other damaged areas should be repaired before coating.	
New PUF		3 gal / square	10 yr Limited Material	A-200	Positive Slope Required.	
Aged Hypalon Sheet (over 5 yrs old)		2 gal / square 3 gal / square	5 yr Limited Material 10 yr Limited Material	115, A-200	Repair using Hypalon compatible products before coating.	
EPDM		2 gal / square 3 gal / square	5 yr Limited Material 10 yr Limited Material	A-151 See Notes	Repair using EPDM compatible products before coating.	
New Smooth BUR (less than 5 yrs old)	A-320	2 gal / square 3 gal / square	5 yr Limited Material 10 yr Limited Material	A-200 See Notes	Blisters, holes, splits or tears, and other damaged areas should be repaired before coating.	
Smooth Mod Bit		2 gal / square 3 gal / square	5 yr Limited Material 10 yr Limited Material	A-200 See Notes	Blisters, holes, splits or tears, and other damaged areas should be repaired before coating.	
Granulated Mod Bit & Mineral Surface Cap Sheets		3 gal / square 4 gal / square	5 yr Limited Material 10 yr Limited Material	A-200 See Notes	Blisters, holes, splits or tears, and other damaged areas should be repaired before coating.	
Skylights	A-301	2 gal / square	5 yr Limited Material	A-200	Refer to Mule-Hide's Product Data Sheet.	
Masonry Walls	A-400-W	2 gal / square	5 yr Limited Material	115, A-200	Refer to Mule-Hide's Product Data Sheet.	

\*\*Must be applied by a Mule-Hide Warranty-Eligible Coatings Contractor

### IMPORTANT NOTES (Details and information subject to change):

When applying coating over an existing roofing system under warranty, the building owner should check with existing roofing system manufacturer, as this coating application may void warranty. Roofing system must be sound and A-350 must be used on areas where ponded water occurs. This information herein should not be considered all-inclusive and should always be accompanied by good application practices. Mule-Hide is NOT responsible for any defects in the existing roofing system. The applicator has sole responsibility for the quality of application of the coating system. Mule-Hide requires proper surface preparation of the existing roofing system. To repair blisters, splits, and other roof surface defects, Mule-Hide recommends that they be repaired in accordance with the published NRCA Repair Manual for Low-Slope Roofing System guidelines prior to application of Mule-Hide Elastomeric Coatings.

Cool temperatures and high humidity retard curing. Do not apply Elastomeric Acrylic Coatings if weather conditions will not permit complete cure. Mule-Hide Coatings are NOT intended for use over graveled surfaces (Spurred Roofs are also NOT acceptable.) Refer to Mule-Hide Coatings Specification Manual for details prior to application. For winter applications and for application over certain existing roof systems, contact Mule-Hide for specific product recommendations. Mule-Hide recommends ADHESION TESTS PRIOR TO COATING to ensure compatibility between the coating and the substrate. Mule-Hide also RECOMMENDS a two (2)-coat application. If finished coverage rates exceed two (2) gallons per square, 2 coats are REQUIRED. Product blisters may occur if coatings are applied too thick in high temperatures. The information herein is based upon data and knowledge considered to be true and accurate and is provided for the applicator's consideration, investigation, and verification. However, Mule-Hide Products Co., Inc., does not warrant any results to be obtained. Statements concerning possible use of Mule-Hide products are made without knowledge of your particular roof and/or coatings project and such an application may not be fit for your particular purpose. MULE-HIDE DISCLAIMS ALL WARRANTIES, INCLUDING THE IMPLIED WARRANTY OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, except written warranties attached to Mule-Hide products and written warranties signed by an officer of Mule-Hide.