



**NEW!**

**New from Plastic Components** GRAY or TAN foundation sill screeds and casing beads for stone veneer applications. All are available in 10 ft. (3 m) lengths and conform to ASTM standards D1784, C1063 and D4216.

Eliminate painting. And look great with a rustproof job that saves time and money!

**Termination Bead**

Colored termination beads provides a finished edge between stone veneer and other materials such as vinyl or cementitious siding, stucco, etc.

Add suffix "WP" to order with weep holes.  
Example: 1050TANWP

Product Number	Description Colored Termination Bead	Ground	Pieces in Box
1050	<div style="border: 1px solid black; width: 40px; height: 20px; margin: 0 auto; text-align: center; line-height: 20px;">White</div> with 1-1/4" (32 mm) perforated flange	1/2" (13 mm)	75
1058		5/8" (16 mm)	75
1075		3/4" (19 mm)	75
1078		7/8" (22 mm)	50
1100		1" (25 mm)	50
1050TAN	<div style="border: 1px solid black; width: 40px; height: 20px; margin: 0 auto; text-align: center; line-height: 20px;">Tan</div> with 1-1/4" (32 mm) perforated flange	1/2" (13 mm)	75
1058TAN		5/8" (16 mm)	75
1075TAN		3/4" (19 mm)	75
1078TAN		7/8" (22 mm)	50
1100TAN		1" (25 mm)	50
1050GRAY	<div style="border: 1px solid black; width: 40px; height: 20px; margin: 0 auto; text-align: center; line-height: 20px;">Gray</div> with 1-1/4" (32 mm) perforated flange	1/2" (13 mm)	75
1058GRAY		5/8" (16 mm)	75
1075GRAY		3/4" (19 mm)	75
1078GRAY		7/8" (22 mm)	50
1100GRAY		1" (25 mm)	50

**Foundation Weep Screens**

Install our foundation weep screens at the plate line or stem wall. They provide a stop for stone veneer and allow moisture to migrate down and away from the wall.

Product Number	Description FHA Weep Screens	Ground	Pieces in Box
632-50	<div style="border: 1px solid black; width: 40px; height: 20px; margin: 0 auto; text-align: center; line-height: 20px;">White</div> weep screen with 3-1/2" (89 mm) flange for framing applications	1/2" (13 mm)	35
632-58		5/8" (16 mm)	35
632-75		3/4" (19 mm)	35
632-78		7/8" (22 mm)	35
632-100		1" (25 mm)	25
632-50TAN	<div style="border: 1px solid black; width: 40px; height: 20px; margin: 0 auto; text-align: center; line-height: 20px;">Tan</div> weep screen with 3-1/2" (89 mm) flange for framing applications	1/2" (13 mm)	35
632-58TAN		5/8" (16 mm)	35
632-75TAN		3/4" (19 mm)	35
632-78TAN		7/8" (22 mm)	35
632-100TAN		1" (25 mm)	25
632-50GRAY	<div style="border: 1px solid black; width: 40px; height: 20px; margin: 0 auto; text-align: center; line-height: 20px;">Gray</div> weep screen with 3-1/2" (89 mm) flange for framing applications	1/2" (13 mm)	35
632-58GRAY		5/8" (16 mm)	35
632-75GRAY		3/4" (19 mm)	35
632-78GRAY		7/8" (22 mm)	35
632-100GRAY		1" (25 mm)	25

**Foundation Sill Screens**

This series of screeds is designed to carry moisture away from a stucco-finished stem wall or foundation wall.

Use it at the plate line or stem wall to give your building the moisture protection it needs.

Product Number	Description Foundation Sill Screenshot	Ground	Pieces in Box
632-75-50	<div style="border: 1px solid black; width: 40px; height: 20px; margin: 0 auto; text-align: center; line-height: 20px;">White</div> 3/4" (19 mm) sill screed with flange. Framing applications.	1/2" (13 mm)	30
632-75-50TAN	<div style="border: 1px solid black; width: 40px; height: 20px; margin: 0 auto; text-align: center; line-height: 20px;">Tan</div> 3/4" (19 mm) sill screed with flange. Framing applications.	1/2" (13 mm)	30
632-75-50GRAY	<div style="border: 1px solid black; width: 40px; height: 20px; margin: 0 auto; text-align: center; line-height: 20px;">Gray</div> 3/4" (19 mm) sill screed with flange. Framing applications.	1/2" (13 mm)	30

**Note** Caulk all butt joints, ends, angles, corners and intersections at time of installation.

*More on back*

Warnock Hersey  
**PC**  
LISTED PRODUCT

# Color Trims for Stone Veneer Applications

## Over Window/Door Drip Edge

Our drip edge is the PVC trim to choose for extreme moisture conditions. Designed for use over window/door openings, it has a 3-1/2" (89 mm) back flange and sloped front edge that move moisture out and away from the wall assembly.

Product Number	Description Drip Edge	Ground	Pieces in Box
SB-EMT75	White	3/4" (19 mm)	30
SB-EMT1	STARTER TRAC™	1" (25 mm)	30
SB-EMT15	with 3" (76 mm)	1-1/2" (38 mm)	30
SB-EMT2	back flange	2" (51 mm)	30
SB-EMT75TAN	Tan	3/4" (19 mm)	30
SB-EMT11TAN	STARTER TRAC™	1" (25 mm)	30
SB-EMT15TAN	with 3" (76 mm)	1-1/2" (38 mm)	30
SB-EMT2TAN	back flange	2" (51 mm)	30
SB-EMT75GRAY	Gray	3/4" (19 mm)	30
SB-EMT1GRAY	STARTER TRAC™	1" (25 mm)	30
SB-EMT15GRAY	with 3" (76 mm)	1-1/2" (38 mm)	30
SB-EMT2GRAY	back flange	2" (51 mm)	30



## Z Flashing

For use at the floor line with plywood or other sheathing products, Plastic Components' "Z" Flashing is suitable for joints such as floor line, gable and other applications.

- Non-rusting
- Pre-drilled nail holes

Product Number	Description	Board Size	Pieces in Box
SBZ-50	White	1/2" (13 mm)	30
SBZ-58	"Z" Flashing	5/8" (16 mm)	30
SBZ-75	with 1/2" (13 mm)	3/4" (19 mm)	30
SBZ-78	drip edge	7/8" (22 mm)	30
SBZ-50TAN	Tan	1/2" (13 mm)	30
SBZ-58TAN	"Z" Flashing	5/8" (16 mm)	30
SBZ-75TAN	with 1/2" (13 mm)	3/4" (19 mm)	30
SBZ-78TAN	drip edge	7/8" (22 mm)	30
SBZ-50GRAY	Gray	1/2" (13 mm)	30
SBZ-58GRAY	"Z" Flashing	5/8" (16 mm)	30
SBZ-75GRAY	with 1/2" (13 mm)	3/4" (19 mm)	30
SBZ-78GRAY	drip edge	7/8" (22 mm)	30

## Ultra-Lath® Plastic Lath

For exterior or interior vertical applications over code-approved substrates (non-rated assemblies).

- Non-rusting
- Self-furred for exceptional keying
- Impervious to sand and the harsh chemicals found in portland cement-based stucco

Product Number	Description Ultra-Lath® plastic lath	Packaging	Qty per Pallet
PDM2796	Sheets 27" x 96" (686 mm x 2.4 m)	10 sheets (180 sq. ft.) per bundle	25 bundles (4,500 sq. ft.) per pallet
PDMR	Rolls 27" x 100' roll (686 mm x 30.5 m)	225 sq. ft. per roll	18 rolls per pallet



**Note** Caulk all butt joints, ends, angles, corners and intersections at time of installation.