



GENERAL CONSTRUCTION



General Construction

Sinker

For construction, carpentry and framing. Checkered countersunk head designed to sink flush with surface. Vinyl-coated smooth shank for easier nailing and firmer holding power. Made to conform to ASTM F1667

Sinker		Coated Smooth Shank			
Size	Gauge	Head Size	Approx. Count Per Pound	SKU	
1-1/8"	3D	15-1/2	11/64"	923	3CTDSKR
1-3/8"	4D	14	13/64"	527	4CTDSKR
1-5/8"	5D	13-1/2	7/32"	387	5CTDSKR
1-7/8"	6D	13	15/64"	293	6CTDSKR
2-1/8"	7D	12-1/2	1/4"	223	7CTDSKR
2-3/8"	8D	11-1/2	17/64"	153	8CTDSKR
2-7/8"	10D	11	9/32"	111	10CTDSKR
3-1/8"	12D	10	5/6"	81	12CTDSKR
3-1/4"	16D	9	11/32"	64	16CTDSKR
3-3/4"	20D	7	3/8"	40	20CTDSKR
4-1/4"	30D	6	13/32"	30	30CTDSKR
4-3/4"	40D	5	7/16"	23	40CTDSKR
5-3/4"	60D	3	1/2"	14	60CTDSKR

Cooler Nail

Used for general construction and framing. Similar to coated sinker, but with smooth flat head instead of checkered countersunk. Made to conform to ASTM F1667

Cooler Nail		Vinyl Coated Smooth Shank			
Size	Gauge	Head Size	Approx. Count Per Pound	SKU	
1-3/8"	4D	14	7/32"	493	4COOL
1-7/8"	6D	13	1/4"	278	6COOL
2-1/2"	7D	12-1/2	17/64"	212	7COOL
2-3/8"	8D	11-1/2	9/32"	144	8COOL
2-7/8"	10D	11	19/64"	105	10COOL
3-1/8"	12D	11	19/64"	83	12COOL
3-1/4"	16D	9	3/8"	69	16COOL

Polebarn Nail

For load-bearing wooden structures where superior holding power is necessary. Nails are made of higher carbon steel for greater stiffness.

Polebarn Nail		Bright Stiff Stock Ring Shank			
Size	Gauge	Head Size	Approx. Count Per Pound	SKU	
2"	6D	11	9/32"	149	6RSPO
2-1/2"	8D	9	5/16"	78	8RSPO
3"	10D	9	5/16"	66	10RSPO
3-1/4"	12D	9	5/16"	61	12RSPO
3-1/2"	16D	9	5/16"	57	16RSPO
4"	20D	7	3/8"	35	20RSPO
4-1/2"	30D	7	3/8"	31	30RSPO
5"	40D	7	3/8"	28	40RSPO
5-1/2"	50D	7	3/8"	26	50RSPO
6"	60D	5	7/16"	17	60RSPO
7"	70D	5	7/16"	15	70RSPO
8"	80D	5	7/16"	13	80RSPO
10"	100D	5	7/16"	12	100RSPO

Polebarn Nail Tempered Hardened Steel Ring Shank

Size	Gauge	Head Size	Approx. Count Per Pound	SKU	
2-1/2"	8D	9	5/16"	78	8TRSPO
3"	10D	9	5/16"	66	10TRSPO
3-1/4"	12D	9	5/16"	61	12TRSPO
3-1/2"	16D	9	5/16"	57	16TRSPO
4"	20D	7	3/8"	35	20TRSPO
4-1/2"	30D	7	3/8"	31	30TRSPO
5"	40D	7	3/8"	28	40TRSPO
5-1/2"	50D	7	3/8"	26	50TRSPO
6"	60D	5	7/16"	17	60TRSPO
7"	70D	5	7/16"	15	70TRSPO
8"	80D	5	7/16"	13	80TRSPO

Fence Staple

Generally used for attaching woven wire fence, welded fence, or barbed wire to wooden fence posts. Made to conform to ASTM F1667

Fence Staple		Bright Barbed		
Size	Gauge	Head Size	Approx. Count Per Pound	SKU
1"	9	1/4"	106	1FS
1-1/8"	9	1/4"	97	118FS
1-1/4"	9	1/4"	87	114FS
1-1/2"	9	1/4"	72	112FS
1-3/4"	9	1/4"	61	134FS
2"	9	1/4"	53	2FS

Fence Staple		Cement Coated Barbed		
Size	Gauge	Head Size	Approx. Count Per Pound	SKU
1"	9	1/4"	106	1CTDFS
1-1/8"	9	1/4"	97	118CTDFS
1-1/4"	9	1/4"	87	114CTDFS
1-1/2"	9	1/4"	72	112CTDFS
1 3/4"	9	1/4"	61	134CTDFS

Joist Hanger Nail

For attaching joist hangers to wood studs. Short, heavy gauge nail provides increased holding power without fully penetrating wood.

Joist Hanger Nail		Bright Smooth Shank		
Size	Gauge	Head Size	Approx. Count Per Pound	SKU
1-1/4"	9	9/32"	149	114JST
1-1/2"	9	9/32"	125	112JST
1-3/4"	9	5/16"	65	134JST
2-1/2"	8	5/16"	62	212JST
1-1/4"	10-1/4	9/32"	194	114JST10
1-1/2"	10-1/4	9/32"	165	112JST10
1-1/4"	11	9/32"	240	114JST11
1-1/2"	11	9/32"	200	112JST11

Joist Hanger Nail		Bright Ring Shank		
Size	Gauge	Head Size	Approx. Count Per Pound	SKU
1-1/2"	9	9/32"	125	112ATJST
1-3/4"	9	5/16"	62	134ATJST
2-1/2"	0.250"	1/2"	27	212ATJST

Truss Nail

For attaching truss plates. As multiple nails are commonly used with truss plates, truss nails are thinner than joist hanger nails to minimize splitting of the wood trusses.

Truss Nail		Coated Smooth Shank		
Size	Gauge	Head Size	Approx. Count Per Pound	SKU
1-1/4"	11	5/16"	223	114CTDTS
1-3/8"	11	5/16"	181	138CTDTS
1-1/2"	11	5/16"	168	112CTDTS

Truss Nail		Coated Ring Shank		
Size	Gauge	Head Size	Approx. Count Per Pound	SKU
1-1/2"	11	5/16"	128	112CTDRSTS