



MATERIAL SAFETY DATA SHEET

Sikaflex® 2C, NS & SL - Part B

HMIS

| | |
|---------------------|----|
| HEALTH | *2 |
| FLAMMABILITY | 2 |
| REACTIVITY | 0 |
| PERSONAL PROTECTION | C |

1. Product And Company Identification

| | |
|--|--|
| Supplier Sika Corporation 201 Polito Ave Lyndhurst, NJ 07071 Company Contact: EHS Department Telephone Number: 201-933-8800 FAX Number: 201-933-9379 Web Site: www.sikausa.com | Manufacturer Sika Corporation 201 Polito Ave Lyndhurst, NJ 07071 Company Contact: EHS Department Telephone Number: 201-933-8800 FAX Number: 201-933-9379 Web Site: www.sikausa.com |
| Supplier Emergency Contacts & Phone Number CHEMTREC: 800-424-9300 INTERNATIONAL: 703-527-3887 | Manufacturer Emergency Contacts & Phone Number CHEMTREC: 800-424-9300 INTERNATIONAL: 703-527-3887 |

Issue Date: 08/11/2006
Product Name: Sikaflex® 2C, NS & SL - Part B
CAS Number: Not Established
Chemical Family: Polyurethane
MSDS Number: 3966
Product Code: 0464140

2. Composition/Information On Ingredients

| Ingredient Name | CAS Number | Percent Of Total Weight |
|---------------------------|------------|-------------------------|
| POLYISOCYANATE PREPOLYMER | mixture | |
| XYLENE (MIXED ISOMERS) | 1330-20-7 | 5 - 10 |

3. Hazards Identification

Eye Hazards
 Causes eye irritation.

Skin Hazards
 May cause skin irritation. Prolonged and/or repeated skin contact may cause an allergic reaction/sensitization.

Ingestion Hazards
 May be harmful if swallowed.

Inhalation Hazards
 May cause nose, throat, and lung irritation. May cause respiratory tract irritation. May cause an allergic respiratory reaction / sensitization after prolonged or repeated contact. Reports have associated repeated and prolonged

MATERIAL SAFETY DATA SHEET

Sikaflex® 2C, NS & SL - Part B

3. Hazards Identification - Continued

Inhalation Hazards - Continued

exposure to some of the chemicals in this product with permanent brain, liver, kidney, and Central Nervous System damage. Headaches and dizziness may result.

4. First Aid Measures

Eye

In case of contact, hold eyelids apart and immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.

Skin

In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately if irritation (redness, rash, blistering) develops and persists.

Ingestion

If victim is fully conscious, give one or two cups of water or milk to drink. Never give anything by mouth to an unconscious victim. Call a physician or a poison control center immediately.

Inhalation

Remove to fresh air. If not breathing, give artificial respiration, seek medical attention.

5. Fire Fighting Measures

Flash Point: 112 °F

Autoignition Point: N/AV °F

Lower Explosive Limit: N/AV

Upper Explosive Limit: N/AV

Fire And Explosion Hazards

Combustible liquid. During a fire, irritating and/or toxic gases and aerosols from the decomposition/combustion products may be present.

Extinguishing Media

In case of fire, use water spray (fog) foam, dry chemical, or CO₂.

Fire Fighting Instructions

In the event of a fire, firefighters should wear full protective clothing and NIOSH-approved self-contained breathing apparatus with a full facepiece operated in the pressure demand or other positive pressure mode.

6. Accidental Release Measures

Eliminate all ignition sources. Use appropriate Personal Protective Equipment (PPE). Absorb and/or contain spill with inert materials (e.g. sand, vermiculite) and then place in appropriate container. For large spills, use water spray to disperse vapors. Prevent runoff from entering waterways or sewers.

7. Handling And Storage

Handling And Storage Precautions

Keep out of reach of children. Not for internal consumption.

Handling Precautions

Keep away from heat, sparks, flame, and other sources of ignition (i.e., pilot lights, electric motors, and static electricity).

Storage Precautions

Store at 32F min. - 122F max. Ideal storage temperature 50-80F. If closed container is exposed to heat, pressure can build up. If moisture enters container, pressure may build up due to reaction. Store in cool, dry area in tightly closed containers, away from sparks and open flames.

MATERIAL SAFETY DATA SHEET

Sikaflex® 2C, NS & SL - Part B

7. Handling And Storage - Continued

Work/Hygienic Practices

Wash thoroughly with soap and water after handling.

8. Exposure Controls/Personal Protection

Engineering Controls

Use of a system of local and/or general exhaust is recommended to keep employee below applicable exposure limits. Refer to the current edition of "Industrial Ventilation: A Manual of Recommended Practice" published by the American Conference of Governmental Industrial Hygienists for information on the design, installation, use, and maintenance of exhaust systems.

Eye/Face Protection

Faceshield over safety glasses or goggles.

Skin Protection

Chemical-resistant gloves. Lab coat or other work clothing to prevent skin exposure. Launder before reuse.

Respiratory Protection

A respirator protection program that meets 29 CFR 1910.134 requirement must be followed whenever workplace conditions warrant a respirator's use. In areas where the Permissible Exposure Limits are exceeded, use a properly fitted NIOSH-approved respirator.

Other/General Protection

Wash thoroughly after handling.

Ingredient(s) - Exposure Limits

XYLENE (MIXED ISOMERS)
ACGIH TLV-STEL 150 ppm
ACGIH TLV-TWA 100 ppm
OSHA PEL-TWA 100 ppm

9. Physical And Chemical Properties

Appearance

Clear liquid

Odor

Aromatic Odor

Chemical Type: Mixture

Physical State: Liquid

Specific Gravity: 1.02

Percent Volatiles: 9.0

Packing Density: 8.5 pounds/gallon

Vapor Density: > AIR

Evaporation Rate: Slower than ether

VOC content: Part B: 92 g/l

For VOC Content of the A & B component mixed, please see the appropriate Part A MSDS.

10. Stability And Reactivity

Stability: Stable

Hazardous Polymerization: Will not occur

Conditions To Avoid (Stability)

Open flame, heat

MATERIAL SAFETY DATA SHEET

Sikaflex® 2C, NS & SL - Part B

10. Stability And Reactivity - Continued

Incompatible Materials

Water, Alcohols and Amines

Hazardous Decomposition Products

CO, CO₂, Oxides of Nitrogen

11. Toxicological Information

No Data Available...

12. Ecological Information

No Data Available...

13. Disposal Considerations

Dispose in accordance with applicable federal, state and local government regulations. Waste generators must determine whether a discarded material is classified as a hazardous waste. USEPA guidelines for the classification determination are listed in 40 CFR Parts 261.3. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.

14. Transport Information

Proper Shipping Name

Ground Transport - Not Regulated by the USDOT (per 49 CFR 173.150(f))
Air, Boat Transport - Flammable Liquids, N.O.S, (Xylene), 3, UN1993, PG III

Additional Shipping Paper Description

Note: This product is packaged for ground transport only.

15. Regulatory Information

U.S. Regulatory Information

All ingredients of this product are listed or are excluded from listing under the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

SARA Hazard Classes

Acute Health Hazard
Chronic Health Hazard
Fire Hazard

SARA Title III - Section 313 Supplier Notification

This product contains the following toxic chemicals that are subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act (EPCRA) of 1986 and of 40 CFR 372.

XYLENE (MIXED ISOMERS) (1330-20-7) 5 - 10 %

This information must be included on all MSDSs that are copied and distributed for this material.

Ingredient(s) - U.S. Regulatory Information

XYLENE (MIXED ISOMERS)
SARA Title III - Section 313 Form "R"/TRI Reportable Chemical
SARA - Acute Health Hazard
SARA - Chronic Health Hazard
SARA - Fire Hazard

Ingredient(s) - State Regulations

XYLENE (MIXED ISOMERS)
New Jersey - Workplace Hazard

MATERIAL SAFETY DATA SHEET

Sikaflex® 2C, NS & SL - Part B

15. Regulatory Information - Continued

Ingredient(s) - State Regulations - Continued

New Jersey - Environmental Hazard
New Jersey - Special Hazard
Pennsylvania - Workplace Hazard
Pennsylvania - Environmental Hazard
Massachusetts - Hazardous Substance
New York City - Hazardous Substance

16. Other Information

HMIS Rating

Health: *2

Fire: 2

Reactivity: 0

PPE: C

Revision/Preparer Information

MSDS Preparer: EHS Department

This MSDS Supercedes A Previous MSDS Dated: 07/21/2006

Disclaimer

The information contained in this Material Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Technical Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this MSDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikacorp.com or 201-933-8800.

SIKA CORPORATION

Printed Using MSDS Generator™ 2000