



The Chemical Company

PRODUCT DATA

7 07 92 00 **Joint Sealants**

SONOLAC®

General-purpose siliconized acrylic latex caulk

Description

Sonolac® is a siliconized acrylic-latex gun-grade caulk for use in general-purpose exterior and interior applications. Its performance characteristics exceed those of oil-based caulks and most butyl caulks.

Yield

Approximate yield for 1/4 by 1/4" (6 by 6 mm) joints:

24.4 lineal ft (7.4 m) per cartridge

308 lineal ft per gallon (25 m/L)

Packaging

300 ml (10.1 oz) cartridges, 12 cartridges per case

5 gallon pails (18.93 L) for professional use; weight is approximately 65 lbs (29.5 kg) each.

Color

White available in 300 mL cartridges and 5 gallon pails.

Custom colors also available by special order in minimum order quantities of 44 cases or 50 pails of 5 gallons each. Allow 6 – 8 weeks lead time for special orders.

Features

- Siliconized
- One component
- Nonstaining, nonbleeding
- Dry on surface within 30 minutes
- Water based
- Lasting flexibility

Benefits

- Provides optimum adhesion
- Easy to apply; saves labor
- Maintains original appearance
- Readily paintable; speeds jobsite production
- Easy to clean up with water
- Provides a durable seal

Shelf Life

2 years when properly stored

Storage

Store in unopened containers in a cool, dry area out of direct sunlight. Elevated temperature will affect shelf life. Keep material from freezing in the container; do not store below 35° F (2° C).

Where to Use

APPLICATION

- Filling joints between walls and woodwork
- Patching wall cracks
- Sealing joints and openings at counter tops, vanities, venting, plumbing, or other fixtures

LOCATION

- Interior and exterior
- Above grade

How to Apply

Joint Preparation

1. In deep joints, control the sealant depth with Closed-Cell Backer-Rod or Soft Backer-Rod (see Form No. 1026342). Where the depth of the joint does not permit the use of backer-rods, use a bondbreaker (polyethylene strip) to prevent three-sided adhesion.
2. Minimum joint size should be 1/4 by 1/4" (6 by 6 mm). Maximum joint size should be 1" (25 mm) wide by 1/2" (13 mm) deep.

Surface Preparation

1. Joints must be clean, dry, free of dirt, dust, loose paint, old caulk, soapy or other residue, oil, and grease.
2. Clean all metal surfaces of all rust. Prime with a rust-preventive primer and allow to thoroughly dry before application.



Technical Data

Sonolac® is a siliconized acrylic-latex product.

Compliances

- ASTM C 834
- USDA compliant for use in meat and poultry areas

Application

1. Apply Sonolac® by caulking gun. Hold nozzle in joint and fill it completely from the bottom up without forming voids or air pockets.
2. Shape joints with a dry or water-wet tool.

Clean Up

Clean tools and equipment with water before Sonolac® dries.

For Best Performance

- Do not apply Sonolac® at temperatures below 40° F (4° C).
- Do not apply exterior if rain is expected within 8 hours following application.
- Sonolac® is not recommended for traffic-bearing and horizontal surfaces, below-grade applications, and water immersion.
- Make certain the most current versions of product data sheet and MSDS are being used; call Customer Service (1-800-433-9517) to verify the most current versions.
- Proper application is the responsibility of the user. Field visits by BASF personnel are for the purpose of making technical recommendations only and not for supervising or providing quality control on the jobsite.

Health and Safety

SONOLAC®

Warning

Sonolac® contains mineral spirits, butyl benzyl phthalate, and ethylene glycol.

Risks

May cause eye, skin or respiratory irritation. Ingestion may cause irritation. Reports associate repeated or prolonged occupational overexposure to solvents with permanent brain, nervous system, liver and kidney damage. INTENTIONAL MISUSE BY DELIBERATELY INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

Precautions

KEEP OUT OF THE REACH OF CHILDREN. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Avoid breathing vapor. Use only with adequate ventilation. Use impervious gloves, eye protection and if the TLV is exceeded or used in a poorly ventilated area, use NIOSH/MSHA approved respiratory protection in accordance with applicable federal, state and local regulations.

First Aid

In case of eye contact, flush thoroughly with water for at least 15 minutes. In case of skin contact, wash with soap and water. If irritation persists, SEEK MEDICAL ATTENTION. If inhalation causes physical discomfort, remove to fresh air. If discomfort persists or any breathing difficulty occurs or if swallowed, SEEK IMMEDIATE MEDICAL ATTENTION.

Refer to Material Safety Data Sheet (MSDS) for further information.

Proposition 65

This product does not knowingly contain materials listed by the State of California as known to cause cancer, birth defects or other reproductive harm.

VOC Content

.34 lbs/gal or 41 g/L, less water and exempt solvents.

**For medical emergencies only,
call ChemTrec (1-800-424-9300).**

BASF Construction Chemicals, LLC – Building Systems

889 Valley Park Drive
Shakopee, MN, 55379

www.BuildingSystems.BASF.com

Customer Service 800-433-9517

Technical Service 800-243-6739



LIMITED WARRANTY NOTICE Every reasonable effort is made to apply BASF exacting standards both in the manufacture of our products and in the information which we issue concerning these products and their use. We warrant our products to be of good quality and will replace or, at our election, refund the purchase price of any products proved defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. Therefore, except for such replacement or refund, BASF MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY, RESPECTING ITS PRODUCTS, and BASF shall have no other liability with respect thereto. Any claim regarding product defect must be received in writing within one (1) year from the date of shipment. No claim will be considered without such written notice or after the specified time interval. User shall determine the suitability of the products for the intended use and assume all risks and liability in connection therewith. Any authorized change in the printed recommendations concerning the use of our products must bear the signature of the BASF Technical Manager.

This information and all further technical advice are based on BASF's present knowledge and experience. However, BASF assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights. In particular, BASF disclaims all CONDITIONS AND WARRANTIES, WHETHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY. BASF SHALL NOT BE RESPONSIBLE FOR CONSEQUENTIAL, INDIRECT OR INCIDENTAL DAMAGES (INCLUDING LOSS OF PROFITS) OF ANY KIND. BASF reserves the right to make any changes according to technological progress or further developments. It is the customer's responsibility and obligation to carefully inspect and test any incoming goods. Performance of the product(s) described herein should be verified by testing and carried out only by qualified experts. It is the sole responsibility of the customer to carry out and arrange for any such testing. Reference to trade names used by other companies is neither a recommendation, nor an endorsement of any product and does not imply that similar products could not be used.

For professional use only. Not for sale to or use by the general public.