

SONOLASTIC® POLYSULFIDE SEALANT PART B

Version 2.0

7/5/06

1. COMPANY AND PRODUCT INFORMATION

Company : BASF Building Systems, Inc.
889 Valley Park Drive
Shakopee, MN 55379 ,

Phone : 952-496-6000
Fax :
Emergency contact : 1-800-424-9300

Productname : SONOLASTIC® POLYSULFIDE SEALANT PART B
MSDS : 11033

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

ITEM	CHEMICAL NAME	CAS NUMBER	WT/WT % LESS THAN
01	Cyclohexanone	108-94-1	20.0 %
02	Epoxy resin	28054-14-4	85.0 %

ITEM	ACGIH		OSHA		COMPANY	SKIN
	TLV-TWA	TLV-STEL	PEL-TWA	PEL-CEILING		
01	25 ppm	N.E.	200 mg/m3	N.E.	N.E.	YES
02	N.E.	N.E.	N.E.	N.E.	N.E.	NO

(See Section 16 for abbreviation legend)

SECTION 3 - HAZARDOUS IDENTIFICATION

EFFECTS OF OVEREXPOSURE - EYE CONTACT: Causes eye irritation.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: May be absorbed through skin. May cause irritation.

EFFECTS OF OVEREXPOSURE - INHALATION: Headaches, dizziness, nausea, decreased blood pressure, changes in heart rate and cyanosis may result from over-exposure to vapor. Slightly irritating to respiratory tract.

EFFECTS OF OVEREXPOSURE - INGESTION: Irritating to mouth, throat and stomach.

SONOLASTIC® POLYSULFIDE SEALANT PART B

SECTION 3 - HAZARDOUS IDENTIFICATION CONTD

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: Prolonged or repeated overexposure may cause liver and kidney damage. No known components of this product are listed as known or suspected carcinogens per NIOSH, NTP, IARC, or OSHA.

PRIMARY ROUTE(S) OF ENTRY: SKIN CONTACT SKIN ABSORPTION INHALATION

SECTION 4 - FIRST AID MEASURES

FIRST AID - EYE CONTACT: Flush eye with water for 15 minutes. Get medical attention.

FIRST AID - SKIN CONTACT: Remove contaminated clothing. Wash skin with soap and water. Get medical attention.

FIRST AID - INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

FIRST AID - INGESTION: If swallowed, DO NOT induce vomiting. Give victim a glass of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person. Should vomiting occur, be sure to keep victim's head below hips to avoid aspiration of vomitus into lungs.

SECTION 5 - FIRE FIGHTING MEASURES

FLASH POINT: 111 F LOWER EXPLOSIVE LIMIT: 1.1 %
(TAGLIABUE CLOSED CUP) UPPER EXPLOSIVE LIMIT: 9.4 %

AUTOIGNITION TEMPERATURE: N/D

EXTINGUISHING MEDIA: CO2 DRY CHEMICAL WATER FOG

UNUSUAL FIRE AND EXPLOSION HAZARDS: Fire produces irritating or poisonous gas.

SPECIAL FIREFIGHTING PROCEDURES: As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear.

SONOLASTIC® POLYSULFIDE SEALANT PART B

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container. Repeat sorbent/sweep cycle until the spill has dried up. Avoid runoff into storm sewers and ditches which lead to waterways.

SECTION 7 - HANDLING AND STORAGE

HANDLING: Keep out of reach of children.

STORAGE: Keep container closed when not in use.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during the use of this product.

RESPIRATORY PROTECTION: Wear NIOSH/MSHA approved respiratory protection when the product is mixed or applied in a poorly ventilated area or if workplace levels of ingredients exceed the TLV. Follow applicable federal, state, and local regulations.

OTHER PROTECTIVE EQUIPMENT: Where contact is likely, wear chemical resistant gloves, chemical safety goggles with a face shield, and clean protective clothing to cover arms and legs to keep exposure to a minimum.

HYGIENIC PRACTICES: Do not take internally. Wash thoroughly after handling. Avoid contact with eyes, skin, and clothing.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

BOILING RANGE	: 313 - 313 F	VAPOR DENSITY	: Is heavier than air
ODOR	: Mild solvent	ODOR THRESHOLD	: N/D
APPEARANCE	: Viscous liquid	EVAPORATION RATE:	Is slower than Butyl Acetate
SOLUBILITY IN H2O	: Insoluble	SPECIFIC GRAVITY:	1.2100
FREEZE POINT	: N/D	pH @ 0.0 %	: N/D
VAPOR PRESSURE	: N/D	VISCOSITY	: N/D
PHYSICAL STATE	: Liquid		
COEFFICIENT OF WATER/OIL DISTRIBUTION: N/D			

(See Section 16 for abbreviation legend)

SONOLASTIC® POLYSULFIDE SEALANT PART B

SECTION 10 - STABILITY AND REACTIVITY

CONDITIONS TO AVOID: Long term exposure to elevated temperatures.
 INCOMPATIBILITY: Strong bases or oxidants. Strong Lewis or mineral acids.
 HAZARDOUS DECOMPOSITION PRODUCTS: Acrid fumes. Oxides of carbon.
 HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.
 STABILITY: This product is stable under normal storage conditions.

SECTION 11 - TOXICOLOGICAL PROPERTIES

PRODUCT DERMAL LD50: No Information PRODUCT ORAL LD50: No Information
 PRODUCT LC50: No Information

COMPONENT TOXICOLOGICAL INFORMATION:

----- CHEMICAL NAME -----	-- DERMAL LD50 --	--- ORAL LD50 ---	----- LC50 -----
Cyclohexanone	948 mg/kg	1535 mg/kg	8000 ppm/4H
Epoxy resin	No Information	No Information	No Information

SECTION 12 - ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: No Information.

SECTION 13 - DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Review all local, state, and federal regulations concerning health and pollution for appropriate disposal procedures.

SECTION 14 - TRANSPORTATION INFORMATION

DOT PROPER SHIPPING NAME: Combustible liquid, n.o.s.
 DOT TECHNICAL NAME: Cyclohexanone
 DOT HAZARD CLASS: COMBUSTIBLE LIQUID HAZARD SUBCLASS: N/A

SONOLASTIC® POLYSULFIDE SEALANT PART B

SECTION 14 - TRANSPORTATION INFORMATION CONTINUED

DOT UN/NA NUMBER: NA1993 PACKING GROUP: III RESP. GUIDE PAGE:
DOT PLACARD AT: 1000 lbs
DOT CLASS NUMBER: 3
UN PROPER SHIPPING NAME: Resin Solution
UN HAZARD CLASS: FLAMMABLE LIQUID
UN CLASS NUMBER: AIR 3 MARINE 3.3
HAZARD SUBCLASS: AIR N/A MARINE N/A
UN UN/NA NUMBER: UN1866 UN PACKING GROUP: AIR III MARINE III
UN PLACARD AT: N/A

SECTION 15 - REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS: AS FOLLOWS -

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200)

CERCLA - SARA HAZARD CATEGORY:

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

IMMEDIATE HEALTH HAZARD CHRONIC HEALTH HAZARD FIRE HAZARD

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

----- CHEMICAL NAME ----- CAS NUMBER WT/WT % IS LESS THAN
No SARA Section 313 components exist in this product.

TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

SONOLASTIC® POLYSULFIDE SEALANT PART B

SECTION 15 - REGULATORY INFORMATION CONTINUED

----- CHEMICAL NAME ----- CAS NUMBER
No information is available.

CALIFORNIA PROPOSITION 65:

WARNING: The chemical(s) noted below and contained in this product, are known to the state of California to cause cancer, birth defects or other reproductive harm:

----- CHEMICAL NAME ----- CAS NUMBER
No Proposition 65 chemicals exist in this product.

INTERNATIONAL REGULATIONS: AS FOLLOWS -

CANADIAN WHMIS: This MSDS has been prepared in compliance with Controlled Product Regulations except for use of the 16 headings.

CANADIAN WHMIS CLASS: No information available.

SECTION 16 - OTHER INFORMATION

HMIS RATINGS - HEALTH: 2 FLAMMABILITY: 2 REACTIVITY: 0
PERSONAL PROTECTION: G

PREVIOUS MSDS REVISION DATE: 03/09/99

REASON FOR REVISION: New product

VOLATILE ORGANIC COMPOUNDS (VOCS): When components are mixed this product contains 100 g/L or 0.84 lbs/gal, less water and exempt solvents.

LEGEND: N.A. - Not Applicable, N.E. - Not Established,
N.D. - Not Determined

This information is furnished without warranty, representation, or license of any kind, except that this information is accurate to the best of ChemRex's knowledge, or is obtained from sources believed by ChemRex to be accurate. No warranty is expressed or implied regarding the accuracy of this information or the results to be obtained from its use thereof. ChemRex assumes no responsibility for injuries proximately caused by use of the Material if reasonable safety procedures are not followed as stipulated in this Data Sheet. Additionally, ChemRex assumes no responsibility for injuries proximately caused by abnormal use of the Material even if reasonable safety procedures are followed. Buyer assumes the risk in its use of the Material.

<END OF MSDS>