
# TAMKO FIBERED **ROOF COATING**

A semi-mastic material consisting of select asphalt, mineral stabilizers, petroleum solvents and special fibers. Primarily used on all types of low sloped roof surfaces with the exception of coal tar based roofing. Acid and alkali resistant.

### 100% ASBESTOS FREE - GUARANTEED!

Provides needed additional weathering protection for membrane surfaces. Used on existing roofs to increase life expectancy and new roofs after suitable weathering.



PRODUCT NUMBER

30001280 - 1 GAL - Green Cove Springs FL 30001646 - 1 GAL - Columbus KS 30001281 - 5 GAL - Green Cove Springs FL 30001647 - 5 GAL - Columbus KS

## APPLICATION

**USES** 

Apply with a roofer's brush or spray equipment. Can be applied at temperatures as low as 50°F when kept at room temperature prior to use. Application rates include:

Composition Roofing	2 to 3 gallons per 100 sq. ft.
Metal Surfaces	1 to 1-1/2 gal per 100 sq. ft.
Concrete/Masonry	3 to 4 gallons per 100 sq. ft.

## PRODUCT DATA\*

TYPICAL PHYSICAL PROPERTIES*	MIN	MAX
Total solids, (non-volatiles), %	50	
Mineral and other stabilizers, %	5	20
Flash point, °F	100	
VOC, grams/litre		300
Viscosity, Stormer/100 rev.		
@77°F, seconds	50	90

### **SPECIFICATION COMPLIANCE:**

ASTM D 4479 Standard Specification for Asphalt Roof Coating

Visit our Web Site at tamko.com

\*All values stated as nominal

For Technical Services call 1 -800-641-4691

CAUTION: The National Institute for Occupational Safety and Health (NIOSH) has concluded that fumes of heated asphalt are a potential occupational carcinogen. Do not heat or burn this product.



BUILDING PRODUCTS TAMKO® is a registered trademark of TAMKO Building Products, Inc.

Central District	220 West 4th St., Joplin, MO	64801	800-641-4691
Northeast District	4500 Tamko Dr., Frederick, MD	21701	800-368-2055
Southeast District	2300 35th St., Tuscaloosa, AL	35401	800-228-2656
Southwest District	7910 S. Central Exp., Dallas, TX	75216	800-443-1834
Western District	5300 East 43rd Ave., Denver, CO	80216	800-530-8868

Information included in this product data sheet was current at time of printing. To obtain a copy of the most current version of this product data sheet, visit us online at tamko.com or call us at 800-641-4691.

07/2008