


TAMKO® FIBERED ALUMINUM ROOF COATING

PRODUCT DATA



PRODUCT NUMBER
30001344 - 5 GAL - Green Cove Springs FL
30002196 - 5 GAL - Columbus KS

USES

An excellent protective material combining high quality asphalts and petroleum solvents with tough fibers and selected aluminum pigments to form a highly reflective surface upon application. Once applied the aluminum pigments leaf to the surface to form a bright metallic coating within 24 hours.

100% ASBESTOS FREE - GUARANTEED!

This high performance material is ideal for coating prepared roofing, metal buildings, tanks, bins, grain elevators, exterior masonry and mobile home roofs. It reduces inside summer temperature by up to 15°F by reflecting the sun's harmful rays. Provides an attractive surface that protects and prolongs the surface life.

APPLICATION

Stir thoroughly before and during use to obtain uniform distribution of the aluminum

Apply with a roofer's brush. Outside temperature must be 50°F and rising before applying. Application rates include:

Composition Roofing	1-1/2 to 2 gallons per 100 sq. ft.
Metal Surfaces	1-1/4 gallons per 100 sq. ft.
Concrete/Masonry	1-1/2 to 2 gallons per 100 sq. ft.

Note: For maximum performance prepare all surfaces with an Asphalt Primer at the rate of 1 gallon per 100 sq. ft. Allow to dry overnight before applying the aluminum coating.

PRODUCT DATA*

TYPICAL PHYSICAL PROPERTIES*	MIN	MAX
Total solids (non-volatiles), %	50	--
Volatiles, %	--	50
Flash point, °F	100	--
VOC, grams/litre	--	500
Viscosity, Stormer/100 rev. @77°F, seconds	20	40

*All values stated as nominal

For Technical Services call 1-800-641-4691

Visit our Web Site at tamko.com



TAMKO
BUILDING PRODUCTS

TAMKO Logo, Roofer Logo and TAMKO® are registered trademarks of TAMKO® Building Products, Inc.

CAUTION: The National Institute for Occupational Safety and Health has concluded that the fumes of heated roofing asphalt are a potential occupational carcinogen. The physical nature of this product may help limit any inhalation hazard during application and/or removal. However, physical forces such as sawing, grinding or drilling during demolition work and heating or burning may increase the inhalation or dermal exposure hazard of this product. This product should not be heated or burned using a direct flame device. Take precautions to prevent breathing and contact with skin.

Central District	220 West 4th St.	Joplin, MO	64801	800-641-4691
Northeast District	4500 Tamko Dr.	Frederick, MD	21701	800-368-2055
Southeast District	2300 35th St.	Tuscaloosa, AL	35401	800-228-2656
Southwest District	7910 S. Central Exp.	Dallas, TX	75216	800-443-1834
Western District	5300 East 43rd Ave.	Denver, CO	80216	800-530-8868

Information included in this product data sheet was current at time of printing. To obtain a copy of the most current version of this product data sheet, visit us online at tamko.com or call us at 800-641-4691.