

Teragren® Bamboo Flooring Product Selection & Submittal Sheet

3-Part CSI Specs available at teragren.com; Coordinating bamboo stair parts, flooring accessories, panels and veneer available.

- **PORTFOLIO:** Prefinished Strand Wide Plank Flooring with Valinge drop/fold self-locking system
- **SYNERGY™:** Prefinished Strand Solid-Strip MPL (multiple precise lengths)
- **SYNERGY™ Floating Floor:** Prefinished Strand Wide Plank Floating Floor with Valinge self-locking system
- **SYNERGY™72:** Prefinished Strand Solid-Strip 72 (.39" x 72.44" x 3.78")
- **STUDIO:** Prefinished Wide Plank Bamboo Floating Floor with Valinge self-locking system
- **CRAFTSMAN II:** Prefinished Long Plank (also available unfinished)
- **SIGNATURE COLORS:** Prefinished Espresso, Cherry, Walnut + Charcoal stain colors
- **SIGNATURE NATURALS:** Prefinished + Unfinished Solid Strip Bamboo Flooring
- **ELEMENTS:** Prefinished Solid Strip- 3 Foot

Product	Finish PF	Color			Grain		Dimensions			Grade		
		N	C	S	FG	VG	Thickness	Length	Width	Above	On	Below
PORTFOLIO	√			**	Strand		.47" (12mm)	72.44" 1840mm	4.96" (126mm)	√	√	√ ¹
SYNERGY	√			***	Strand		.47" (12mm)	24.02/36.02/48.03/72.05" 610/915/1220/1830mm	3.78" (96mm)	√	√	
SYNERGY WP-FF	√			***	Strand		.55" (14mm)	72.05" 1830mm	7.68" (195mm)	√	√	√ ¹
SYNERGY-72	√			***	Strand		.39" (10mm)	72.44" 1840mm	3.78" (96mm)	√	√	
STUDIO*	√	√	√		√	√	.55" (14mm)	75" 1905mm	7.68" (195mm)	√	√	√ ¹
CRAFTSMAN II	√	√	√		√	√	.59" (15mm)	75.59" 1920mm	5.43" (138mm)	√	√	√ ¹
SIGNATURE COLORS	√			√	√		.59" (15mm)	24.41/36.22/48.03/72.44" 620/920/1220/1840mm	3.62" (92mm)	√	√	
SIGNATURE NATURALS	√	√	√		√	√	.59" (15mm)	24.41/36.22/48.03/72.44" 620/920/1220/1840mm	3.62" (92mm)	√	√	
ELEMENTS	√	√	√		√	√	.59" (15mm)	36.22" 920mm	3.62" (92mm)	√	√	

¹ Floating only below grade

****PORTFOLIO** - Available in 10 designer colors + textures, including handscraped options

*****SYNERGY** - Available in solid-strip 12mm or wide plank floating floor in "Wheat", "Java", Brindle" or "Chestnut" colors

*****SYNERGY-72** - Available in solid-strip in 10mm in Wheat or Java only

***STUDIO** - .15" bamboo wear-layer mounted on 100% bamboo fiber cross-ply core

Color: Natural (N) or Caramelized or Stains (S): Espresso, Cherry, Charcoal, Walnut

Grain: Flat Grain (FG) or Vertical Grain (VG) or Strand

Finish: Prefinished (PF) or Unfinished (UF)

SKU example: PF-FGC = Prefinished Flat Grain Caramelized



This product has been certified to meet the requirements of the flooring products certification program for indoor air quality.



COMPLETE DETAILS ARE AVAILABLE AT WWW.RFCI.COM

CERT. # SCS-FS-01878

Product Specifications



FINE BAMBOO FLOORING, PANELS & VENEER

Product	Installation				Over Radiant Heat	Residential Warranty		Commercial Warranty	
	Nail	Staple	Glue	Float		Structural	Wear-through Finish	Structural	Wear-through Finish
<i>PORTFOLIO</i>			√	√	√	Lifetime	25 yrs	Lifetime	10 yrs
<i>SYNERGYSS</i>	√	√	√		√	Lifetime	25 yrs	Lifetime	10 yrs
<i>SYNERGYWP-FF</i>			√	√	√	Lifetime	25 yrs	Lifetime	10 yrs
<i>SYNERGY-72</i>	√	√	√		√	Lifetime	25 yrs	Lifetime	10 yrs
<i>STUDIO</i>			√	√	√	Lifetime	25 yrs	Lifetime	10 yrs
<i>CRAFTSMAN II</i>	√	√	√	√	√	Lifetime	25 yrs	Lifetime	10 yrs
<i>SIGNATURE</i>	√	√	√		√	Lifetime	25 yrs	Lifetime	10 yrs
<i>ELEMENTS</i>	√	√	√		√	Lifetime	7 yrs	Lifetime	3 yrs

SPECIFICATIONS:

For product specific test results, please refer to www.teragren.com/ad/tech_csi.html

See our Material and Sustainability Report at www.teragren.com

The following apply to all Teragren products.

Bamboo Species: Phyllostachys Pubescens (common name: Moso) sustainably harvested at maturity between 5 ½ and 6 years for maximum stability, hardness and clarity of color. Specify Teragren Optimum 5.5® Moso Bamboo Flooring.

Finish: Prefinished flooring features a durable 7-coat aluminum oxide/polyurethane finish; water-based, solvent-free.

Manufacturing Adhesive: Teragren’s proprietary manufacturing adhesive emits less formaldehyde than allowed by U.S. OSHA, European E0, CARB Phase 1 & 2, and Japanese JIS/JAS (F****) emission standards. Ask about formaldehyde-free products by special order.

LEED® Credits: Teragren bamboo products contribute to certification under the U.S. Green Building Council’s LEED® (Leadership in Energy & Environmental Design) rating system: MR Credit 6: Rapidly Renewable Materials. All Teragren flooring products contribute to IEQ Credit 4.3 (FloorScore®-certified); Select urea-free Teragren bamboo panels and countertops contribute to IEQ Credit 4.4

FSC-PURE traditional certified bamboo products available by special order and qualify for MR Credit 7: Certified Wood. Before specifying, please contact Teragren for updated LEED® credit information



Maintenance: For cleaning Teragren recommends Bona Swedish Formula Hardwood Floor Cleaner (www.bonakemi.com) or WoodWise Floor Cleaner (www.woodwiseproducts.com).

For Refinishing: Use Bona Prep™ Recoating Adhesion System Tel: 800.872.5515, www.bonakemi.com. See www.teragren.com “Care Instructions” for more information.