



Professional Caulks & Sealants

Catalog



Titebond
THE PRO'S ADVANTAGE

PAINTERS PLUS CAULK

Seals joints, repairs cracks & fills gaps
Paints & stains easily with one coat
Resists mold, mildew & water

15 YEAR
White

PERFORMED ACRYLIC

STRONG ADHESION
GOOD FLEXIBILITY
WEAR-RESISTANT

CAUTION: EYE AND SKIN IRRITANT.
Avoid contact on face and eyes.

NET 10.1 fl. oz. (300 mL)

Titebond
THE PRO'S ADVANTAGE

WEATHERMASTER SEALANT

Extrudes down to 0°F
Superior flexibility - Won't crack
Applied in extreme weather conditions
Tite-bond up to 1" - Extrudes easily

LIFETIME

SUPERIOR POLYMER TECHNOLOGY

UV-RESISTANT
PAINTABLE
REACTIVE

CAUTION: EYE AND SKIN IRRITANT.
Avoid contact on face and eyes.

NET 10.1 fl. oz. (300 mL)

Titebond
THE PRO'S ADVANTAGE

100% SILICONE SEALANT

MULTI-PURPOSE SEALANT

15 YEAR
White

ELASTIC GROUT

FLEXIBILITY
DISCOLOR RESISTANT

CAUTION: EYE, SKIN AND RESPIRATORY IRRITANT.
Avoid contact on face and eyes.

NET 10.1 fl. oz. (300 mL)

WeatherMaster™ Sealant

Titebond® WeatherMaster™ Sealant has been specifically formulated to outperform all other sealant technologies, including silicones, tripolymers and urethanes. This superior polymer formula provides the best possible performance on siding, windows, doors and vents. In addition to offering permanent flexibility, it provides unbeatable adhesion to wood, fiberboard, vinyl, aluminum, metal roofing, brass and other common building materials.

WeatherMaster™ Sealant is available in over 170 colors, all of which match today's popular siding colors, regardless of the material or manufacturer. If touch-ups are necessary, it is paintable in one hour after application. It is waterproof, extrudes in extreme weather conditions and is UV-resistant, making it the ideal choice for exterior applications. Safety is not compromised, as this sealant contains no solvents or isocyanates and is VOC-compliant.



WeatherMaster™ Sealant Ordering Information

Cat. No.	Color	Size	Unit/Case	Ctn. lbs.	Cases/Pallet
44001	White	10.3 oz.	12	15	108
43991	Crystal Clear	10.3 oz.	12	10	108
44011	Translucent	10.3 oz.	12	10	108

More than 170 colors- please reference the WeatherMaster Color Reference Guide

Exceeds the requirements of ASTM C920 Type S, Grade NS, Class 25 and TTS-00230C.

WeatherMaster™ Sealant Comparison Guide

	WeatherMaster	VOC Solvent	Silicone	Urethane	Tripolymer
Paintable	1 hour	2 hours	No	2-7 days	24 hours
Shrinkage	1%	30%	5%	5%	50%
Flexibility	40%	25%	25%	25%	25%
Cold Weather Extrusion	0°	20°	-35°	32°	-40°
VOC – compliant	Yes	Yes	Yes	Yes	Yes
Gap Filling	1"	1/2"	1/2"	1/2"	1/2"
Odor	Slight	Heavy	Mild	Mild	Moderate
Service Temperature (°F)	-75° to 350°	-20° to 200°	-45° to 350°	-40° to 180°	-40° to 180°



Titebond®

THE PRO'S ADVANTAGE™

History of Solutions

For more than 50 years, the Titebond® name has represented one of the most respected brands of adhesives for construction professionals. Given the reputation among contractors and dedicated do-it-yourselfers, the use of the Titebond® name makes a strong statement about the confidence in the quality of our caulk and sealant product offerings.

Franklin International has brought, and continues to bring, years of innovative research and development to the forefront of the caulk and sealant industry. Storied accomplishments from Franklin include:

- The first colored caulk program.
- The first modified acrylic caulk with low temperature extrudability.
- The first advanced polymer technology caulks (170+ colors) to the vinyl siding, fiber cement siding and building material industry.

Future of Commitment

With a long-term commitment to the future growth of our customers, partners and worldwide markets, Franklin International is actively positioned to provide many adhesive solutions. Our dedication to research initiatives will continue to result in innovative products to meet evolving industry needs and environmental concerns. As a result, our caulks and sealants meet stringent VOC and indoor air quality regulations, without compromising superior product and quality performance.



All Siding Sealant

A unique, modified-acrylic formula that offers superior adhesion on all common construction materials. It is ideal for sealing doors, windows, soffits and awnings around vinyl, aluminum, stucco, wood, brick and glass. This sealant dries quickly and can be painted and stained within 2-4 hours of application. It is also de-aired for a smooth, uniform bead and cleans up with water when wet. Titebond® All Siding Sealant exceeds the performance requirements for ASTM C920, C834 and TT-S-00230C.



Cat. No.	Color	Size	Unit/Case	Ctn. lbs.	Cases/Pallet
3301	White	10.1 oz.	12	15	108
3311	Cape Gray	10.1 oz.	12	15	108
3321	Almond	10.1 oz.	12	15	108
3331	Brown	10.1 oz.	12	15	108
3351	Clay	10.1 oz.	12	15	108
3361	Cedar	10.1 oz.	12	15	108

Adhesive Caulk

A urethane acrylic formula that does it all! Its excellent adhesion and flexibility outperform both silicone and urethane sealants, making it ideal for all interior/exterior home remodeling projects. It provides a watertight seal on most applications, including tubs, sinks, showers, doors, windows, siding, vents and gutters. Titebond® Adhesive Caulk also bonds and repairs ceramic tile, towel bars, molding, cove base, mirrors, tub surrounds, paneling and insulation material. It offers a quick grab and is easy to tool and finish. Meets or exceeds ASTM C834 and the performance requirements of ASTM C920 Class 25 and Federal Specification TT-S-00230C Class A.



Cat. No.	Color	Size	Unit/Case	Ctn. lbs.	Cases/Pallet
8701	White	10.1 oz.	12	15	108
8711	Almond	10.1 oz.	12	15	108
8721	Black	10.1 oz.	12	15	108
8731	Bronze	10.1 oz.	12	15	108
8741	Clear	10.1 oz.	12	15	108
8751	Gray	10.1 oz.	12	15	108

Kitchen & Bath Sealant

A 100% silicone formula specifically designed to permanently seal high-moisture areas found in kitchens and baths. This highly flexible, mildew-resistant sealant offers strong, watertight adhesion and will not shrink or discolor over time. Titebond® Kitchen & Bath Sealant is safe for food preparation areas when fully cured and is unaffected by water, humidity or heat. It meets or exceeds Federal Specification TT-S-001543A, Class A and ASTM C920 Type S, Grade NS, Class 25.



Cat. No.	Color	Size	Unit/Case	Ctn. lbs.	Cases/Pallet
1601	White	10.1 oz.	12	11	108
1611	Clear	10.1 oz.	12	11	108
1621	Almond	10.1 oz.	12	11	108

100% Silicone Sealant

A versatile, 100% silicone formula designed for interior and exterior applications. Ideal for most construction, remodeling and repair projects including doors, windows, siding, vents, tubs, sinks and more. It forms a tough yet flexible seal that is watertight and mildew-resistant. Titebond® 100% Silicone Sealant offers strong adhesion to most materials and can withstand extreme temperature changes. It has been certified to Federal Specification TT-S-001543A, Class A and passes ASTM C920 Type S, Grade NS, Class 25.



Cat. No.	Color	Size	Unit/Case	Ctn. lbs.	Cases/Pallet
2601	White	10.1 oz.	12	11	108
2611	Clear	10.1 oz.	12	11	108
2621	Almond	10.1 oz.	12	11	108
2631	Black	10.1 oz.	12	11	108

Painters Plus Caulk

Designed for both interior and exterior applications, this siliconized acrylic formula is ideal for back filling trim, repairing cracks and sealing joints. It provides a mildew-resistant, watertight seal for most construction and repair projects. Titebond® Painters Plus Caulk is highly flexible and offers a smooth bead that can be painted or stained easily in one coat. It is easy to extrude, cleans up with water and has no residual odor. Exceeds the performance requirements of ASTM C834.



Cat. No.	Color	Size	Unit/Case	Ctn. lbs.	Cases/Pallet
8301	White	10.1 oz.	12	15	108
8311	Almond	10.1 oz.	12	15	108
8321	Brown	10.1 oz.	12	15	108
8331	Clear	10.1 oz.	12	10	108
8341	Gray	10.1 oz.	12	15	108
8351	Woodtone	10.1 oz.	12	15	108
8361	Black	10.1 oz.	12	15	108
8371	Antique White	10.1 oz.	12	15	108

Painters Caulk

A quality, yet economical latex formula designed specifically for interior pre-paint preparation. Ideal for filling gaps around baseboards, moldings and mantels, as well as repairing cracks in plaster and drywall. It dries quickly and offers good adhesion to most common building materials. Titebond® Painters Caulk offers a smooth, uniform bead that can be painted or stained with one coat. It is easy to extrude, cleans up with water and has no residual odor.



Cat. No.	Color	Size	Unit/Case	Ctn. lbs.	Cases/Pallet
7301	White	10.1 oz.	12	15	108

Gutter & Seam Sealant

A long-lasting, advanced polymer sealant formulated specifically for sealing aluminum, galvanized and vinyl clad gutters and downspouts. Titebond® Gutter & Seam Sealant provides a highly weather-resistant seal against water, wind, dust and dirt while retaining its resiliency and flexibility for years. It offers excellent adhesion to wood, metal, aluminum, steel, plastics, masonry and glass.



Cat. No.	Color	Size	Unit/Case	Ctn. lbs.	Cases/Pallet
7321	White	10.3 oz.	12	15	108
7331	Aluminum Gray	10.3 oz.	12	15	108

Concrete Joint Sealant

This one-component, advanced polymer sealant is formulated specifically for filling contraction or expansion joints and cracks in concrete decks and floors. Titebond® Self-Leveling Concrete Joint Sealant is designed to flow easily and smoothly into concrete cracks and joints to provide a permanent and durable seal. Meets or exceeds Federal Specification TT-S-00230C, Type I, Class A, ASTM C920 Type S Grade P Class 25, Use T and M, CAN/CGSB-19.13-M87, Class-1-40-B-N and C-1-25-B-N.



Cat. No.	Color	Size	Unit/Case	Ctn. lbs.	Cases/Pallet
3191	Gray	10.3 oz.	12	15	108
3192	Gray	29 oz.	12	39	38

Roof Cement Sealant

Titebond® Roof Cement Sealant is an all-weather, asphalt-based patching compound that is specifically designed and formulated to repair cracks, seams, gaps and holes in roofing materials. Use to set flashings, drip edges and roofing material edges and to install shingles and roll roofing. Ideal for repair and new construction roofing applications. It also seals around skylights, vents, chimneys, valleys and exhaust pipes. Formulated to meet Federal Specification SS-C-153C Type I. Compliance: ASTM D6511, SCAQMD Rule #1168.



Cat. No.	Color	Size	Unit/Case	Ctn. lbs.	Cases/Pallet
3211	Black	10.3 oz.	12	10	108
3212	Black	29 oz.	12	26	38

Blacktop Repair

A durable, acrylic-latex formula specifically designed for repairing and sealing cracks in all asphalt surfaces. It provides a durable, weather-resistant seal that helps protect from oil, gas, grease, salt, water and ice damage. Its silicized acrylic formula offers excellent adhesion and will not peel, crack or pull away from the repaired area. Titebond® Blacktop Repair dries to a textured finish, extrudes easily and cleans up with water.



Cat. No.	Color	Size	Unit/Case	Ctn. lbs.	Cases/Pallet
3181	Black	10.1 oz.	12	15	108

Concrete Repair

A silicized acrylic formula specifically designed for repairing and sealing cracks in concrete steps, sidewalks and driveways, as well as mortar joints. It provides a durable, weather-resistant seal that helps protect from oil, gas, salt, water and ice damage. It offers excellent adhesion and will not peel, crack or pull away from the repaired area. Titebond® Concrete Repair dries to a textured finish, extrudes easily and cleans up with water.



Cat. No.	Color	Size	Unit/Case	Ctn. lbs.	Cases/Pallet
3171	Gray	10.1 oz.	12	15	108

Tub & Tile Caulk

An acrylic formula that provides a mildew-resistant, watertight seal is specifically designed for sealing around tubs, sinks, showers, lavatories, countertops, backsplashes and ceramic tile. It dries fast and can be painted easily with one coat. Titebond® Tub & Tile Caulk offers good adhesion to porcelain, ceramic, marble, fiberglass and painted surfaces. It cleans up with water and has no residual odor.



Cat. No.	Color	Size	Unit/Case	Ctn. lbs.	Cases/Pallet
3110	White	5.5 oz.	12	8	192



**Professional
Caulks & Sealants**
Catalog

Refer to www.titebond.com for WeatherMaster™ Color Match Cross-Reference Guide.

Refer to your caulk and sealants order forms for all merchandising.

Franklin International

2020 Bruck Street Columbus, Ohio 43207

800.669.4583 Customer Service 800.347.4583 Technical Service
www.titebond.com 800.879.4553 FAX