

ACOUSTICAL SEALANT 30CTG

Version 4.0
REVISION DATE: 06/25/2014

Print Date 06/26/2014

SECTION 1 - PRODUCT IDENTIFICATION

Trade name : **ACOUSTICAL SEALANT 30CTG**

Product code : 93170X 330

COMPANY : Tremco Incorporated
3735 Green Road
Cleveland, OH 44122

Telephone : (216) 292-5000 8:30 - 5:00 EST
Emergency Phone : (216) 765-6727 8:30 - 5:00 EST
After Hours: Chemtrec 1-800-424-9300

Product use : Sealant

SECTION 2 - HAZARDS IDENTIFICATION**Emergency Overview**

Dark Gray. Non-sag gunnable paste. No serious effects anticipated under normal conditions of use. Vapor may irritate respiratory tract. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

Acute Potential Health Effects/ Routes of Entry

Inhalation : No serious effects anticipated under normal conditions of use. Vapor may irritate respiratory tract.

Eyes : Slightly irritating.

Ingestion : May cause irritation to the mouth, throat and stomach. May cause gastrointestinal irritation, nausea, and vomiting.

Skin : Irritant effect may be delayed.

Aggravated Medical Conditions

Pre-existing eye, skin, liver, kidney, and respiratory disorders may be aggravated by exposure.

Chronic Health Effects

Carbon black is classified by IARC to be a known animal carcinogen and a possible human carcinogen (Group 2B). Carbon black is encapsulated by resin and not expected to have adverse effects unless made airborne. Inhalation of crystalline silica (quartz) can cause cancer based on animal data, and IARC concludes sufficient evidence in humans (Group 1). Prolonged and repeated overexposure to free crystalline silica dust above the TLV level may cause scarring of the lungs with cough and shortness of breath. A delayed lung injury, silicosis may result from breathing free silica. Fillers are encapsulated and not expected to be released from product under normal conditions of use. Prolonged or repeated exposure to mineral spirits (petroleum naphtha or stoddard solvent) may cause defatting, drying, and irritation of the skin, dermatitis, central nervous system (CNS) effects, and adverse liver, kidney, and lung effects.

SECTION 3 - PRODUCT COMPOSITION

Chemical Name	CAS-No.	Weight %
Clay	1332-58-7	30.0 - 60.0
Calcium Carbonate (Limestone)	1317-65-3	15.0 - 40.0

ACOUSTICAL SEALANT 30CTG

Version 4.0

Print Date 06/26/2014

REVISION DATE: 06/25/2014

Polybutene	9003-29-6	7.0 - 13.0
Stoddard solvent (Mineral Spirits)	8052-41-3	7.0 - 13.0
Residual oils (petroleum)	64742-62-7	5.0 - 10.0
Isobutylene isoprene copolymer	NJ TSRN# 51721300-5275P	3.0 - 7.0
N-Tallow alkyltrimethyldiamine	61791-53-5	3.0 - 7.0
Petroleum distillates	64742-47-8	1.0 - 5.0
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	0.1 - 1.0
1,2,4-Trimethylbenzene	95-63-6	0.1 - 1.0
Carbon Black	1333-86-4	0.1 - 1.0

SECTION 4 - FIRST AID MEASURES

Get immediate medical attention for any significant overexposure.

Inhalation	:	Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.
Eye contact	:	Flush with water for 15 minutes. If irritation persists, get medical attention.
Skin contact	:	Clean area of contact thoroughly using soap and water. If irritation, rash or other disorders develop, get medical attention immediately.
Ingestion	:	Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.

SECTION 5 - FIRE FIGHTING MEASURES

Flash point	:	Not available.
Method	:	Not available.
Burning rate	:	Non-flammable solid
Lower explosion limit	:	Not available.
Upper explosion limit	:	Not available.
Autoignition temperature	:	Not available.
Extinguishing media	:	If water fog is ineffective, use carbon dioxide, dry chemical or foam.
Hazardous combustion products	:	Smoke, fumes. Carbon monoxide and carbon dioxide can form.
Protective equipment for firefighters	:	Use accepted fire fighting techniques. Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA).
Fire and explosion conditions	:	This product not expected to ignite under normal conditions of use.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Use appropriate protective equipment. Avoid contact with material. Scrape up and transfer to appropriate container for disposal.

SECTION 7 - HANDLING AND STORAGE

Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when

ACOUSTICAL SEALANT 30CTG

Version 4.0

Print Date 06/26/2014

REVISION DATE: 06/25/2014

not in use. Precautions also apply to emptied containers. Handle in compliance with common hygienic practices. Clean hands thoroughly after handling. Do not use in confined or poorly ventilated areas. Store in sealed containers in a cool, dry, ventilated warehouse location.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Personal protection equipment

- Respiratory protection : Not required under normal conditions of use. Wear appropriate, properly fitted NIOSH/MSHA approved organic vapor or supplied air respirator when airborne contaminant level(s) are expected to exceed exposure limits indicated on the MSDS. Follow manufacturer's directions for respirator use.
- Hand protection : Use suitable impervious rubber or vinyl gloves and protective apparel to reduce exposure.
- Eye protection : Wear appropriate eye protection.
- Skin and body protection : Prevent contact with shoes and clothing.
- Protective measures : Use professional judgment in the selection, care, and use.
- Engineering measures : General ventilation is sufficient.

Exposure Limits

Chemical Name	CAS Number	Regulation	Limit	Form
Clay	1332-58-7	ACGIH TWA: OSHA PEL: OSHA PEL: OSHA TWA: OSHA TWA: OSHA PEL: OSHA PEL:	2 mg/m3 15 mg/m3 5 mg/m3 15 mg/m3 5 mg/m3 5 mg/m3 15 mg/m3	Respirable fraction. Total dust. Respirable fraction. Total dust. Respirable fraction. Respirable fraction. Total dust.
Calcium Carbonate (Limestone)	1317-65-3	OSHA PEL: OSHA PEL: ACGIH TWA: ACGIH TWA: OSHA TWA: OSHA TWA:	5 mg/m3 15 mg/m3 3 mg/m3 10 mg/m3 15 mg/m3 5 mg/m3	Respirable fraction. Total dust. Respirable particles. Inhalable particles. Total dust. Respirable fraction.
Stoddard solvent (Mineral Spirits)	8052-41-3	ACGIH TWA: OSHA PEL:	100 ppm 2,900 mg/m3	
Petroleum distillates	64742-47-8	ACGIH TWA: ACGIH TWA:	200 mg/m3 200 mg/m3	Non-aerosol.as total hydrocarbon vapor Non-aerosol.as total hydrocarbon vapor
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	OSHA TWA: OSHA TWA: OSHA PEL: OSHA PEL: ACGIH TWA:	0.1 mg/m3 0.3 mg/m3 15 mg/m3 5 mg/m3 0.025 mg/m3	Respirable. Total dust. Total dust. Respirable fraction. Respirable fraction.

ACOUSTICAL SEALANT 30CTG

Version 4.0

Print Date 06/26/2014

REVISION DATE: 06/25/2014

<u>Chemical Name</u>	<u>CAS Number</u>	<u>Regulation</u>	<u>Limit</u>	<u>Form</u>
1,2,4-Trimethylbenzene	95-63-6	ACGIH TWA:	25 ppm	
Carbon Black	1333-86-4	ACGIH TWA: OSHA PEL: OSHA TWA: OSHA TWA:	3.5 mg/m3 3.5 mg/m3 15 mg/m3 5 mg/m3	Total dust. Respirable fraction.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Form	: Non-sag gunnable paste
Color	: Dark Gray
Odor	: Naptha
pH	: Not available.
Vapour pressure	: Not available.
Vapor density	: Heavier than air
Melting point/range	: Not available.
Freezing point	: Not available.
Boiling point/range	: 400 °C, 752 °F
Water solubility	: Negligible
Specific Gravity	: 1.62
% Volatile Weight	: 9 %

SECTION 10 - REACTIVITY / STABILITY

Substances to avoid	: Oxidizing agents.
Stability	: Material is stable under normal storage, handling, and use.
Hazardous polymerization	: Will not occur under normal conditions.

SECTION 11 - TOXICOLOGICAL INFORMATION

No Data Available

SECTION 12 - ECOLOGICAL INFORMATION

No Data Available

SECTION 13 - DISPOSAL CONSIDERATIONS

Disposal Method : Waste not regulated under RCRA. Incinerate at EPA approved facility or dispose of waste in compliance with state and local regulations.

ACOUSTICAL SEALANT 30CTG

Version 4.0
REVISION DATE: 06/25/2014

Print Date 06/26/2014

SECTION 14 - TRANSPORTATION / SHIPPING DATA**CFR / DOT:**

Not Regulated

TDG:

Not Regulated

IMDG:

Not Regulated

SECTION 15 - REGULATORY INFORMATION**North American Inventories:**

All components are listed or exempt from the TSCA inventory.
This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

U.S. Federal Regulations:

SARA 313 Components : None present or none present in regulated quantities.

SARA 311/312 Hazards : Acute Health Hazard
Chronic Health Hazard

OSHA Hazardous Components :

Clay	1332-58-7
Calcium Carbonate (Limestone)	1317-65-3
Stoddard solvent (Mineral Spirits)	8052-41-3
Petroleum distillates	64742-47-8
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7
1,2,4-Trimethylbenzene	95-63-6
Carbon Black	1333-86-4

OSHA Status: Considered : Irritant
hazardous based on the Carcinogen
following criteria:

OSHA Flammability : Not Regulated

Regulatory VOC (less water and : 150 g/l
exempt solvent)

VOC Method 310 : 9.28 %

Chemical is listed as an IARC, NTP, OSHA, or ACGIH Carcinogen:
Crystalline Silica (Quartz)/ Silica Sand 14808-60-7

ACOUSTICAL SEALANT 30CTG

Version 4.0

Print Date 06/26/2014

REVISION DATE: 06/25/2014

Carbon Black 1333-86-4

U.S. State Regulations:

MASS RTK Components	Clay	1332-58-7
	Calcium Carbonate (Limestone)	1317-65-3
	Stoddard solvent (Mineral Spirits)	8052-41-3
	Petroleum distillates	64742-47-8
	Crystalline Silica (Quartz)/ Silica Sand	14808-60-7
Penn RTK Components	Clay	1332-58-7
	Calcium Carbonate (Limestone)	1317-65-3
	Polybutene	9003-29-6
	Stoddard solvent (Mineral Spirits)	8052-41-3
	Residual oils (petroleum)	64742-62-7
	Isobutylene isoprene copolymer	NJ TSRN# 51721300-5275P
	N-Tallow alkyltrimethyldiamine	61791-53-5
	Petroleum distillates	64742-47-8
NJ RTK Components	Clay	1332-58-7
	Calcium Carbonate (Limestone)	1317-65-3
	Polybutene	9003-29-6
	Stoddard solvent (Mineral Spirits)	8052-41-3
	Residual oils (petroleum)	64742-62-7
	Petroleum distillates	64742-47-8
	Crystalline Silica (Quartz)/ Silica Sand	14808-60-7
	Carbon Black	1333-86-4

Components under California Proposition 65:

WARNING! Contains chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm

SECTION 16 - OTHER INFORMATION

HMIS Rating :

Health	2
Flammability	1
Reactivity	0
PPE	

0 = Minimum
 1 = Slight
 2 = Moderate
 3 = Serious
 4 = Severe

Further information:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

Prepared by: Rich Mikol

Legend

ACGIH - American Conference of Governmental Hygienists
 CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act
 DOT - Department of Transportation

PEL - Permissible Exposure Limit
 RCRA - Resource Conservation and Recovery Act
 RTK - Right To Know

ACOUSTICAL SEALANT 30CTG

Version 4.0

Print Date 06/26/2014

REVISION DATE: 06/25/2014

DSL - Domestic Substance List
EPA - Environmental Protection Agency
HMIS - Hazardous Materials Information System
IARC - International Agency for Research on Cancer
MSHA - Mine Safety Health Administration
NDSL - Non-Domestic Substance List
NIOSH - National Institute for Occupational Safety and Health
NTP - National Toxicology Program
OSHA - Occupational Safety and Health Administration

SARA - Superfund Amendments and Reauthorization Act
STEL - Short Term Exposure Limit
TLV - Threshold Limit Value
TSCA - Toxic Substances Control Act
TWA - Time Weighted Average
V - Volume
VOC - Volatile Organic Compound
WHMIS - Workplace Hazardous Materials Information System

