

TREMSIL 200 ANODIZED ALUMINUM - 30 CTG

 Version 2.0
 REVISION DATE: 07/08/2012

Print Date 12/06/2013

SECTION 1 - PRODUCT IDENTIFICATION

Trade name : TREMSIL 200 ANODIZED ALUMINUM - 30 CTG
 Product code : 97187865 323

COMPANY : Tremco Incorporated
 3735 Green Road
 Cleveland, OH 44122

Telephone : (216) 292-5000 8:30 - 5:00 EST
 Emergency Phone: : (216) 765-6727 8:30 - 5:00 EST
 After Hours: Chemtrec 1-800-424-9300

Product use : Sealant

SECTION 2 - HAZARDS IDENTIFICATION
Emergency Overview

Aluminum/Gray. Paste. May cause moderate irritation to the respiratory system. May cause nausea, headaches, and dizziness. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

Acute Potential Health Effects/ Routes of Entry

Inhalation : May cause moderate irritation to the respiratory system. May cause nausea, headaches, and dizziness.
 Eyes : Direct contact may cause severe irritation.
 Ingestion : May cause irritation to the mouth, throat and stomach. May cause tooth erosion and slight irritation.
 Skin : May cause moderate irritation.

Aggravated Medical Conditions

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure.

Chronic Health Effects

As a by product of curing, acetic acid is produced. Acetic acid is a severe eye, skin and mucus membrane irritant and may cause burns with repeated or prolonged contact. Chronic exposure can cause bronchitis and pharyngeal edema. Acetic acid may cause tooth erosion from tooling. Carbon black is classified by IARC to be a known animal carcinogen and a possible human carcinogen (Group 2B). Carbon black is encapsulated by resin and not expected to have adverse effects unless made airborne. Organosilane may cause liver injury with fibrosis after repeated and prolonged overexposure. Fillers are encapsulated and not expected to be released from product under normal conditions of use. Prolonged or repeated exposure to mineral spirits (petroleum naphtha or stoddard solvent) may cause defatting, drying, and irritation of the skin, dermatitis, central nervous system (CNS) effects, and adverse liver, kidney, and lung effects.

Target Organs: Skin, Eye, Ingestion

SECTION 3 - PRODUCT COMPOSITION

Chemical Name	CAS-No.	Weight %
Silicone polymer	NJ TSRN# 51721300-5110P	40.0 - 70.0
Distillates, petroleum, hydrotreated	64742-46-7	15.0 - 40.0

TREMSIL 200 ANODIZED ALUMINUM - 30 CTG

Version 2.0

Print Date 12/06/2013

REVISION DATE: 07/08/2012

middle		
Polydimethylsiloxane, trimethyl endcap	63148-62-9	10.0 - 30.0
Amorphous silica	7631-86-9	7.0 - 13.0
Ethyltriacetoxysilane	17689-77-9	1.0 - 5.0
Titanium dioxide	13463-67-7	1.0 - 5.0
Carbon Black	1333-86-4	- <1.0

SECTION 4 - FIRST AID MEASURES

Get immediate medical attention for any significant overexposure.

Inhalation	:	Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.
Eye contact	:	Flush with water for at least 15 minutes while holding eye lids apart. Get medical attention immediately.
Skin contact	:	Wash area of contact thoroughly with hand cleaner followed by soap and water. If irritation, rash or other disorders develop, get medical attention immediately.
Ingestion	:	Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.

SECTION 5 - FIRE FIGHTING MEASURES

Flash point	:	> 149 °C, > 300 °F
Method	:	Tag Closed Cup
Lower explosion limit	:	Not available.
Upper explosion limit	:	Not available.
Autoignition temperature	:	Not available.
Extinguishing media	:	If water fog is ineffective, use carbon dioxide, dry chemical or foam.
Hazardous combustion products	:	Smoke, fumes. Carbon monoxide and carbon dioxide can form.
Protective equipment for firefighters	:	Use accepted fire fighting techniques. Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA).
Fire and explosion conditions	:	This product not expected to ignite under normal conditions of use.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Use appropriate protective equipment. Avoid contact with material. Stop flow. Contain spill. Keep out of water courses. Absorb spill in sand, earth or other suitable material. Transfer to appropriate container for disposal.

SECTION 7 - HANDLING AND STORAGE

Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. Store in sealed containers in a cool, dry, ventilated warehouse location.

TREMSIL 200 ANODIZED ALUMINUM - 30 CTG
Version 2.0
REVISION DATE: 07/08/2012

Print Date 12/06/2013

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION
Personal protection equipment

- Respiratory protection : Wear NIOSH/MSHA approved vapor respirator with appropriate cartridge when the vapor concentration is expected to exceed exposure limits indicated on the MSDS. Follow manufacturer's directions for respirator use.
- Hand protection : Use suitable impervious rubber or vinyl gloves and protective apparel to reduce exposure.
- Eye protection : Use safety glasses if eye contact is likely.
- Protective measures : Use professional judgment in the selection, care, and use.
- Engineering measures : Use general ventilation and/ or local exhaust to reduce the airborne contaminant concentration below the exposure limit listed in the MSDS

Exposure Limits

Chemical Name	CAS Number	Regulation	Limit	Form
Amorphous silica	7631-86-9	ACGIH TWA:	3 mg/m3	Respirable particles.
		ACGIH TWA:	10 mg/m3	Inhalable particles.
		OSHA PEL:	15 mg/m3	Total dust.
		OSHA PEL:	5 mg/m3	Respirable fraction.
		OSHA TWA:	0.8 mg/m3	
Titanium dioxide	13463-67-7	ACGIH TWA:	10 mg/m3	
		OSHA PEL:	15 mg/m3	Total dust.
		OSHA TWA:	15 mg/m3	Total dust.
		OSHA TWA:	5 mg/m3	Respirable fraction.
Carbon Black	1333-86-4	ACGIH TWA:	3.5 mg/m3	
		OSHA PEL:	3.5 mg/m3	
		OSHA TWA:	15 mg/m3	Total dust.
		OSHA TWA:	5 mg/m3	Respirable fraction.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

- Form : Paste
- Color : Aluminum/Gray
- Odor : Pungent
- pH : Not available.
- Vapour pressure : Not available.
- Vapor density : NA
- Melting point/range : Not available.
- Freezing point : Not available.
- Boiling point/range : Not available.
- Water solubility : Insoluble

TREMSIL 200 ANODIZED ALUMINUM - 30 CTG

Version 2.0

Print Date 12/06/2013

REVISION DATE: 07/08/2012

Specific Gravity : 1.015 Average

% Volatile Weight : 0 %

SECTION 10 - REACTIVITY / STABILITY

Substances to avoid : Water, alcohols, strong oxidizing agents, strong acids and strong bases.Amines.

Decomposition products : Hydrolyzes slowly with water or moisture to form acetic acid.

Stability : Stable

Hazardous polymerization : Will not occur.

SECTION 11 - TOXICOLOGICAL INFORMATION

Amorphous silica, CAS-No.: 7631-86-9

Acute oral toxicity (LD-50 oral) 22,500 mg/kg (Rat) 15,000 mg/kg (Mouse)

SECTION 12 - ECOLOGICAL INFORMATION

No Data Available

SECTION 13 - DISPOSAL CONSIDERATIONS

Disposal Method : Waste not regulated under RCRA. Incinerate at EPA approved facility or dispose of waste in compliance with state and local regulations.

SECTION 14 - TRANSPORTATION / SHIPPING DATA**CFR / DOT:**

Not Regulated

TDG:

Not Regulated

IMDG:

Not Regulated

SECTION 15 - REGULATORY INFORMATION**North American Inventories:**

All components are listed or exempt from the TSCA inventory.



TREMSIL 200 ANODIZED ALUMINUM - 30 CTG

Version 2.0

Print Date 12/06/2013

REVISION DATE: 07/08/2012

This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

U.S. Federal Regulations:

SARA 313 Components : None present or none present in regulated quantities.

SARA 311/312 Hazards : Acute Health Hazard
Chronic Health Hazard

OSHA Hazardous Components :

Amorphous silica 7631-86-9
Titanium dioxide 13463-67-7
Carbon Black 1333-86-4

OSHA Status: Considered : Irritant
hazardous based on the Carcinogen
following criteria:

OSHA Flammability : IIIB

Regulatory VOC (less water and : 1 g/l
exempt solvent)

VOC Method 310 : 0 %

Chemical is listed as an IARC, NTP, OSHA, or ACGIH Carcinogen:
Carbon Black 1333-86-4

U.S. State Regulations:

MASS RTK Components : Amorphous silica 7631-86-9
Titanium dioxide 13463-67-7

Penn RTK Components : Silicone polymer NJ TSRN# 51721300-5110P
Distillates, petroleum, hydrotreated middle 64742-46-7
Polydimethylsiloxane, trimethyl endcap 63148-62-9
Amorphous silica 7631-86-9
Titanium dioxide 13463-67-7

NJ RTK Components : Silicone polymer NJ TSRN# 51721300-5110P
Distillates, petroleum, hydrotreated middle 64742-46-7
Polydimethylsiloxane, trimethyl endcap 63148-62-9
Amorphous silica 7631-86-9
Ethyltriacetoxysilane 17689-77-9
Carbon Black 1333-86-4

Components under California Proposition 65:

WARNING! Contains chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm

TREMSIL 200 ANODIZED ALUMINUM - 30 CTG

Version 2.0

Print Date 12/06/2013

REVISION DATE: 07/08/2012

SECTION 16 - OTHER INFORMATION
HMIS Rating :

Health	2
Flammability	1
Reactivity	0
PPE	

0 = Minimum
 1 = Slight
 2 = Moderate
 3 = Serious
 4 = Severe

Further information:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

Prepared by: Rich Mikol

Legend

ACGIH - American Conference of Governmental Hygienists

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

DOT - Department of Transportation

DSL - Domestic Substance List

EPA - Environmental Protection Agency

HMIS - Hazardous Materials Information System

IARC - International Agency for Research on Cancer

MSHA - Mine Safety Health Administration

NDSL - Non-Domestic Substance List

NIOSH - National Institute for Occupational Safety and Health

NTP - National Toxicology Program

OSHA - Occupational Safety and Health Administration

PEL - Permissible Exposure Limit

RCRA - Resource Conservation and Recovery Act

RTK - Right To Know

SARA - Superfund Amendments and Reauthorization Act

STEL - Short Term Exposure Limit

TLV - Threshold Limit Value

TSCA - Toxic Substances Control Act

TWA - Time Weighted Average

V - Volume

VOC - Volatile Organic Compound

WHMIS - Workplace Hazardous Materials Information System