



**DECKTITE 230 SL 4.9L of base, 2x.25L of c/a**

Version 2.0  
REVISION DATE: 07/08/2012

Print Date 07/09/2012

This is a kit that contains the following components:

THC 900 NEUTRAL BASE  
DECKTITE 230 SL CURATIVE



**THC 900 NEUTRAL BASE**Version 2.0  
REVISION DATE: 07/08/2012

Print Date 07/09/2012

**SECTION 1 - PRODUCT IDENTIFICATION**

Trade name : THC 900 NEUTRAL BASE  
Product code : 964230 802

COMPANY : Tremco Incorporated  
3735 Green Road  
Cleveland, OH 44122

Telephone : (216) 292-5000 8:30 - 5:00 EST  
Emergency Phone: : (216) 765-6727 8:30 - 5:00 EST  
After Hours: Chemtrec 1-800-424-9300

Product use : Coating

**SECTION 2 - HAZARDS IDENTIFICATION****Emergency Overview**

White. Liquid. May cause drowsiness, weakness, and fatigue. Vapor and/or mist may irritate nose and throat. May cause moderate irritation to the respiratory system. May cause allergic respiratory sensitization. Move to fresh air. If required, artificial respiration or administration of oxygen can be performed by trained personnel. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

**Acute Potential Health Effects/ Routes of Entry**

Inhalation : May cause drowsiness, weakness, and fatigue. Vapor and/or mist may irritate nose and throat. May cause moderate irritation to the respiratory system. May cause allergic respiratory sensitization.

Eyes : Vapor and/or mist may cause eye irritation.

Ingestion : May cause irritation to the mouth, throat and stomach. May cause gastrointestinal irritation, nausea, and vomiting.

Skin : May cause sensitization resulting in irritation, itching and redness.

**Aggravated Medical Conditions**

Pre-existing eye, skin, liver, kidney, and respiratory disorders may be aggravated by exposure.

**Chronic Health Effects**

Overexposure may cause dermatitis, asthma, skin and respiratory sensitization and decreased lung function. Repeated overexposure to vapors and/or material may injure the liver, kidneys and respiratory system unless suitable engineering controls and/or personal protective equipment are used. Prolonged or repeated exposure to xylene may cause defatting, drying, and irritation of the skin, dermatitis, central nervous system (CNS) effects, heart muscle sensitization and arrhythmia, hearing loss, and brain, liver, kidney damage. Xylene overexposure may affect fetal development. Prolonged or repeated exposure to butyl benzyl phthalate may cause reduced body weights and adverse effects on the liver, kidney, spleen, pancreas, and reproductive organs. The International Agency for Research on Cancer (IARC) has evaluated ethylbenzene and classified it as a possible human carcinogen (Group 2B) based on sufficient evidence for carcinogenicity in experimental animals, but inadequate evidence for cancer in exposed humans. Prolonged and repeated exposure to excessive airborne concentrations of talc can result in scarring of the lungs (pneumoconiosis) or the covering of the lungs (pleural thickening). Fillers are encapsulated and not expected to be released from product under

## THC 900 NEUTRAL BASE

Version 2.0

Print Date 07/09/2012

REVISION DATE: 07/08/2012

normal conditions of use. Prolonged or repeated exposure to mineral spirits (petroleum naphtha or stoddard solvent) may cause defatting, drying, and irritation of the skin, dermatitis, central nervous system (CNS) effects, and adverse liver, kidney, and lung effects.

**Target Organs:** Eye, Lung, Liver, Kidney, Skin, Nerve

### SECTION 3 - PRODUCT COMPOSITION

Chemical Name	CAS-No.	Weight %
Polyurethane Polymer	NJ TSRN# 51721300-5000P	30.0 - 60.0
Calcium Carbonate (Limestone)	1317-65-3	30.0 - 60.0
Talc	14807-96-6	10.0 - 30.0
Butyl benzyl phthalate	85-68-7	7.0 - 13.0
Stoddard solvent (Mineral Spirits)	8052-41-3	3.0 - 7.0
Xylene	1330-20-7	1.0 - 5.0
Ethylbenzene	100-41-4	0.1 - 1.0

### SECTION 4 - FIRST AID MEASURES

Get immediate medical attention for any significant overexposure.

Inhalation	:	Move to fresh air. If required, artificial respiration or administration of oxygen can be performed by trained personnel. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.
Eye contact	:	Flush with water for at least 15 minutes while holding eye lids apart. Get medical attention immediately.
Skin contact	:	Wash area of contact thoroughly with hand cleaner followed by soap and water. If irritation, rash or other disorders develop, get medical attention immediately.
Ingestion	:	Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.

### SECTION 5 - FIRE FIGHTING MEASURES

Flash point	:	116 °F, 47 °C
Method	:	Setaflash Closed Cup
Lower explosion limit	:	Not available.
Upper explosion limit	:	Not available.
Autoignition temperature	:	Not available.
Extinguishing media	:	If water fog is ineffective, use carbon dioxide, dry chemical or foam.
Hazardous combustion products	:	Carbon monoxide and carbon dioxide can form. Smoke, fumes. Hydrocyanic acid and nitrogen oxides can form.
Protective equipment for firefighters	:	Use accepted fire fighting techniques. Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA).

## THC 900 NEUTRAL BASE

Version 2.0

Print Date 07/09/2012

REVISION DATE: 07/08/2012

Fire and explosion conditions : Product may ignite if heated in excess of its flash point. Closed container, may burst when exposed to extreme heat. Empty containers may contain ignitable vapors. Vapors may travel to sources of ignition and flashback.

### SECTION 6 - ACCIDENTAL RELEASE MEASURES

Use appropriate protective equipment. Avoid contact with material. Remove sources of ignition immediately. Stop flow of material if safe to do so. Contain spill and keep out of water courses. Ventilate area.

### SECTION 7 - HANDLING AND STORAGE

Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. Change soiled work clothes frequently. Clean hands thoroughly after handling. Do not smoke, weld, generate sparks, or use flame near container. To prevent generation of static discharges, use bonding/grounding connection when pouring liquid. Extinguish all ignition sources including pilot lights, non-explosion proof motors and electrical equipment until vapors dissipate. Store under dry warehouse conditions away from heat and all ignition sources.

### SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

#### Personal protection equipment

- Respiratory protection : Wear appropriate, properly fitted NIOSH/MSHA approved respirator when airborne contaminant level(s) are expected to exceed exposure limits indicated on the MSDS. Select positive pressure supplied air respirator (TC19C or equivalent) for isocyanates.
- Hand protection : Use suitable impervious nitrile or neoprene gloves and protective apparel to reduce exposure.
- Eye protection : Wear appropriate eye protection. Wear chemical safety goggles and/or face shield to prevent eye contact. Do not wear contact lenses. Do not touch eyes with contaminated body parts or materials. Have eye washing facilities readily available.
- Skin and body protection : Prevent contact with shoes and clothing.
- Protective measures : Use professional judgment in the selection, care, and use.
- Engineering measures : Use only in well ventilated areas. Provide maximum ventilation in enclosed areas. Use local exhaust when the general ventilation is inadequate.

#### Exposure Limits

Chemical Name	CAS Number	Regulation	Limit	Form
Calcium Carbonate (Limestone)	1317-65-3	OSHA PEL:	5 mg/m <sup>3</sup>	Respirable fraction.
		OSHA PEL:	15 mg/m <sup>3</sup>	Total dust.
		ACGIH TWA:	3 mg/m <sup>3</sup>	Respirable particles.
		ACGIH TWA:	10 mg/m <sup>3</sup>	Inhalable particles.
		OSHA TWA:	15 mg/m <sup>3</sup>	Total dust.
		OSHA TWA:	5 mg/m <sup>3</sup>	Respirable fraction.

## THC 900 NEUTRAL BASE

Version 2.0

Print Date 07/09/2012

REVISION DATE: 07/08/2012

Chemical Name	CAS Number	Regulation	Limit	Form
Talc	14807-96-6	ACGIH TWA: OSHA TWA: OSHA TWA: OSHA PEL: OSHA PEL:	2 mg/m3 0.1 mg/m3 0.3 mg/m3 15 mg/m3 5 mg/m3	Respirable fraction. Respirable. Total dust. Total dust. Respirable fraction.
Stoddard solvent (Mineral Spirits)	8052-41-3	ACGIH TWA: OSHA PEL:	100 ppm 2,900 mg/m3	
Xylene	1330-20-7	ACGIH TWA: ACGIH STEL: OSHA PEL:	100 ppm 150 ppm 435 mg/m3	
Ethylbenzene	100-41-4	ACGIH TWA: ACGIH STEL: OSHA PEL:	100 ppm 125 ppm 435 mg/m3	

### SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Form	: Liquid
Color	: White
Odor	: Solvent
pH	: Not available.
Vapour pressure	: Not available.
Vapor density	: Heavier than air
Melting point/range	: Not available.
Freezing point	: Not available.
Boiling point/range	: Not available.
Water solubility	: Negligible
Specific Gravity	: 1.32
% Volatile Weight	: 6 %

### SECTION 10 - REACTIVITY / STABILITY

Substances to avoid	: Strong acids.Strong bases.Amines.Water or moisture.Alcohols.
Stability	: Material is stable under normal storage, handling, and use.
Hazardous polymerization	: Will not occur under normal conditions.

### SECTION 11 - TOXICOLOGICAL INFORMATION

Butyl benzyl phthalate, CAS-No.: 85-68-7	
Acute oral toxicity (LD-50 oral)	13,500 mg/kg ( Rat )

**THC 900 NEUTRAL BASE**

Version 2.0

Print Date 07/09/2012

REVISION DATE: 07/08/2012

Xylene, CAS-No.: 1330-20-7

Acute oral toxicity (LD-50 oral)

4,300 mg/kg ( Rat ) 1,590 mg/kg ( Mouse ) 6,670 mg/kg (

Rat ) 3,523 - 8,600 mg/kg ( Rat ) 5,627 mg/kg ( Mouse )

Acute inhalation toxicity (LC-50)

6,350 mg/l for 4 h ( Rat ) 3,907 mg/l for 6 h ( Mouse ) 8,000

mg/l for 4 h ( Rat )

Ethylbenzene, CAS-No.: 100-41-4

Acute oral toxicity (LD-50 oral)

5,460 mg/kg ( Rat ) 3,500 mg/kg ( Rat )

Acute dermal toxicity (LD-50 dermal)

17,800 mg/kg ( Rabbit )

**SECTION 12 - ECOLOGICAL INFORMATION**

No Data Available

**SECTION 13 - DISPOSAL CONSIDERATIONS**

RCRA Class : D001: Reportable Quantity = 100 lbs. (Characteristic of ignitability)

This classification applies only to the material as it was originally produced.

Disposal Method : Subject to hazardous waste treatment, storage, and disposal requirements under RCRA. Recycle or incinerate waste at EPA approved facility or dispose of in compliance with federal, state and local regulations.

**SECTION 14 - TRANSPORTATION / SHIPPING DATA****CFR / DOT:**

Not Regulated

**TDG:**

Not Regulated

**IMDG:**

Not Regulated

**SECTION 15 - REGULATORY INFORMATION****North American Inventories:**

All components are listed or exempt from the TSCA inventory.

This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

**U.S. Federal Regulations:**

**THC 900 NEUTRAL BASE**

Version 2.0

Print Date 07/09/2012

REVISION DATE: 07/08/2012

SARA 313 Components : Xylene 1330-20-7  
Ethylbenzene 100-41-4

SARA 311/312 Hazards : Acute Health Hazard  
Fire Hazard

## OSHA Hazardous Components :

Calcium Carbonate (Limestone) 1317-65-3  
Talc 14807-96-6  
Butyl benzyl phthalate 85-68-7  
Stoddard solvent (Mineral Spirits) 8052-41-3  
Xylene 1330-20-7  
Ethylbenzene 100-41-4

OSHA Status: Considered : Irritant  
hazardous based on the Sensitizer  
following criteria:

OSHA Flammability : II

When appropriately mixed with the other part, product has a VOC less water and exempt solvent of:  
102 g/l

Regulatory VOC (less water and : 85 g/l  
exempt solvent)

VOC Method 310 : 6 %

Chemical is listed as an IARC, NTP, OSHA, or ACGIH Carcinogen:

Butyl benzyl phthalate 85-68-7

**U.S. State Regulations:**

MASS RTK Components : Calcium Carbonate (Limestone) 1317-65-3  
Talc 14807-96-6  
Butyl benzyl phthalate 85-68-7  
Stoddard solvent (Mineral Spirits) 8052-41-3  
Xylene 1330-20-7  
2,4-Toluene diisocyanate 584-84-9  
Toluene-2,6-Diisocyanate 91-08-7

Penn RTK Components : Polyurethane Polymer NJ TSRN# 51721300-5000P  
Calcium Carbonate (Limestone) 1317-65-3  
Talc 14807-96-6  
Butyl benzyl phthalate 85-68-7  
Stoddard solvent (Mineral Spirits) 8052-41-3  
Xylene 1330-20-7

NJ RTK Components : Polyurethane Polymer NJ TSRN# 51721300-5000P  
Calcium Carbonate (Limestone) 1317-65-3  
Talc 14807-96-6  
Butyl benzyl phthalate 85-68-7  
Stoddard solvent (Mineral Spirits) 8052-41-3  
Xylene 1330-20-7

**THC 900 NEUTRAL BASE**

Version 2.0

Print Date 07/09/2012

REVISION DATE: 07/08/2012

WARNING! Contains chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm:

85-68-7	Butyl benzyl phthalate
100-41-4	Ethylbenzene
108-88-3	Toluene

**SECTION 16 - OTHER INFORMATION****HMIS Rating :**

Health	2
Flammability	2
Reactivity	0
PPE	

0 = Minimum  
 1 = Slight  
 2 = Moderate  
 3 = Serious  
 4 = Severe

**Further information:**

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

**Prepared by: Rich Mikol****Legend**

ACGIH - American Conference of Governmental Hygienists

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

DOT - Department of Transportation

DSL - Domestic Substance List

EPA - Environmental Protection Agency

HMIS - Hazardous Materials Information System

IARC - International Agency for Research on Cancer

MSHA - Mine Safety Health Administration

NDSL - Non-Domestic Substance List

NIOSH - National Institute for Occupational Safety and Health

NTP - National Toxicology Program

OSHA - Occupational Safety and Health Administration

PEL - Permissible Exposure Limit

RCRA - Resource Conservation and Recovery Act

RTK - Right To Know

SARA - Superfund Amendments and Reauthorization Act

STEL - Short Term Exposure Limit

TLV - Threshold Limit Value

TSCA - Toxic Substances Control Act

TWA - Time Weighted Average

V - Volume

VOC - Volatile Organic Compound

WHMIS - Workplace Hazardous Materials Information System



**DECKTITE 230 SL CURATIVE**Version 2.0  
REVISION DATE: 07/08/2012

Print Date 07/09/2012

**SECTION 1 - PRODUCT IDENTIFICATION**

Trade name : DECKTITE 230 SL CURATIVE  
Product code : 964230 802

COMPANY : Tremco Incorporated  
3735 Green Road  
Cleveland, OH 44122

Telephone : (216) 292-5000 8:30 - 5:00 EST  
Emergency Phone: : (216) 765-6727 8:30 - 5:00 EST  
After Hours: Chemtrec 1-800-424-9300

Product use : Curative

**SECTION 2 - HAZARDS IDENTIFICATION****Emergency Overview**

Amber. Liquid solution. May cause slight irritation to the respiratory system. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

**Acute Potential Health Effects/ Routes of Entry**

Inhalation : May cause slight irritation to the respiratory system.  
Eyes : Vapors or liquid may cause tearing, blurred vision, severe irritation, and possible chemical burns.  
Ingestion : May cause irritation to the mouth, throat and stomach. May cause chemical burns to stomach, mouth, nose, and throat.  
Skin : May cause moderate irritation. May cause sensitization resulting in irritation, itching and redness.

**Aggravated Medical Conditions**

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure.

**Chronic Health Effects**

Prolonged and repeated overexposure to amines may cause liver and kidney damage based on animal studies. Prolonged or repeated exposure to xylene may cause defatting, drying, and irritation of the skin, dermatitis, central nervous system (CNS) effects, heart muscle sensitization and arrhythmia, hearing loss, and brain, liver, kidney damage. Xylene overexposure may affect fetal development. The International Agency for Research on Cancer (IARC) has evaluated ethylbenzene and classified it as a possible human carcinogen (Group 2B) based on sufficient evidence for carcinogenicity in experimental animals, but inadequate evidence for cancer in exposed humans. Fillers are encapsulated and not expected to be released from product under normal conditions of use.

**Target Organs:** Skin, Eye, Lung

**SECTION 3 - PRODUCT COMPOSITION**

## DECKTITE 230 SL CURATIVE

Version 2.0

Print Date 07/09/2012

REVISION DATE: 07/08/2012

Chemical Name	CAS-No.	Weight %
Polyamido Amine	NJ TSRN# 51721300-5004P	> 60.0
Xylene	1330-20-7	7.0 - 13.0
Alkyl ether amine	NJ TSRN# 51721300-5166P	5.0 - 10.0
Ethylbenzene	100-41-4	1.0 - 5.0

### SECTION 4 - FIRST AID MEASURES

Get immediate medical attention for any significant overexposure.

Inhalation	:	Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.
Eye contact	:	Flush with water for 15 minutes. If irritation persists, get medical attention.
Skin contact	:	Wash area of contact thoroughly with hand cleaner followed by soap and water. If irritation, rash or other disorders develop, get medical attention immediately.
Ingestion	:	Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.

### SECTION 5 - FIRE FIGHTING MEASURES

Flash point	:	52 °C, 126 °F
Method	:	Pensky-Martens Closed Cup
Lower explosion limit	:	Not available.
Upper explosion limit	:	Not available.
Autoignition temperature	:	Not available.
Extinguishing media	:	If water fog is ineffective, use carbon dioxide, dry chemical or foam.
Hazardous combustion products	:	Carbon monoxide, carbon dioxide, and nitrogen oxides.
Protective equipment for firefighters	:	Use accepted fire fighting techniques. Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA).
Fire and explosion conditions	:	Product may ignite if heated in excess of its flash point.

### SECTION 6 - ACCIDENTAL RELEASE MEASURES

Stop flow. Contain spill. Keep out of water courses. Absorb spill in sand, earth or other suitable material. Transfer to appropriate container for disposal.

### SECTION 7 - HANDLING AND STORAGE

Store under normal warehouse conditions in sealed containers. Keep container closed when not in use. Vapor may migrate to sources of ignition. Do not smoke, weld, generate sparks, or use flame near container. Change soiled work clothes frequently. Clean hands thoroughly after handling. Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. Handle in compliance with common hygienic practices. Clean hands thoroughly after handling.

## DECKTITE 230 SL CURATIVE

Version 2.0  
REVISION DATE: 07/08/2012

Print Date 07/09/2012

### SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

#### Personal protection equipment

- Respiratory protection : Use full engineering controls before relying on personal protective equipment. Wear NIOSH/MSHA approved vapor respirator with appropriate cartridge when the vapor concentration is expected to exceed exposure limits indicated on the MSDS. Follow manufacturer's directions for respirator use.
- Hand protection : Protect hands with impervious gloves.
- Eye protection : Wear chemical safety goggles and/or face shield to prevent eye contact. Do not wear contact lenses. Do not touch eyes with contaminated body parts or materials. Have eye washing facilities readily available.
- Protective measures : Use professional judgment in the selection, care, and use.
- Engineering measures : Use local exhaust when the general ventilation is inadequate.

#### Exposure Limits

Chemical Name	CAS Number	Regulation	Limit	Form
Xylene	1330-20-7	ACGIH TWA: ACGIH STEL: OSHA PEL:	100 ppm 150 ppm 435 mg/m <sup>3</sup>	
Ethylbenzene	100-41-4	ACGIH TWA: ACGIH STEL: OSHA PEL:	100 ppm 125 ppm 435 mg/m <sup>3</sup>	

### SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

- Form : Liquid solution
- Color : Amber
- Odor : Solvent
- pH : Not available.
- Vapour pressure : Not available.
- Vapor density : Not available.
- Melting point/range : Not available.
- Freezing point : Not available.
- Boiling point/range : Not available.
- Water solubility : Negligible
- Specific Gravity : 0.98
- % Volatile Weight : 10 %

**DECKTITE 230 SL CURATIVE**Version 2.0  
REVISION DATE: 07/08/2012

Print Date 07/09/2012

**SECTION 10 - REACTIVITY / STABILITY**

Substances to avoid : Acids.

Stability : Stable under normal conditions. Avoid welding arcs, flames or other high temperature sources.

Hazardous polymerization : Will not occur under normal conditions.

**SECTION 11 - TOXICOLOGICAL INFORMATION**

Xylene, CAS-No.: 1330-20-7  
Acute oral toxicity (LD-50 oral) 4,300 mg/kg ( Rat ) 1,590 mg/kg ( Mouse ) 6,670 mg/kg ( Rat ) 3,523 - 8,600 mg/kg ( Rat ) 5,627 mg/kg ( Mouse )  
Acute inhalation toxicity (LC-50) 6,350 mg/l for 4 h ( Rat ) 3,907 mg/l for 6 h ( Mouse ) 8,000 mg/l for 4 h ( Rat )

Ethylbenzene, CAS-No.: 100-41-4  
Acute oral toxicity (LD-50 oral) 5,460 mg/kg ( Rat ) 3,500 mg/kg ( Rat )  
Acute dermal toxicity (LD-50 dermal) 17,800 mg/kg ( Rabbit )

**SECTION 12 - ECOLOGICAL INFORMATION**

No Data Available

**SECTION 13 - DISPOSAL CONSIDERATIONS**

RCRA Class : D001: Reportable Quantity = 100 lbs. (Characteristic of ignitability)  
This classification applies only to the material as it was originally produced.

Disposal Method : Subject to hazardous waste treatment, storage, and disposal requirements under RCRA. Recycle or incinerate waste at EPA approved facility or dispose of in compliance with federal, state and local regulations.

**SECTION 14 - TRANSPORTATION / SHIPPING DATA****CFR / DOT:**

Not Regulated

**TDG:**

Not Regulated

**IMDG:**

**DECKTITE 230 SL CURATIVE**Version 2.0  
REVISION DATE: 07/08/2012

Print Date 07/09/2012

Not Regulated

**SECTION 15 - REGULATORY INFORMATION****North American Inventories:**

All components are listed or exempt from the TSCA inventory.  
This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

**U.S. Federal Regulations:**

SARA 313 Components : Xylene 1330-20-7  
Ethylbenzene 100-41-4

SARA 311/312 Hazards : Acute Health Hazard  
Fire Hazard

## OSHA Hazardous Components :

Xylene 1330-20-7  
Ethylbenzene 100-41-4

OSHA Status: Considered : Irritant  
hazardous based on the  
following criteria:

OSHA Flammability : II

Regulatory VOC (less water and  
exempt solvent) : 102 g/l

VOC Method 310 : 10 %

**U.S. State Regulations:**

MASS RTK Components : Xylene 1330-20-7  
Ethylbenzene 100-41-4

Penn RTK Components : Polyamido Amine NJ TSRN# 51721300-5004P  
Xylene 1330-20-7  
Alkyl ether amine NJ TSRN# 51721300-5166P  
Ethylbenzene 100-41-4

NJ RTK Components : Polyamido Amine NJ TSRN# 51721300-5004P  
Xylene 1330-20-7  
Alkyl ether amine NJ TSRN# 51721300-5166P  
Ethylbenzene 100-41-4

WARNING! Contains chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm:

100-41-4 Ethylbenzene  
108-88-3 Toluene

**DECKTITE 230 SL CURATIVE**Version 2.0  
REVISION DATE: 07/08/2012

Print Date 07/09/2012

**SECTION 16 - OTHER INFORMATION****HMIS Rating :**

Health	3
Flammability	2
Reactivity	1
PPE	

0 = Minimum  
 1 = Slight  
 2 = Moderate  
 3 = Serious  
 4 = Severe

**Further information:**

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

**Prepared by: Rich Mikol****Legend**

ACGIH - American Conference of Governmental Hygienists

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

DOT - Department of Transportation

DSL - Domestic Substance List

EPA - Environmental Protection Agency

HMIS - Hazardous Materials Information System

IARC - International Agency for Research on Cancer

MSHA - Mine Safety Health Administration

NDSL - Non-Domestic Substance List

NIOSH - National Institute for Occupational Safety and Health

NTP - National Toxicology Program

OSHA - Occupational Safety and Health Administration

PEL - Permissible Exposure Limit

RCRA - Resource Conservation and Recovery Act

RTK - Right To Know

SARA - Superfund Amendments and Reauthorization Act

STEL - Short Term Exposure Limit

TLV - Threshold Limit Value

TSCA - Toxic Substances Control Act

TWA - Time Weighted Average

V - Volume

VOC - Volatile Organic Compound

WHMIS - Workplace Hazardous Materials Information System