



# COVERAGE SPRAY CHART

Built On The Principles Of Quality And Integrity

PRODUCT	PRODUCT NAME	COATS	COVERAGE *	PSI **	GAL/MIN	TIP SIZE	FAN ***
120	FIBERED ALUMINUM ROOF COATING	1	1-1.5 GAL	3000	1.5	.051-.067	6
126	NON-FIBERED ALUMINUM ROOF COATING	1	1 GAL	3000	1.5	.033-.067	6
360	NON-FIBERED ASPHALT EMULSION	2	2-8 GAL	3000	2-8 GAL	.0861<	6-12"
363	FIBERED ASPHALT EMULSION	2	2-8 GAL	1500	2-8 GAL	.0861<	6-12"
365	MODIFIED ASPHALT EMULSION	2	2-8 GAL	1500	2-8 GAL	.0861<	6-12"
901	WHITE ELASTOMERIC ROOF COATING	2	1-2 GAL	2000 MIN	4 GAL	.0631<	12-18"
911	ETERNALASTIC WHITE ELASTOMERIC ROOF COATING	2	1-2 GAL	2000 MIN	2 GAL	.0631<	12-18"
921	REFLEX WHITE ELASTOMERIC ROOF COATING	1	1-2 GAL	2000 MIN	3 GAL	.0631<	12-18"
960	ETERNALASTIC METAL PRIMER	1	1 GAL	1000	1 GAL	.025-.067	6-12"
980	ETERNALASTIC ACRYLIC ASPHALT PRIMER	1	1 GAL	1000	1 GAL	.025-.067	6-12"
990	ETERNALASTIC EPDM RINSEABLE PRIMER	1	.2 GAL	HUDSON SPRAYER	.20 PER SQR	HUDSON SPRAYER	HUDSON SPRAYER
4003	FIBERED RESATURANT & SEALER	1	3 GAL	1000	3 GAL	0.051	8"

\* COVERAGE IS PER COAT AND WILL VARY. CONSULT DATA SHEET AND/OR GUIDE SPECIFICATION FOR EXACT REQUIREMENTS.

\*\* TEMPERATURE OF CERTAIN PRODUCTS AND THE AMBIENT TEMPERATURE WILL GREATLY INFLUENCE SPRAYABILITY. SIZE OF HOSES, LENGTH OF HOSES AND ELEVATION OF WORK SURFACE VS. SPRAY RIG WILL AFFECT SPRAYABILITY.

\*\*\* DESIRED FAN WIDTH MAY VARY DEPENDING UPON APPLICATION.

FLORIDA  
1904 SW 31ST AVE  
HALLANDALE, FL 33009  
800.432.2855

CALIFORNIA  
14435 MACAW STREET  
LA MIRADA, CA 90638  
877.827.2622

TEXAS  
1225 BRAI DRIVE  
PORT ARTHUR, TX 77640  
866.727.0091