

For all types of interior repairs on plaster, drywall, wood and concrete

- Ready to use
- Fast drying
- Applies easily with a putty knife
- Creates a hard, durable finish



Description

SHEETROCK Spackling Compound is an all-purpose patching compound for general repair before painting or decorating. Fills and conceals nail holes, cracks, scars and other imperfections in plaster, gypsum panel, wood and concrete surfaces.

For interior use only.

Preparation

Use directly from container; no mixing or thinning required. Maintain a minimum temperature of 55 °F (13 °C). Provide adequate ventilation to carry off excess moisture.

Application

Apply with a putty knife. For shallow cracks, one application is sufficient. For deep cracks, two thin applications will produce better results. Allow compound to dry thoroughly between applications.

Sand smooth when compound is hard and dry.

Spackling Compound

Drying Time

Compound hardens within a few hours. Allow extra drying time during periods of high humidity and/or low temperature.

Decorating

Surface must be completely dry and free of dust and sandpaper residue. Apply any standard primer and decoration.

Cleanup

Clean tools and containers with soap and water immediately after use.

Packaging

Available in 1 pt., 1 qt. and 1 gal. pails.

WARNING

When mixed with water, this material hardens and then slowly becomes hot. DO NOT attempt to make a cast enclosing any part of the body using this material. Failure to follow these instructions may cause severe burns that may require surgical removal of affected tissue. Avoid eye contact or inhalation of dust. Wear eye protection. If eye contact occurs, flush thoroughly with water for 15 minutes. If irritation persists, consult physician. If dry sanding or if dusty, wear a NIOSH/MSHA-approved respirator. Dust can cause eye, nose, throat or respiratory irritation. Avoid creating dust by wet sanding. Long-term breathing of large amounts of mica can cause lung disease. Do not ingest. If there is any discomfort, consult a physician. Product safety information: (800) 507-8899.

KEEP OUT OF REACH OF CHILDREN.

Trademarks: The following trademarks used herein are owned by United States Gypsum Company or a related company: SHEETROCK, USG.

Note: Products described here may not be available in all geographic markets. Consult your U.S. Gypsum Company sales office or representative for information.

Notice: We shall not be liable for incidental and consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instructions or for other than the intended use. Our liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days from date it was or reasonably should have been discovered.

For product information: (800) USG-4YOU (874-4968).

United States Gypsum Company

125 South Franklin Street
P.O. Box 806278
Chicago, IL 60680-4124
A Subsidiary of USG Corporation

J1107/9-95
Printed in U.S.A.
© 1995, United States Gypsum Company

