

USG SHEETROCK® BRAND TEXTURE 1 SAND FINISH TEXTURE PAINT

PROVIDES A FINE, LIGHT SAND FINISH
TO INTERIOR WALLS AND CEILINGS

- Interior white latex texture paint that can be sprayed, brushed or roller applied
- Dries to a hard, durable, natural white finish
- Conceals minor surface defects
- Applies quickly and easily



Fine Sand

DESCRIPTION

Formulated to provide a fine, uniform texture over interior surfaces of gypsum drywall, plaster, concrete, wood, and other materials. Swirl patterns and other designs may be created by using a paint brush or texturing brush. Gives a durable, natural white finish.

ADVANTAGES

Classic Texture: Subtle, versatile light sand finish.

Easy to Use: Applied with spray, roller or brush.

Economical: Fast, low-cost application with coverage up to 200 sq. ft. per gallon.

LIMITATIONS

1. During application, avoid drafts and maintain minimum temperature of 55°F (13°C) within working areas.
2. Use fresh material. Store in a dry location at room temperature. Protect from freezing.
3. Do not exceed recommended water proportions.
4. Do not intermix with paints or other materials.

DIRECTIONS

SURFACE PREPARATION

Substrate must be sound, dry, clean, and free of oil, grease, mildew, efflorescence, and other foreign materials and/or contaminants. Product, air, and surface temperatures must be maintained at a minimum of 55°F (13°C) throughout the finishing process when using joint compound, primer and texture products.

NEW DRYWALL

Treat joints and nailheads with an appropriate USG joint treatment system.

NEW CONCRETE/PLASTER

Age at least 60 days before texturing. Remove form oils and efflorescence and grind down form lines. Fill cracks and holes, and level concrete surfaces with USG Sheetrock® Brand Durabond® Setting-Type Joint Compound, USG Sheetrock® Brand Easy Sand™ Lightweight Setting-Type Joint Compound or USG Cover Coat® Compound and let dry.

PAINTED SURFACES

Lightly sand to dull any sheen and develop “tooth” for good bond. Wash surface with a strong detergent from the bottom up to remove any dust, dirt or sheen. A strong solution of TSP (trisodiumphosphate) works best. Follow manufacturer’s directions on the container.

Note: Texturing over previously painted, textured, or stained substrates may require application(s) of a stain-blocking sealer to obtain uniform color (check manufacturer’s instructions for stain containment instructions). Prevent rust stains by spot-priming bare metal with a good rust-inhibitive primer and let dry prior to the full surface priming.

SUBSTRATE PRIMING

Application of a prime coat is necessary to equalize surface porosity. After prepared surfaces have thoroughly dried, apply a prime coat of USG Sheetrock® Brand First Coat™ Primer flat latex paint or a good quality interior latex flat wall paint with high solids content. Prime coat should be applied undiluted and allowed to dry before decorating.

MIXING

If necessary, adjust consistency by slowly adding water, maximum one pint per gallon of product. Avoid overthinning. Mix until consistency is smooth and uniform.

Note: Overthinning may cause poor adhesion, lack of hide, and unequal suction when dry. Do not intermix with paints or other materials.

APPLICATION

Apply USG Sheetrock® Brand Texture 1 Sand Finish Texture Paint when air, water, mix, and surface temperatures are above 55°F (13°F). Using a roller or brush, apply generously in long strokes. Cross-roll adjoining areas to prevent ridging and framing.

Note: Avoid drafts during application; provide ventilation when work is complete.

DRYING TIME

At 72°F, 50% relative humidity, allow two to four hours. Wait overnight before overcoating.

COVERAGE

Five gallons covers up to approximately 1,000 sq. ft. (93 sq. m) based on use over smooth, hard surfaces. Masonry, textured, rough, and porous surfaces will require more product.

CLEANUP

Clean hands and equipment with warm, soapy water before texture hardens.

PRODUCT DATA

Color	White. May be painted after drying.
Dilution (water)	Up to one pint per gallon.
pH	9.2 to 9.5.
Drying Time	At 72°F, 50% relative humidity, dries in two to four hours.
Coverage	Up to 200 sq. ft. per gal.
Storage	Close container after each use. Store in dry place at room temperature. Protect from freezing. Rotate stock on a first-in, first-out basis.
Shelf Life	Up to nine months shelf life under good storage conditions.
Packaging	One and five gallon pails.
Coating VOC	6 g/L.

PRODUCT INFORMATION

See usg.com for the most up-to-date product information.

WARNING

Spraying mist or dust created from product may cause eye, skin, nose, throat, or respiratory irritation. Avoid inhalation of mist or dust. Wear a NIOSH/MSHA-approved respirator when dusty or misty or if spray applying. Use proper ventilation to reduce mist/dust exposure. Wear eye protection. If eye contact occurs, immediately flush thoroughly with water for 15 minutes. If irritation persists, call physician. Wear long-sleeved work clothing to prevent skin irritation. Wash thoroughly with soap and water after use. Do not ingest. If ingested, call a physician. Product safety information: 800 507-8899.
KEEP OUT OF REACH OF CHILDREN.

TRADEMARKS

The trademarks USG, COVER COAT, DURABOND, EASY SAND, FIRST COAT, SHEETROCK, IT'S YOUR WORLD. BUILD IT., the USG logo, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates.

NOTICE

We shall not be liable for incidental or consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instruction or for other than the intended use. Our liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days from date it was or reasonably should have been discovered.

NOTE

All products described here may not be available in all geographic markets. Consult your local sales office or representative for more information.

SAFETY FIRST!

Follow good safety and industrial hygiene practices during handling and installing all products and systems. Take necessary precautions and wear the appropriate personal protective equipment as needed. Read material safety data sheets and related literature on products before specification and/or installation.

SUBMITTAL APPROVALS

Job Name	
Contractor	Date

800 USG.4YOU
800 (874-4968)
usg.com

Manufactured by
United States Gypsum Company
550 West Adams Street
Chicago, IL 60661

J2117/rev. 2-15
© 2015 USG Corporation and/or
its affiliates. All rights reserved.
Printed in U.S.A.

USG
IT'S YOUR WORLD. BUILD IT.™