

# Olympia Micro™ ClimaPlus™ Performance

10

Year Availability

4211, 4221, 4231, 4411, 4421, 4742, 4744

HRC

High Recycled Content



USG



OLYMPIA MICRO Panels with *CLIMAPLUS* Performance/  
DOWN FINELINE DXF Suspension System

See LEED report tool at [usgdesignstudio.com](http://usgdesignstudio.com)  
for detailed sustainability information.

#### Features and Benefits

- Non-directional pattern reduces installation time and waste.
- Economical, fine-textured panel.
- Excellent light reflective finish (LR-.86) reduces light fixtures and energy use.
- Available in Optimized Recycled Content formulations to help maximize LEED recycled content contribution.
- USDA Certified Biobased Product?
- Available with .60 NRC.
- *CLIMAPLUS*™ 30-year lifetime system warranty against visible sag, mold and mildew.

#### Applications

- Offices
- Classrooms
- Reception/Lobby areas
- Hotels
- Conference areas
- Retail stores

#### Substrate

- Wet-formed mineral fiber

To order samples, go to [usg.com](http://usg.com)



Flat White  
050

Fine-Textured Panel



# Olympia Micro™

## ClimaPlus™ Performance

To order samples/literature:

Web: [usg.com](http://usg.com)  
 E-mail: [samplit@usg.com](mailto:samplit@usg.com)  
 Fax: 888.874.2348

Technical Services:  
 800 USG.4YOU (800.874.4968)

Websites:

[usg.com](http://usg.com)  
[usgdesignstudio.com](http://usgdesignstudio.com)  
 For the most up-to-date  
 technical information:  
[usgdesignstudio.com](http://usgdesignstudio.com)



	Edge	Panel Size	Class	Item No.	UL Classified							Recycled Content <sup>1</sup>					Panel Cost	
					NRC <sup>5</sup>	CAC Min.	LR <sup>2</sup>	Color	Grid Options	VOC Emissions	Anti-Mold & Mildew	Total	PC	PI	LEED RC			
<b>OLYMPIA MICRO™ unperforated</b>	SQ	2'x2'x5/8"	Class A	4210	—	35	.86	White	A, B, C	Low	●	44.9%	14.5%	30.5%	29.7%	\$		
		2'x4'x5/8"	Class A	4913	—	35	.86	White	A, B	Low	●	44.9%	14.5%	30.5%	29.7%	\$		
<b>OLYMPIA MICRO Panels .50 NRC</b>	SQ	2'x2'x5/8"	Class A	4211	.50	30	.86	White	A, B, C	Low	●	44.9%	14.5%	30.5%	29.7%	\$		
		2'x4'x5/8"	Class A	4411	.50	30	.86	White	A, B	Low	●	44.9%	14.5%	30.5%	29.7%	\$		
		2'x4'x5/8"	Class A	4411HRC	.50	30	.86	White	A, B	Low	●	54.5% HRC	45.4%	9.1%	49.9%	\$		
	SLT	2'x2'x5/8"	Class A	4221	.50	35	.86	White	D	Low	●	44.9%	14.5%	30.5%	29.7%	\$		
		2'x2'x5/8"	Class A	4221HRC	.50	35	.86	White	D	Low	●	54.5% HRC	45.4%	9.1%	49.9%	\$		
		2'x4'x5/8"	Class A	4421	.50	35	.86	White	D	Low	●	44.9%	14.5%	30.5%	29.7%	\$		
		2'x4'x5/8"	Class A	4421HRC	.50	35	.86	White	D	Low	●	54.5% HRC	45.4%	9.1%	49.9%	\$		
	FLB	2'x2'x5/8"	Class A	4231	.50	35	.86	White	E, F, G, H	Low	●	44.9%	14.5%	30.5%	29.7%	\$		
		2'x2'x5/8"	Class A	4231HRC	.50	35	.86	White	E, F, G, H	Low	●	54.5% HRC	45.4%	9.1%	49.9%	\$		
	2'x4'x5/8"	Class A	4431	.50	35	.86	White	E, F, G, H	Low	●	44.9%	14.5%	30.5%	29.7%	\$			
<b>OLYMPIA MICRO Panels .60 NRC</b>	SQ	2'x2'x3/4"	Class A	4750	.60	33	.86	White	A, B, C	Low	●	61% HRC	14%	46.9%	37.5%	\$		
		2'x4'x3/4"	Class A	4751	.60	33	.86	White	A, B	Low	●	61% HRC	14%	46.9%	37.5%	\$		
	SLT	2'x2'x3/4"	Class A	4752	.60	35	.86	White	D	Low	●	61% HRC	14%	46.9%	37.5%	\$		
		2'x4'x3/4"	Class A	4753	.60	35	.86	White	D	Low	●	61% HRC	14%	46.9%	37.5%	\$		
	FLB	2'x2'x3/4"	Class A	4754	.60	35	.86	White	E, F, G, H	Low	●	61% HRC	14%	46.9%	37.5%	\$		
		2'x4'x3/4"	Class A	4755	.60	35	.86	White	E, F, G, H	Low	●	61% HRC	14%	46.9%	37.5%	\$		
<b>OLYMPIA MICRO ILLUSION™ Two/24 Panels</b> The look of 2'x2' panels	SLT <sup>3</sup>	2'x4'x3/4"	Class A	4742	.50	35	.86	White	D	Low	●	44.9%	14.5%	30.5%	29.7%	\$		
	ILT <sup>4</sup>	2'x4'x3/4"	Class A	4744	.50	35	.86	White	I, J	Low	●	44.9%	14.5%	30.5%	29.7%	\$		

### ILLUSION Two/24

### Patterns



### Legend

#### Low Emissions (VOC)

Low-emitting performance meets CA Specification 01350 (CA Dept. of Health Services Standard Practice for the testing of VOC emissions) and is listed on the CHPS database for low-emitting materials. USG Certificate of Compliance for Low VOC Emissions also available on [usg.com](http://usg.com).

#### ClimaPlus Warranty Performance<sup>6</sup>

Contains a broad spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mold and mildew. Includes sag resistance performance.

#### High Recycled Content

Classified as containing greater than 50% total recycled content. Total recycled content is based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

#### ≥ .85 LR

Grid Profile Options	A DX®/DXL™	B DXW™	C <sup>7</sup> CENTRICITEE™ DXT™	D DX/DXL	E CENTRICITEE DXT	F IDENTITEE™ DXI™	G FINELINE® DXF™	H FINELINE 1/8 DXFF™	I CENTRICITEE DXT	J IDENTITEE DXI

### Physical Data/ Footnotes

**Product literature**  
Data sheet: SC2180

**ASTM E1264 classification**  
Type III, Form 2, Pattern CE

**ASTM E84 surface burning characteristics**  
Class A  
Flame spread: 25  
Smoke developed: 50

**Weight**  
0.78–1.03 lbs./sq. ft.

**Thermal resistance**  
R-1.4 (5/8" panels)  
R-1.7 (3/4" panels)

**Maximum backloading**  
See USG 30-Year Limited Warranty Commercial Applications SC2102.

**Maintenance**  
Can be cleaned easily with a soft brush or vacuum.

### Notes

- For details, see LEED report tool at [usgdesignstudio.com](http://usgdesignstudio.com).
- LR values are shown as averages.
- Panels have 15/16" routing.
- Panels have 9/16" routing.
- Mixing .50 and .60 NRC panels in the same ceiling plane is not recommended.
- For details, see Ceiling Systems Limited Warranty Commercial Applications

(SC2102) and ClimaPlus Ceilings Certification of Performance (SC2451).  
 7. This product has achieved both BioPreferred initiatives: Federal Procurement Preference and Certified Product Labeling. See the complete listing of all USG ceiling panels on [biopreferred.gov](http://biopreferred.gov) website.



Manufactured by USG Interiors, LLC  
 550 West Adams Street  
 Chicago, IL 60661

The following are trademarks of USG Interiors, LLC or a related company: CENTRICITEE, CLIMAPLUS, DOWN, DX, DXF, DXFF, DXI, DXL, DXT, DXW, FINELINE, IDENTITEE, ILLUSION, OLYMPIA MICRO, USG.

Safety First! Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read MSDS and literature before specification and installation.

SC2180/rev. 12-14  
 © 2014 USG Interiors, LLC  
 Printed in U.S.A.