Warranties and Limitations



Page 1 of 4

Lifetime (30-Year) Limited Warranty

All USG Donn brand suspension systems, when used with any USG ceiling panels or tiles or SHETROCK brand gypsum lay-in ceiling panels, carry a lifetime (30-year) warranty that our products shall be free from manufacturing defects and that the suspension systems shall be free from the occurrence of 50% red rust as defined by ASTM D610 test procedures for 30 years from the date of installation.

USG ceiling panels and tiles with *CLIMAPLUS* performance are specially formulated to endure environments with up to 100% relative humidity and temperatures up to 104 °F. These panels carry a limited warranty against visible sag for 30 years when installed in a DONN suspension system.

Sag resistance is measured under 'Standard Test Method for Strength Properties of Pre-fabricated Architectural Acoustical Tile or Lay-in Ceiling Panels', ASTM C367-05. The Test Method cautions (Section 17.3) that it "is not designed to establish the expected performance of the ceiling panels under field conditions of use, but only the sag properties for the specific temperature, humidity, exposure time and mounting conditions used in the test.

Neither this Test Method nor any other laboratory test we are aware of can predict long-term sag resistance. We do know that the higher the relative humidity and temperature, and the longer the time these conditions prevail, the more susceptible to sag are the ceiling panels. Nevertheless, USG has offered sag resistant ceiling panels for more than 20 years, and we have very rarely received sag complaints. This excellent field performance is expected because the formulations of both core and/or backing, depending on the particular panel, inherently impart sag resistance. Avoidance of extreme temperature and humidity conditions and regular cleaning will enhance sag resistance and all other performance attributes of the ceiling panels.

USG CLIMAPLUS ceiling panels with Superior Performance are warranted to be free from the growth of mold, mildew, and Gram-positive and Gram-negative odor- and stain-causing bacteria for 30 years from the date of installation. These ceiling panels include an antimicrobial treatment on the painted surface that contains a mold-inhibiting agent that provides broad-spectrum control for the growth of mold and mildew over the warranty period; these ceiling panels also resist the growth of Gram-positive and Gram-negative odor and stain causing bacteria. CLIMAPLUS fiberglass panels and RADAR Ceramic CLIMAPLUS ceiling panels do not have Superior Performance antimicrobial treatment; they are warranted to be free from the growth of mold, mildew, and odor- and stain-causing bacteria for 30 years from the date of installation due to the inherent characteristics of the products.

CLEAN ROOM *CLIMAPLUS* and SHEETROCK *CLIMAPLUS* gypsum lay-in panels do not feature the Superior Performance antimicrobial treatment and therefore are not included in the 30-Year Antimicrobial System Warranty.

All USG limited warranties are subject to use under normal conditions. Abnormal conditions include exposure to chemical fumes, vibrations, moisture from conditions such as leaks or condensation, excessive humidity, or excessive dirt or dust buildup.

By "lifetime" we mean the useful life of the ceiling system, up to a maximum of 30 years.

Page 2 of 4					
	The CLIMAPLUS warranty periods for these and other USG productions are considered to the control of the control	ducts and systems are as f	ollows:		
Warranties	Ceiling Systems	Panel/Tile	Suspension System		
	CLIMAPLUS Panels & Tile plus Donn Suspension System	Lifetime 30 Years	Lifetime 30 Years		
	All other USG Ceiling Panels & Tile plus Donn Suspension System	1 Year	Lifetime 30 Years		
	USG Specialty Ceilings	1 Year			
	la management	1			
	Individual Products	Panel/Tile	Suspension System		
	CLIMAPLUS Panels & Tile	10 Years			
	All Other USG Ceiling Panels & Tile	1 Year			
	Down Suspension Systems		10 Years		
	All warranties are subject to the following terms and conditions:				
Vho is covered?	Except where stated otherwise on specific product warranties, all USG warranties cover the original owner of the				
	building at the time of installation.				
/hat will USG do?	In the unlikely event of product performance failure at our election LICC will replace the goods or we will refund or				
viiat wiii 03a uo:	In the unlikely event of product performance failure, at our election USG will replace the goods or we will refund or credit an amount equal to the (original) purchase price of the goods within warranted conditions.				
	credit an amount equal to the (original) purchase price of the goods within warranted conditions.				
	The building owner is responsible for all costs associated with removal and installation.				
What does this warranty not cover?	All ceiling products and systems must be installed and maintained in accordance with current USG written				
	instructions and best industry practice, including the CISCA Handbook and ASTM C636, "Standard Practice for				
	Installation of Metal Ceiling Suspension Systems for Acoustical Tile and Lay-In Panels." Sheetrock Gypsum				
	Panels used with the USG Drywall Suspension System are not covered.				
	Also, you must observe the following:				
	 Care must be taken that the products are not damaged during delivery and while they are stored at the job site. 				
	The products must always be protected from vibration, direct contact with water including condensation, and chemical content in the products are not damaged during actively and white they are stored at the job site. The products must always be protected from vibration, direct contact with water including condensation, and chemical content in the products are not damaged during actively and white they are stored at the job site.				
	cal fumes, both before and after installation.				
	These products may not be used in exterior applications. The only exception is RADAR Ceramic CLIMAPLUS, These products may not be used in exterior applications. The only exception is RADAR Ceramic CLIMAPLUS,				
	which may be used in exterior soffits.				
	,				
	Except for ceilings with Superior Performance, CLIMAPLUS fiberglass ceiling panels and RADAR Ceramic CLIMAPLUS ceil-				
	ing panels, the growth of mold or bacteria is not covered by this warranty nor is it the responsibility of USG.				
	All products should be maintained to avoid excessive dirt or dust buildup or the presence of excessive moisture that				
	would provide a medium for microbial growth on ceiling panels.				
	Demons that may approximate the protections fire upday for the protection and the protection of the pr				
	Damage that may occur from vibrations, fire, water, freezing temperature, accident, any form of abuse or				
	exposure to Abnormal Conditions is not covered in this warranty. If subject to Abnormal Conditions, the products should be removed immediately and replaced once the conditions are normal.				
	Should be removed infinediately and replaced once the cond	nuono ait nonnal.			

Warranties and Limitations

Page 3 of 4			
Warranta O and History	All calling products and suppossing	a quatama must be installed and maintained in accordance with LICC written	
Warranty Conditions	All ceiling products and suspension systems must be installed and maintained in accordance with USG written installation instructions for that product in effect at the time of installation and best industry practice. Prior to, during, and after installation, the ceiling product must be kept clean and dry, and maintained in an environment free of chemical fumes or vibration, not subject to Abnormal Conditions and within the following conditions:		
	Performance Level	Environmental Limitations	
	RADAR Ceramic CLIMAPLUS	60-104°F (16-40°C) Up to 100% RH	
	CLIMAPLUS Ceilings	60-104°F (16-40°C) up to 95% RH	
	Standard Commercial Ceilings	60-85°F (16-29°C) up to 70% RH	
	ceiling product is exposed to enviro and up to 100% RH, including stan either AX or ZXLA suspension syste	g panels: The sag performance warranty extends to installations where the onments subject to temperatures of 60-104°F (16-40°C), chemical fumes, steam, ding water applications, so long as the product is installed with ems. For swimming pools, install only with AX or ZXLA suspension systems. arking garages, install with ZXLA suspension system (wind uplift should be	
	must be maintained to avoid excesthese panels or tiles. Microbial pro	s CLEAN ROOM <i>CLIMAPLUS</i> and SHEETROCK gypsum lay-in panels): These ceilings sive dirt or dust buildup that would provide a medium for microbial growth on tection does not extend beyond the treated surface as received from the materials that contact the treated surface such as supported materials.	
Suspension Systems	Prior to, during, and after installation, the suspension systems (excluding DXLA, AX, ZXLA and the USG drywall suspension system) shall be maintained in a temperature range of 60-104 °F (16-40 °C) and relative humidity shall not exceed 90%. DXLA shall be maintained in a temperature range of 60-104 °F (16-40 °C) and relative humidity shall not exceed 95%. AX, ZXLA and the USG Drywall Suspension System shall be maintained in a temperature range from 60-104 °F (16-40 °C) and relative humidity can be up to 100%. The warranty does not cover rusting that occurs from building leaks or condensation.		
General notes	it should be no heavier than 0.26 lb be applied perpendicular to the sus insulation. Insulation is also not rec	d to support any material including insulation. Where insulation must be used, os./sq. ft. and installed with the following USG recommendations: insulation must spension cross tees with the suspension system supporting the weight of the ommended to be used as follows: Firecode applications, unless specified and use ories, Inc. Mold or mildew growth on insulation or placed above the by this warranty.	
	This warranty does not cover dama wear and tear.	ge caused by fire, water, accident, or by any form of abuse except normal	
	systems. Please note that not all pr	s about proper maintenance, touch up, and repainting of our ceiling oducts can be repainted and that repainting will affect acoustical	

Note

or tiles.

1. RADAR Ceramic ceiling panels with CLIMAPLUS performance will withstand corrosive chemical fumes and contain coatings and/or a formulation to inhibit or retard the growth of mold and mildew.

performance, appearance, microbial resistance, fire resistance, and ventilation through the ceiling panels

Page 4 of 4	
	Normal environmental conditions must prevail to warrant product performance. This warranty will not cover situations where the panels are subject to vibrations or chemical fumes or where moisture comes in contact with the ceiling panel or tile as a result of a leaking roof, a sweating pipe, a leaking radiator, a flood, condensation on windows, condensation on more subtle surfaces where dew points are reached, humidified air from the HVAC system or any other similar causes.
How do you get service?	You must notify USG of the problem within 30 days of the time the problem first became apparent to you at the following address: USG, 550 West Adams Street, Chicago, IL 60661. Please send us any photographs of the problem area as these are often helpful. (Or, call us at 800 950.3839.) We will contact you within 30 days and, if we authorize a replacement or payment, that will be done within 30 days thereafter.
How does state law apply?	This warranty gives you specific legal rights and you may also have other rights, which vary from state to state. Replacement or refunding the purchase price of defective material shall constitute the sole and total obligation of USG. We shall not be responsible for any labor charges or other installation or replacement costs or for incidental or consequential damages of any nature whatsoever. THIS WARRANTY IS IN LIEU OF AND EXCLUDES ALL OTHER WARRANTIES NOT EXPRESSLY SET FORTH HEREIN, WHETHER IMPLIED BY OPERATION OF LAW OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS.

