



### Features

- ✓ 4 1/2" frame depth with polyurethane thermal barrier
- ✓ AAMA AW60 Performance Class
- ✓ Low maintenance and smooth operation
- ✓ "Inside slide" design with flush exterior screen track
- ✓ Available in half slide, center slide, end slide or center open configurations
- ✓ Accepts 1" insulating glass; bead glazed
- ✓ Sturdy corner-blocked and crimped door leaf construction
- ✓ Adjustable grease-packed ball bearing rollers
- ✓ Hinged or lift-off access doors optional
- ✓ 5/8" between-glass Venetian blinds available
- ✓ Head and jamb receptors available
- ✓ Offered through Advantage by Wausau
- ✓ NFRC labeled
- ✓ Recycled aluminum framing available upon request

### Performance

<b>Allowable Air</b>
0.30 cfm/sqft at 6.24 psf
<b>Water</b>
12 psf
<b>NFRC U-Factor</b>
0.47 to 0.67 BTU/hr.sqft. °F
<b>CRF<sub>f</sub></b>
49 to 53
<b>STC</b>
33 to 38



DISCLAIMER: Wausau Window and Wall Systems takes no responsibility for product selection or application, including, but not limited to, compliance with building codes, safety codes, laws, merchantability or fitness for a particular purpose; and further disclaims all liability for the use, in whole or in part, of this Technical Guide in preparation of project specifications and/or other documents. Technical Guides are subject to change at any time, without notice, and at Wausau's sole discretion. ©2009 Wausau